

Chapter Trans 300

TRANSPORTATION OF SCHOOL CHILDREN

Trans 300.01 Purpose and scope.
Trans 300.02 Definitions.

Subchapter I—Purchasing and Operating Requirements

Trans 300.10 Manufacturer.
Trans 300.11 Dealer.
Trans 300.12 Distributor.
Trans 300.13 Purchaser.
Trans 300.15 Employer requirements.
Trans 300.16 Driver requirements.
Trans 300.17 Passengers.
Trans 300.18 Out of service.
Trans 300.19 Requirements to convert a school bus.
Trans 300.20 Adoption of standards.
Trans 300.21 Rebody requirements.
Trans 300.22 Charter operations.

Subchapter II—Equipment Standards

Trans 300.25 Aisle.
Trans 300.26 Alternator, generator.
Trans 300.27 Barriers.
Trans 300.28 Battery.
Trans 300.29 Battery carrier and connections.
Trans 300.30 Book racks.
Trans 300.31 Brakes.
Trans 300.32 Bumpers.
Trans 300.33 Capacity.
Trans 300.34 Color.
Trans 300.35 Construction.
Trans 300.355 Crossing gate.
Trans 300.36 Defroster.
Trans 300.37 Drive shaft.
Trans 300.38 Emergency warning equipment.
Trans 300.39 Emergency exits.
Trans 300.40 Exhaust system.
Trans 300.41 Fire extinguisher.
Trans 300.42 First aid kit.
Trans 300.43 Fenders.
Trans 300.44 Floor covering.
Trans 300.45 Frame.
Trans 300.46 Fuel tank and fuel system integrity.
Trans 300.47 Heaters.

Trans 300.48 Horn.
Trans 300.49 Inside height.
Trans 300.50 Insulation.
Trans 300.51 Instruments, gauges.
Trans 300.52 Interior.
Trans 300.53 Ladders.
Trans 300.54 Lights, lamps, and reflectors.
Trans 300.55 Mirrors.
Trans 300.56 Mounting of body.
Trans 300.57 Openings.
Trans 300.58 Rub rails.
Trans 300.59 Seating.
Trans 300.60 Service door.
Trans 300.61 Signs and lettering.
Trans 300.62 Steering.
Trans 300.63 Steps.
Trans 300.64 Stop signal arm.
Trans 300.65 Sunshield.
Trans 300.66 Suspension system.
Trans 300.67 Tires.
Trans 300.68 Wheels.
Trans 300.69 Windows.
Trans 300.70 Windshield.
Trans 300.71 Windshield washer.
Trans 300.72 Windshield wipers.
Trans 300.73 Wiring.

Subchapter III—Special Additional Requirements

Trans 300.75 Special service opening.
Trans 300.76 Power lift or ramps.
Trans 300.77 Wheelchair fasteners.
Trans 300.78 Seats and restraints.
Trans 300.79 Communications.
Trans 300.80 Optional equipment.
Trans 300.81 Authorized optional equipment.

Subchapter IV—General Requirements

Trans 300.85 Replacement equipment.
Trans 300.86 Enforcement policy.
Trans 300.87 Inspection procedures.
Trans 300.88 Applicability.
Trans 300.89 Penalties.

Note: Chapter Trans 300 was renumbered from chapter MVD 17 and revised by emergency rule effective September 8, 1982; chapter MVD 17 as it existed on February 28, 1983 was repealed and a new chapter Trans 300 was created effective March 1, 1983.

Trans 300.01 Purpose and scope. (1) The purpose of this chapter is to promote the safe transportation of pupils and other authorized persons in school buses as defined in s. 340.01 (56), Stats.

(2) This chapter is intended to provide specific safety-related standards regarding the design, construction, inspection, and operation of school buses.

(3) The chapter provides for differing standards for vehicles of varying size and configuration.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83.

Trans 300.02 Definitions. In this chapter:

(1) “Attended” means the driver is in the immediate area of the school bus service door or, in the case of a bus equipped with a power lift, the driver is assisting a disabled person to board or exit the bus operating the power lift controls.

(1m) “Department” means the department of transportation.

(2) “Driver’s compartment” means the area forward of the rearmost portion of the driver’s seat across the entire width of the bus.

(2m) “FMVSS” means federal motor vehicle safety standard.

(3) “GAWR” means the gross axle weight rating.

(4) “GVWR” means the gross vehicle weight rating.

(4g) “Lights” or “lamps” mean devices that emit light, either to illuminate roads, license plates and similar items, or to warn motorists and the public of the presence of a school bus and the need for due care. In this chapter, both terms have the same meaning and may be used interchangeably.

(4m) “Rebody” means the placing of a new or replacement school bus body on a previously-licensed school bus chassis.

(5) “SAE” means the society of automotive engineers.

(6) (a) “School bus” or “bus” means a passenger motor vehicle which is designed to carry 10 or more passengers in addition to the driver, is painted in accordance with s. 347.44 (1), Stats., and transports persons as described in s. 340.01 (56) (a) and (am), Stats. A school bus may be classed as one of the following types:

1. A type “A” school bus is a conversion or body constructed upon a van-type or cutaway front-section vehicle with a left side driver’s door, designed for carrying more than 10 persons. This definition shall include the following 2 classifications:

a. Type A-I, with a GVWR over 10,000 pounds.

b. Type A-II, with a GVWR of 10,000 pounds and under.

2. A type “B” school bus is a conversion or body constructed and installed upon a van or front-section vehicle chassis, or stripped chassis, with a gross vehicle weight rating of more than 10,000 pounds, designed for carrying more than 10 persons. Part of the engine is beneath or behind, or both, the windshield and

beside the driver's seat. The entrance door is behind the front wheels.

3. A type "C" school bus is a body installed upon a flat back cowl chassis, with a gross vehicle weight rating of more than 10,000 pounds, designed for carrying more than 10 persons. All of the engine is in front of the windshield and the entrance door is behind the front wheels.

4. A type "D" school bus is a body installed upon a chassis, with the engine mounted in the front, midships, or rear, with a gross vehicle weight rating of more than 10,000 pounds, designed for carrying more than 10 persons. The engine may be behind the windshield and beside the driver's seat, or it may be at the rear of the bus, behind the rear wheels, or midships between the front and rear axles. The entrance door is ahead of the front wheels.

(b) "School bus" does not include an alternative vehicle, a human service vehicle, a motor bus or a motor vehicle operated as part of an urban mass transit system, in accordance with s. 340.01 (56) (b), Stats.

(7) "Secretary" means the secretary of the department of transportation.

(7m) "Vehicular hazard warning lamps" means utilization of all turn signal lights simultaneously by actuating the vehicular hazard warning switch.

(8) "Wheelchair" means any specially constructed wheeled device used exclusively for the movement of physically disabled persons.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83; renum. (1) to (1m), cr. (1), (2m), (4m), (7m), am. (8), Register, February, 1995, No. 470, eff. 3-1-95; r and recr. (6), Register, December, 1997, No. 504, eff. 1-1-98; CR 15-069: cr. (7r) Register April 2016 No. 724, eff. 5-1-16; renum. (7r) to (4g) under s. 13.92 (4) (b) 1., Stats., Register April 2016 No. 724.

Subchapter I—Purchasing and Operating Requirements

Trans 300.10 Manufacturer. It is the vehicle manufacturer and the school bus body manufacturer's responsibility to manufacture a school bus in compliance with all federal and state standards applicable to the manufacturer of school buses. The vehicle manufacturer shall provide copies of all equipment recalls to the administrator, Wisconsin division of state patrol, to assure appropriate repairs are made.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83; am. Register, February, 1995, No. 470, eff. 3-1-95.

Trans 300.11 Dealer. (1) It is the chassis dealer's responsibility to furnish a motor vehicle chassis that is to be combined with a school bus body which meets the applicable state standards that relate to chassis components. The chassis dealer is the statutory owner of the school bus.

(2) General practice through the years has made the school bus body distributor the person who actually delivers the school bus to the purchaser. The presale inspection shall be the responsibility of the dealer or the distributor delivering the school bus to the purchaser.

(3) The dealer or distributor that is required to secure the presale inspection shall be clearly indicated on the purchase order.

(4) The dealer shall assure that copies of all equipment recalls are provided to the division of state patrol.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83; am. (2), (3), cr. (4), Register, February, 1995, No. 470, eff. 3-1-95.

Trans 300.12 Distributor. The school bus body distributor acts as an agent of the final assembler of the school bus. The distributor is the agent that may arrange for the presale inspection of the school bus. If the purchaser wishes to arrange for the presale inspection, this shall clearly be stated on the purchase order. The distributor shall furnish a school bus body which meets the applicable state standards that relate to body components. The distribu-

tor or owner who furnishes a rebody shall arrange for the initial inspection prior to its use as a school bus.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83; am. Register, February, 1995, No. 470, eff. 3-1-95.

Trans 300.13 Purchaser. (1) Any person intending to purchase a motor vehicle to be used as a school bus shall provide the seller with a written notice of such intent prior to the signing of the purchase order. A notation on the purchase order shall fulfill this requirement.

(2) Any person intending to purchase a school bus body to be combined with a motor vehicle chassis to form a body-on-chassis type school bus shall provide the seller or distributor with a written notice of such intent prior to the signing of the purchase order. A notation on the purchase order shall fulfill this requirement.

(3) Any person purchasing a school bus may not use the vehicle for any pupil transportation unless the bus has been inspected by the department and approved for use as a school bus in Wisconsin. This may not preclude such use if items needing correction or alteration after the initial inspection are of a nature that would not affect safe transportation of students. The inspecting officer shall advise the owner if a new bus may be used while the items not in compliance are being corrected.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83; cr. (intro.), Register, February, 1995, No. 470, eff. 3-1-95; am. (3), Register, December, 1997, No. 504, eff. 1-1-98; 2017 Wis. Act 49: r. (intro.) Register August 2017 No. 740, eff. 8-4-17.

Trans 300.15 Employer requirements. (1) Each employer of school bus drivers shall be responsible to determine that only qualified personnel operate school buses according to safe practices and that each bus is qualified for pupil transportation.

(2) The operator or owner of a school bus shall have a maintenance record file for each school bus. The maintenance record file shall be kept at the principal repair facility used for the bus. If the bus owner does not operate a repair facility, the record file shall be kept current at another location accessible for inspection. The record file shall be maintained for the life of the bus and shall contain:

(a) Identification of the bus including make, model, vehicle identification number, and fleet number.

(b) A record of repairs performed including the date and nature of repair.

(c) A record of the lubrication and preventive maintenance performed including date and nature of maintenance.

(d) The initial pre-sale inspection and a copy of the latest inspection performed by state employees.

(3) All required records shall be open for inspection and presented to the secretary or designee upon demand. The secretary may periodically authorize deletion or destruction of material contained in the record file.

(4) A driver's report indicating a school bus defect or unsafe condition, in either written or electronic form, shall be maintained for a period of 7 calendar days after repair.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83; am. (2) (a), Register, February, 1995, No. 470, eff. 3-1-95; am. (3), Register, December, 1997, No. 504, eff. 1-1-98; CR 03-116: am. (2) (d) Register April 2004 No. 580, eff. 5-1-04; CR 15-069: am. (2) (d), r. and recr. (4) Register April 2016 No. 724, eff. 5-1-16.

Trans 300.16 Driver requirements. (1) Prior to the start of any trip, the driver, or employer designee, shall check the condition of the bus, giving particular attention to brakes, tires, lights, emergency equipment, mirrors, windows, and interior cleanliness of the bus. Defects shall be reported in writing, or electronic file, to the person in charge of bus maintenance by completing a pre-trip report. In addition to completing a pre-trip report when a defect or unsafe condition is found, an inspection log indicating the date, time, and identification of who completed the inspection must be completed prior to the start of any trip. It is the driver's responsibility to ensure that the pre-trip inspection

has been completed prior to the start of any trip. The driver shall be responsible for the cleanliness of the interior of the bus and shall ensure that the windshield and mirrors are clean before each school bus operation and that the strobe light is actuated whenever the bus is in operation on a highway for purposes specified in s. 340.01 (56) (a) and (am), Stats.

(2) Articles may not be transported within the bus body if there is or may be interference with the safe transportation of pupils or with the driver or if the articles obstruct the aisle, stepwell, or steps. No animal, firearm, or other weapon of any sort, or articles not associated with school activity shall be permitted on a bus without the express, written authorization of the appropriate school administrator. The bus driver shall refuse admittance to any student not presenting the required written authorization. The driver shall designate where all such articles shall be carried in the bus. The provisions of this subsection do not apply to animals specially trained to aid disabled persons which may be permitted in accord with s. 106.52 (3) (am), Stats.

(3) The driver may not smoke or permit smoking aboard the school bus.

(4) A driver may not operate a school bus while under the influence of alcohol or a controlled substance or a combination of alcohol and a controlled substance or permit the use of alcohol or a controlled substance on any school bus. The driver may not operate a school bus if he or she is under any medication, or combination of medication and alcohol, which may affect the safe operation of the bus.

(5) Drivers operating a school bus that meets the definition of a commercial motor vehicle shall comply with ss. 346.63 (5) and 346.63 (7) (a), Stats.

(6) Drivers operating a school bus not meeting the definition of a commercial motor vehicle shall comply with the following:

(a) A driver may not consume an intoxicating beverage regardless of its alcoholic content within 4 hours before going on duty, or operating, or having physical control of, a school bus.

(b) A driver may not consume an intoxicating beverage regardless of its alcoholic content while on duty, or operating, or in physical control of, a school bus.

(c) A driver may not have in his or her possession any alcoholic beverage regardless of its alcoholic content while on duty or operating a school bus.

(d) A driver may not operate a school bus while having any measured alcohol concentration above 0.0.

(7) The driver shall maintain order among passengers being transported and shall promptly report any misconduct to the proper authority. The driver may assign a seating order.

(8) Loading stations or points shall be selected with due regard for traffic and pedestrian safety and shall be approved by school authorities. Flashing warning lights shall be used as required by s. 346.48 (2), Stats. The stop arm shall be used in conjunction with the flashing red warning lights and shall be extended only after the bus comes to a stop. Except where there are special loading zones where the bus is entirely off the traveled portion of the highway, the bus shall be stopped on the traveled portion of the highway in the lane farthest to the right which is improved, designed or ordinarily used for vehicular travel, excluding the berm or shoulder. The flashing red warning lights may not be extinguished until loading or unloading is completed and persons who must cross the highway are safely across. The stop arm shall be retracted before putting the bus in motion.

(9) A school bus may not be stopped on any portion of a highway for the loading or discharge of pupils or other persons unless the bus is painted the yellow and black school bus color combination, is equipped with a stop signal arm and alternating flashing red or flashing red and amber lights and is identified by a school bus sign. This subsection does not apply to a vehicle which is operating within a municipality and which is not readily identifiable as a school bus. When loading or discharging pupils in a rural

area, a vehicle not identifiable as a school bus shall do so off the highway and in such a manner that the pupils do not have to cross the highway.

(10) The driver shall make sure that there is no traffic danger before allowing pupils to cross the highway. Pupils obliged to cross the highway shall be required to cross from a point at least 10 feet forward of the standing bus only after receiving a signal from the driver. When discharging passengers the driver may not proceed until all persons are at a safe distance away from the bus or, if crossing the roadways, they are safely across the street or highway. This subsection applies only where alternating flashing red or flashing red and amber lights are required by s. 346.48, Stats., or authorized by s. 349.21, Stats.

(11) A driver may not leave the bus unattended with the engine running or the key in the ignition when pupils are in the bus or in the immediate area of the bus.

(12) Except as provided in sub. (15), the doors of a bus shall be closed securely before starting and shall remain closed while the bus is in motion. Abrupt starts and stops or sudden maneuvers are prohibited, except in an emergency.

(13) The driver may not require nor permit any passenger to stand while the vehicle is in motion except while a passenger is going to a door or seat just prior to stopping or immediately after loading. This does not apply to chaperones or monitors in the performance of their duties. The driver may not permit any passenger to sit anywhere on the bus except in seats provided.

(14) The driver may not operate a school bus beyond the legal posted speed limits on any town, county, municipal, state or federal highway.

(15) The driver of a school bus required to stop at a railroad crossing by s. 346.45, Stats., shall come to a full stop at a distance of not less than 15 feet nor more than 50 feet before crossing at grade any track of a railroad. The vehicle hazard warning lamps shall be used when the bus is slowing for the stop and shall remain on until the bus has resumed normal speed. While the bus is so stopped, the driver shall open the service door and listen and look in both directions along the track for any approaching train and for signals indicating the approach of a train. After stopping and upon proceeding when it is safe to do so, the driver of the bus shall cross only in the gear of the bus that will make it unnecessary to manually shift gears while traversing the crossing, and the driver may not shift gears while traversing the crossing. The service door shall remain open until the front wheels of the bus have cleared the first set of tracks for each required stop, but shall be closed before shifting.

(16) In case of an accident or a breakdown, when practicable, the driver shall remain with the bus and may send 2 responsible pupils or other passengers to the nearest place for help unless aid has been secured by means of 2-way communication.

(17) The use of audio headsets by drivers shall be prohibited.

(18) Drivers shall check the entire interior of the school bus following each trip to assure all passengers are off the bus.

(19) Drivers, school boards, transportation supervisors, and bus owners shall cooperate at all times with authorized division of state patrol personnel in carrying out the inspection of school buses and equipment.

(20) No persons except pupils, school employees, chaperones and other persons approved by the school or department authorities shall be permitted to ride in a school bus subject to this chapter, provided that school board members or an authorized department official conducting an inspection of the vehicle or examination of the driver's ability shall be given such privilege. Transportation of passengers in excess of the number posted in the bus is prohibited.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83; am. (2), (3), renum. (5) to (15) to be (7) to (16) and (19) and am. (7) to (10), (12), (14) to (16), cr. (5), (6), (17), (18), (20), Register, February, 1995, No. 470, eff. 3-1-95; am. (2) to (4), (6) (a) to (d), (8) to (11), (13) and (15), Register, December, 1997, No. 504, eff. 1-1-98; am. (1), Register, April, 1999, No. 520, eff. 5-1-99; correction in (2) made under s. 13.92

(4) (b) 7., Stats., Register March 2012 No. 675; CR 15-069: am. (1), (8) to (10) Register April 2016 No. 724, eff. 5-1-16.

Trans 300.17 Passengers. School bus passengers shall comply with any lawful order given by the driver in carrying out the driver's responsibility of transporting passengers safely.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83.

Trans 300.18 Out of service. (1) Any bus that is found to be in such condition that it is unsafe for use as a school bus shall have an "out of service" sticker attached to the lower right corner of the windshield, and the vehicle may not be used as a school bus while the sticker is displayed.

(2) A vehicle with an "out of service" sticker displayed shall be reinspected by and shall have the sticker removed by an employee of the division of state patrol or authorized agent of the carrier at the direction of the division of state patrol employee prior to reuse as a school bus.

(3) It shall be illegal for any person other than an agent of the department to remove, conceal or obstruct an "out of service" sticker unless the vehicle:

- (a) Has the base school bus registration removed.
- (b) Is re-registered in such a manner as to prohibit its use as a school bus.
- (c) Is converted to meet the requirements of s. Trans 300.19.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83; am. (1), (2), Register, February, 1995, No. 470, eff. 3-1-95; am. (1), (2) and (3) (a) and (b), Register, December, 1997, No. 504, eff. 1-1-98.

Trans 300.19 Requirements to convert a school bus. The owner of every vehicle identified as a school bus by color, signs, and lights which is converted from a school bus to some other type of vehicle shall comply with the following requirements:

- (1)** Repaint the entire vehicle to a color other than glossy yellow or any color commonly referred to as yellow.
- (2)** Physically remove the flashing red lights from the vehicle; the mere disconnection, covering or repainting of the flashing red lights does not comply with this requirement.
- (3)** Remove the stop signal arm.
- (4)** Remove any sign identifying the vehicle as a school bus.
- (5)** Remove the crossing gate.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83; am. (2), Register, December, 1997, No. 504, eff. 1-1-98; CR 03-116: cr. (5) Register April 2004 No. 580, eff. 5-1-04.

Trans 300.20 Adoption of standards. (1) Pursuant to s. 227.21, Stats., the attorney general and the legislative reference bureau have consented to the incorporation by reference of the following standards.

(a) *SAE J579c—sealed beam headlamp units for motor vehicles.* SAE standard approved January 1940 and last revised by the lighting committee December 1984.

(b) *SAE J585e—tail lamps (rear position lamps).* SAE standard approved March 1918 and last revised by the lighting committee March 1986.

(c) *SAE J586 Feb 84—stop lamps.* SAE standard approved February 1927, completely revised by the lighting committee December 1989.

(d) *SAE J587 Oct 81—license plate lamps.* SAE standard approved March 1918 and last revised by the lighting committee August 1985.

(e) *SAE J588f—turn signal lamps.* SAE standard approved February 1927 and last revised by the lighting committee June 1991.

(f) *SAE J592 Jan 84—clearance, side marker, and identification lamps.* SAE standard approved January 1937 and last revised by the lighting committee March 1990.

(g) *SAE J593e—backup lamps.* SAE standard approved August 1947 and last revised June 1989.

(h) *SAE J887 May 82—school bus warning lamps.* SAE standard approved July 1964 and completely revised August 1987.

(i) *SAE J914b—side turn signal lamps.* SAE recommended practice approved February 1965 and last revised November 1989.

(j) *SAE J1133 April 84—school bus stop arm.* Report of the lighting committee, approved April 1976, completely revised July 1989.

(k) *Federal regulations adopted.* The federal regulations in title 49, Code of Federal Regulations, part 393, parts and accessories necessary for safe operation, and part 571, motor vehicle safety standards, adopted by the United States department of transportation and in effect on October 1, 1996 shall be enforced in relation to a school bus under this chapter as though the regulations were set out in full in this chapter.

Note: Copies of the references are on file in the offices of the Division of State Patrol, the Secretary of State, and the Legislative Reference Bureau; or may be purchased from the Society of Automotive Engineers (SAE), 400 Commonwealth Drive, Warrendale, PA, 15096. The standards are noted in the SAE handbook, 1997 edition. Any standard or recommended practice shall be treated as an approved standard and shall not be advisory in nature.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83; correction in (1) (intro.) made under s. 13.93 (2m) (b) 7., Stats., Register, December, 1987, No. 384; am. (1) (a) to (i), (2), cr. (1) (j), (k), Register, February, 1995, No. 470, eff. 3-1-95; am. (1) (k) and renum. and am. (2) to be (1) (k) Note, Register, December, 1997, No. 504, eff. 1-1-98; correction in (1) (intro.) made under s. 13.92 (4) (b) 6., Stats., Register March 2012 No. 675.

Trans 300.21 Rebody requirements. (1) A school bus may be upgraded by the installation of a new body on an older chassis. This product will be known as a reboddy school bus.

(2) A chassis provided for a reboddy shall be currently titled and licensed as a school bus in Wisconsin.

(3) Proof shall be presented to the school bus body distributor that all chassis defects from the previous inspection have been corrected.

(4) The following items shall have been replaced with new or rebuilt parts within 12 months prior to the time of reboddy:

- (a) All brake lines replaced with steel or stainless steel lines and all brake hoses replaced.
- (b) Hydrovac and related lines.
- (c) Vacuum tanks.
- (d) Shock absorbers.
- (e) If air equipped, all tanks, lines, diaphragms, and valves.

(5) Any chassis 5 years old or less that has the items in sub. (4) may be waived from replacement provided the school bus body distributor is satisfied it is in like-new condition.

(6) The replacement body shall meet all FMVSS requirements applicable at the time the body was manufactured.

(7) All reboddy school buses shall be inspected by the division of state patrol before operation as a school bus. This inspection shall be the same inspection as a presale inspection.

History: Cr. Register, February, 1995, No. 470, eff. 3-1-95.

Trans 300.22 Charter operations. A school bus may be used temporarily as a motor bus for transportation purposes if the following requirements are met:

(1) The registration requirements as provided in s. 341.26 (7), Stats.

(2) The lettering as prescribed by s. 347.44 (1) (c), Stats., is covered or removed. This may be accomplished by substituting the word "charter" for "school." This subsection does not apply when transporting children for any purpose under s. 346.48 (2) (c), Stats.

History: Cr. Register, February, 1995, No. 470, eff. 3-1-95; am (2), Register, December, 1997, No. 504, eff. 1-1-98.

Subchapter II—Equipment Standards

Trans 300.25 Aisle. (1) Every type A-I, B, C or D school bus or type A-II school bus manufactured in 2 stages, shall have a center aisle with a minimum clearance 12 inches wide. The cen-

ter aisle shall be the open area which pupils entering the service door utilize to gain access to their seats. The center aisle shall extend from the driver's compartment to the emergency exit at the rear of the bus. The school bus that has a side emergency door shall, in addition, have a 12-inch wide aisle from the center aisle to the side emergency door. The intent of this requirement is to provide a 12-inch wide, unrestricted aisle to any emergency door.

(2) An open area for wheelchairs is not an aisle.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83; am. (1), Register, February, 1995, No. 470, eff. 3-1-95; am. (1) and (2), Register, December, 1997, No. 504, eff. 1-1-98.

Trans 300.26 Alternator, generator. (1) The alternator or generator shall have a capacity that meets or exceeds the minimum requirement for the reserve capacity rating of the battery.

(2) A school bus of more than 15,000 pounds GVWR shall be equipped with an alternator or generator of at least 100 ampere rating.

(3) A school bus of 15,000 pounds GVWR or less but more than 10,000 pounds GVWR shall be equipped with an alternator or generator of at least 80 ampere rating.

(4) A type A-II school bus shall be equipped with an alternator or generator of at least 60 ampere rating. If a school bus is equipped with a power lift, it shall be equipped with an 80 ampere or more rated alternator or generator.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83; am. (4), Register, February, 1995, No. 470, eff. 3-1-95; am. (4), Register, December, 1997, No. 504, eff. 1-1-98.

Trans 300.27 Barriers. (1) Every type A-I, B, C or D school bus shall be equipped with a barrier forward of the foremost right and left front seats that complies with FMVSS 222, school bus seating and crash protection.

(2) A type A-II school bus manufactured in 2 stages shall be equipped with a barrier or a padded stanchion forward of the foremost right and left front seats. The barrier shall extend from the wall to the aisle. If a stanchion is utilized, the area immediately in front of the foremost seat shall be protected with a padded panel extending from no more than 4 inches above the floor to the crossbar. The stanchion bars shall be padded.

(3) If the bus meets any federal requirements relating to the use of seat belts, the bus shall, in addition, be equipped with barriers or stanchions as indicated in this section.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83; am. Register, February, 1995, No. 470, eff. 3-1-95; am. (1) and (2), Register, December, 1997, No. 504, eff. 1-1-98.

Trans 300.28 Battery. The storage battery shall have a cranking performance rating equal to or greater than the cubic inch displacement of the engine powered by any means other than with diesel fuel.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83.

Trans 300.29 Battery carrier and connections.

(1) All batteries shall be securely attached in a manner to prevent dislocation in the event of an accident. The battery may be mounted in the engine compartment or, when mounted outside of the engine compartment, it shall be contained in a closed, drained, weather-tight and vented compartment which shall retain the battery in the event of upset or roll-over of the bus. If the battery is mounted in the body skirt, the battery compartment door or cover shall be secured by a latch. The battery may not be located in the passenger compartment.

(2) The cables to the battery may not be spliced.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83; am. (1), Register, February, 1995, No. 470, eff. 3-1-95; am., Register, December, 1997, No. 504, eff. 1-1-98.

Trans 300.30 Book racks. (1) Book racks, if installed, shall be located above the side windows. They may not extend forward of the foremost point of the front seat or across or above the rear emergency door.

(2) Book racks made of expanded, punched, or woven metal are not permitted.

(3) Book racks shall be free of projections or sharp edges.

(4) Book racks are permitted only in buses with a minimum of 72" head room.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83; am. (1), Register, December, 1997, No. 504, eff. 1-1-98; CR 15-069: am. (1) Register April 2016 No. 724, eff. 5-1-16.

Trans 300.31 Brakes. (1) Every school bus shall meet federal brake standards under 49 CFR 393.40 to 393.52, 396.17, and applicable standards under 49 CFR 571.105 and 571.121, in effect at the time of manufacture. Each brake system including the parking brake shall be maintained in good working order. The brake system shall be free of any leaks. The lines and hoses may not be chafed, flattened or restricted in any way.

(2) A type A-I, B, C or D school bus that uses air assisted brakes shall be equipped with a low pressure warning system which functions at 60 psi and lower. The governor cut out pressure may not exceed 135 psi. The governor cut in pressure may not be lower than 80 psi.

(3) A type A-I, B, C or D school bus that uses vacuum assisted brakes shall be equipped with a low pressure warning system which functions when the vacuum is 8 inches of mercury and less.

(4) A type A-I, B, C or D school bus when equipped with air or vacuum assisted brakes shall be equipped with a reserve tank having a capacity of not less than 1,000 cubic inches to provide additional air or vacuum for the primary brake system. There shall be a check valve or pressure protective valve to protect the system from loss of air or vacuum. There shall be no accessory except the low pressure warning device operated from the air or vacuum reserve tank or its connecting lines. The low pressure warning system shall be installed to indicate the air pressure or vacuum in the tank. The gauge required to monitor this system shall be visible to the driver at all times. Unless previously equipped, a type A-I school bus with a GVWR of 11,500 pounds or less that uses vacuum assisted brakes is not required to be equipped with an additional reserve tank and gauge, provided the vacuum assist system meets FMVSS No. 105.

(5) Every school bus shall be equipped with a power assist brake system.

(6) The interior of the brake drums, brake linings, brake discs, and pads shall be free of cracks and contamination from oil or grease.

(7) The brake systems shall be properly adjusted to provide maximum braking effort in accordance with 49 CFR 396.17 (appendix G).

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83; am. (1), (6), (7), Register, February, 1995, No. 470, eff. 3-1-95; am. (1) to (4), Register, December, 1997, No. 504, eff. 1-1-98; CR 03-116: am. (4) Register April 2004 No. 580, eff. 5-1-04.

Trans 300.32 Bumpers. (1) The front bumper of type A-I, B, C or D buses shall have not less than an 8-inch face and shall extend between the frame rails as a minimum. The bumper shall be of sufficient strength and be positioned to permit pushing a vehicle of similar weight without distortion to the bumper, chassis, or body.

(2) The rear bumper of type A-I, B, C or D buses shall have not less than an 8-inch face and shall wrap around the rear corners of the body to a point at least 12 inches forward. The bumper shall be of sufficient strength and shall be positioned to permit the bus to be pushed without distortion to either the bumper or the bus body. There shall be no more than 1/2 inch space between the bumper and the body. Protective material may be utilized to fill all or part of the required 1/2 inch space.

(3) Type A-II buses shall be equipped with bumpers on the front and on the rear.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83; am. (1), (2), Register, February, 1995, No. 470, eff. 3-1-95; am. (1) to (3), Register, December, 1997, No. 504, eff. 1-1-98.

Trans 300.33 Capacity. (1) The passenger capacity of a school bus shall be determined by the following standards:

(a) Pupils through the 12th grade shall be allotted 13 inches of seating space.

(b) Each wheelchair location shall be counted as one seating position.

(2) There shall be displayed on the inside of the bus directly over the windshield on the right side a sign indicating the maximum pupil passenger capacity. The size of the letters and numerals shall be large enough to permit them to be read by passengers. Transportation of passengers in excess of the number designated on the sign or of the actual seat measurement is prohibited.

(3) The total available seating capacity per seat shall determine the capacity of the bus. Fold down or fold up seats or reclining seats are not permitted except that at side emergency door locations, a "flip-up seat" may be used. The "flip-up seat" shall conform to the following requirements:

(a) The "flip-up seat" shall be designed and constructed to inhibit passenger limbs from becoming lodged between the seat cushion and seat back.

(b) The working mechanism under the seat shall be covered to eliminate any tripping hazard.

(c) The bottom of the "flip-up seat" shall be covered with sheet metal or other material of equal strength and durability and any sharp edges padded to prevent injury or snagging of clothing.

(d) The seat shall be designed and constructed to rise to a vertical position automatically when not occupied.

(4) All passengers aboard a school bus shall be seated in a permanently mounted seat. This subsection does not apply to persons transported in wheelchairs or in other devices where special care is required.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83; am. (2), renum. (3) to (3) (intro.) and am., cr. (3) (a) to (d), Register, February, 1995, No. 470, eff. 3-1-95; am. (3) (intro.), Register, December, 1997, No. 504, eff. 1-1-98.

Trans 300.34 Color. (1) All school buses shall be painted national school bus glossy yellow with the exception of the trim, grill, roof, wheels and the bumpers. Grills and wheels may be chrome, black, yellow, silver, white or gray. Engine hood tops may be painted matte black or lusterless yellow for glare reduction.

(2) When painted, the bumper shall be painted black.

(3) Stop arms shall be painted black.

(3m) Rub rails shall have a 2 inch minimum black color down their center, by either painting or application of a high quality blackout film, paint film, or retro-reflective tape. The remainder of each rub rail shall be either black or national school bus glossy yellow.

(4) The following may be designated as trim or body components and if painted shall be either black or yellow:

(a) Door handles.

(b) Grab handles.

(c) Window sash, seals, gaskets, pillars, and bands on exposed edges.

(d) Door seals and gaskets.

(e) Mirror frame and mounting brackets.

(f) Lamp flanges, housings, and an area around the tail, stop, turn, and back up lamps not to exceed 3 inches. Areas adjacent to rub rails may exceed 3 inches to the extent of the width of the rub rail.

(g) Reflector frames and flanges.

(h) Windshield wiper arms.

(i) Snow rails.

(j) License frame and mounting brackets.

(k) Service door.

(5) The body manufacturer's name including a logo may appear on the exterior of the vehicle in any color.

(6) Noncontrasting reflective material is permitted to include, but not limited to, rub rails, snow rails, as "school bus" lettering and the owner's identification as required in s. Trans 300.61 (6) or permitted in s. Trans 300.61 (7). Front or rear bumper, or both, may be marked diagonally 45° down to centerline of pavement with 2-inch wide strips of noncontrasting reflective material.

(7) Yellow reflective tape may be located on the rub rail in areas of emergency exit windows in order to meet requirements of FMVSS 217.

(8) An external camera, audio monitor or recording device housing shall be either national school bus glossy yellow, black, gray, or white.

(9) Sensors used for anti-theft or pre-trip inspections shall be either national school bus glossy yellow, black, gray, or white

(10) The roof of a school bus may be painted white. The front and rear roof caps shall be painted school bus glossy yellow or black. The white roof may not extend below the side windows, or if equipped, the drip rail.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83; am. (1), (4) (f), (6), Register, February, 1995, No. 470, eff. 3-1-95; am. (6) and cr. (7), Register, December, 1997, No. 504, eff. 1-1-98; CR 03-116; am. (1), (4) (c) and (f), cr. (4) (k) Register April 2004 No. 580, eff. 5-1-04; CR 15-069; am. (1), renum. (3) (intro.) to (3) and am., r. (3) (a), (b), am. (4) (f), cr. (8) to (10) Register April 2016 No. 724, eff. 5-1-16.

Trans 300.35 Construction. (1) The construction shall be of prime commercial quality steel or other metal, or material with strength at least equivalent to all-steel, as certified by the bus body manufacturer, except for the grill, hood, or fenders and shall comply with FMVSS 220, school bus rollover protection. Type A-I, B, C or D school buses shall comply with FMVSS 221, school bus body joint strength.

(2) The construction shall provide a reasonably dustproof and weather tight unit. Openings between the chassis and passenger compartment shall be sealed to prevent fumes or exhaust gas from entering the bus body.

(3) The floor or subfloor shall be of prime commercial quality steel of at least 14 gauge or material with strength at least equivalent to all-steel, as certified by the bus body manufacturer. Plywood may be used in addition to other flooring material. The floor shall be level from front to back and from side to side except in the wheel housing, toeboard, and driver's seat platform areas. The body cross members below the floor may have no more than 2 consecutive and no more than 3 total members that are completely rusted through.

(4) For type A-I, B, C or D buses, all joints within bus bodies which employ discrete fasteners, specifically those which join panels to panels, shall achieve a significant portion of the strength of the parent metal, so that all available panel materials are capable of serving as part of the structure.

(5) All metal used in construction of the bus body shall be zinc- or aluminum-coated or treated by an equivalent process before the bus is constructed. Included are such items as structural members, inside and outside panels, floor panels and floor sill. Excluded are the door handles, grab handles, stanchions, interior decorative parts, and other interior plated parts.

(6) Annually between December 1 and December 15, each school bus manufacturer shall certify to the department that all school buses manufactured for sale in Wisconsin in the following calendar year will comply with this section. The certification shall be filed in the division of state patrol. The certification may be addressed to the administrator, division of state patrol, P.O. Box 7912, Madison, WI 53707-7912.

(7) Each school bus body manufacturer shall stamp the letters "WI" either preceding or following the body identification number to indicate that the bus body was built to meet Wisconsin school bus construction standards. The school bus body manufacturer shall furnish to the department a blueprint indicating the size

and placement of the “WT” requirement on its buses to be sold in Wisconsin. A sample plate shall be furnished by the manufacturer to the division of state patrol showing the placement of the “WT”. This subsection does not apply to vehicles in use as school buses in Wisconsin prior to March 1, 1979.

(8) The owner of any vehicle previously marked, registered, or titled in another jurisdiction as a school bus shall, prior to using the vehicle for any pupil transportation in Wisconsin, submit the vehicle for department inspection and approval as provided by s. Trans 300.13 (3). In addition, the owner shall provide proof satisfactory to the division of state patrol that the vehicle is constructed in compliance with this section.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83; am. (1), (2), (6), r. and rec. (8), Register, February, 1995, No. 470, eff. 3-1-95; emerg. am. (1) and (3), eff. 7-1-97; am. (1), (3) and (4), Register, December, 1997, No. 504, eff. 1-1-98.

Trans 300.355 Crossing gate. (1) All school buses shall have a crossing gate installed by May 1, 2004.

(2) The crossing gate shall be mounted on the right side of the front bumper and shall open to 90 degrees.

(3) The crossing gate shall meet or exceed SAE J1133. The crossing gate shall be constructed of noncorrosive or nonferrous material or treated in accordance with body sheet metal specifications and shall have no sharp edges or projections that could cause hazard or injury to students. The color may be yellow, black, silver or gray.

(4) The crossing control arm shall extend a minimum of 70 inches, measured from the bumper at the arm assembly attachment point, when in the extended position. The arm shall extend simultaneously with the stop arm by means of the stop arm controls.

(5) An automatic recycling interrupt switch may be installed for temporary disabling of the crossing control arm. An electromagnetic device may be installed to stabilize the arm when in the stored position.

History: CR 03-116; cr. Register April 2004 No. 580, eff. 5-1-04.

Trans 300.36 Defroster. (1) The defrosting system shall have the capacity to keep the windshield, the window to the left of the driver and the glass in the service door clear of fog and frost. The defroster outlets may not be restricted in any way.

(2) Fans may be used in addition to defrosters, but shall be mounted so as not to obstruct the driver’s view.

(3) Any exposed fan blade shall have a shroud.

(4) The defrosting system shall conform to SAE standards J391 and J382.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83; cr. (4), Register, February, 1995, No. 470, eff. 3-1-95; am. (1), Register, December, 1997, No. 504, eff. 1-1-98.

Trans 300.37 Drive shaft. (1) Each segment of the drive shaft more than 18 inches long shall be equipped with a suitable guard to prevent an accident or injury in the event of its fracture or disconnection. This section does not apply to type A-II buses manufactured in a single stage.

(2) The universal joints and the center bearing of every bus subject to inspection may not be loose or worn.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83; am. (1), Register, February, 1995, No. 470, eff. 3-1-95; am. (1) and (2), Register, December, 1997, No. 504, eff. 1-1-98.

Trans 300.38 Emergency warning equipment. (1) Each school bus shall be equipped with 3 bidirectional emergency triangles. Oil burning pot flares may not be carried on a school bus.

(2) All emergency equipment shall be kept in suitable fasteners or containers in a readily accessible place in the driver’s compartment. The container or units shall be secured to the bus.

(3) Emergency equipment may be locked or kept in a locked compartment provided it is not locked when passengers are being transported.

(4) This section does not preclude the carrying of additional emergency equipment.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83; r. (5), Register, February, 1995, No. 470, eff. 3-1-95; am. (1) and (4), Register, December, 1997, No. 504, eff. 1-1-98.

Trans 300.39 Emergency exits. (1) Each school bus shall have emergency exits that comply with 49 CFR 571.217 and FMVSS 217, bus window retention and release, and the following requirements. If a left side emergency door is utilized, there shall also be an emergency exit window in accordance with sub. (8), located in the back of the bus. A window by itself does not meet this requirement for an emergency exit.

(2) Required emergency exits shall be designed to be opened from both the inside and the outside of the bus. Side emergency exit windows are exempt from this requirement.

(3) There may not be any obstructions in the aisles or inside of the door that would delay or hinder an orderly use of the emergency exit. Articles transported on non-occupied seats inside the bus shall be secured.

(4) Steps leading to an emergency door are prohibited.

(5) The upper and lower portion of the central rear emergency door shall be equipped with approved safety glass, the area of which shall be not less than 400 square inches in the upper portion and not less than 280 square inches in the lower portion. Van type buses are exempt from the requirement to have glazing in the lower part of the door. The left side emergency door shall be equipped with safety glass in the upper portion and the lower portion shall be of at least the same gauge metal as the body. The emergency door shall be hinged on the right side if it is in the rear of the bus and on the front side if it is in the left side and shall open only outward. Control of the emergency door from the driver’s seat shall not be permitted.

(6) The emergency doors shall be equipped with a slide bar, cam-operated latch which shall have a minimum stroke of one inch. The latch shall be equipped with an electric plunger-type switch connected with a distinctive signal audible to the driver, shall be automatically operated, shall clearly indicate the unlatching of the emergency door and may not have a cutoff switch installed in the circuit. The switch and its activating plunger shall be enclosed in a case, which will prevent tampering, and wires leading from the switch shall be concealed in the body. The switch shall be so installed that the plunger contacts the farthest edge of the slide bar in such a manner that any movement of the slide bar will immediately close the circuit and activate the signal. The door latch shall be equipped with an interior handle which shall be capable of quick release but shall be protected against accidental release. The handle shall lift up to release the latch. The outside handle shall be such as to minimize hitching and shall be securely attached.

(7) If locks are installed on the emergency door they shall include a device to prevent the activating of the starter mechanism of the bus engine while any door is locked. An audio alarm shall indicate to the driver when any door lock is in the locked position while the ignition switch is in the “on” position. Any locking device on a school bus manufactured after July 1, 1977 or installed on any school bus after July 1, 1977 shall comply with these requirements.

(8) A rear emergency window at least 16 inches in height and as wide as practicable shall be provided in any bus where the emergency door is not in the rear. It shall be hinged at the top and designed to prevent accidental closing in an emergency. A positive latch on the inside of the window shall provide for quick release, but offer protection against accidental release. The outside handle shall be nondetachable and designed to minimize hitching.

(9) The inside of each emergency window shall have the designation “Emergency Exit”. An emergency door shall be identified with either the words “Emergency Exit” or “Emergency

Door” on the inside at the top of, or above the door. Directly beneath or above each “Emergency Door” or “Emergency Exit” designation specified by this section a label shall state in letters at least one inch high, “DO NOT BLOCK” in a color that contrasts with the background of the label. Concise operating instructions shall be located within 6 inches of the release mechanism. When a release mechanism is not located within an occupant space of an adjacent seat, a label that indicates the location of the nearest mechanism shall be placed within that occupant space. The outside of the emergency door shall be clearly marked “Emergency Door” or “Emergency Exit” in letters 2 inches high at the top of, or above the door or immediately below the upper glass. An arrow at least 6 inches long and 3/4 inch in width indicating the direction the release mechanism should be turned to open the door shall be painted in black on the yellow background. The outside of the emergency window shall be labeled “Emergency Exit” in letters at least 2 inches high, directly above the window or on the window glazing. There may not be any labeling on the glazing indicating emergency door. Labeling or operating instructions may be located on the glazing of emergency window exits as long as the labeling or instructions are clearly visible inside and outside the vehicle.

(10) A distinctive audible signal automatically operated shall clearly indicate to the driver the unlatching of any emergency window and no cutoff switch shall be installed in the circuit.

(11) The area on the inside above the emergency door shall be covered with padding at least 2 inches high the entire width of the door opening.

(12) If the bus has a side emergency door, there shall be a clear, unrestricted area to permit an exit aisle of 12 inches from the center aisle of the bus without having to go over any obstructing seat. The 12-inch measurement may be taken at any position from floor to roof. The intent of this subsection is to provide a 12-inch unrestricted aisle to and through the side emergency door.

(13) Type A-II buses manufactured in 2 stages shall provide emergency exits as required for larger vehicles.

(14) In addition to side and rear emergency exits, doors, or windows, one or more roof hatches may be installed provided they meet all requirements specified in FMVSS 217. In addition to the audible warning required on emergency doors by FMVSS 217, additional emergency exits shall be likewise protected as indicated in s. Trans 300.39 (10).

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83; am. (1), (2), (6), (9), r. and recr. (14), Register, February, 1995, No. 470, eff. 3-1-95; am. (2), (3), (9) and (13), Register, December, 1997, No. 504, eff. 1-1-98; CR 15-069; am. (9) Register April 2016 No. 724, eff. 5-1-16.

Trans 300.40 Exhaust system. (1) The exhaust system, which includes the exhaust manifolds, joining gaskets, piping leading from the exhaust manifold, muffler and tail pipe may not enter the bus body at any location. The exhaust system pipes shall be of nonflexible steel except that those buses which utilize a diesel engine may be equipped with a flexible pipe of not more than 18 inches long between the engine and the first exhaust pipe hanger. Stainless steel bellows assemblies are allowed. School buses with 2007 EPA or newer diesel engines, subject to emissions standards in 40 CFR 86.007-11, may have flexible tubing at original manufactured locations and if replaced must meet or exceed manufacturer specifications.

(1m) School buses equipped with an EPA 2007 or newer diesel engine, which is subject to emissions standards in 40 CFR 86.007-11, shall maintain or exceed original specifications equipped by the manufacturer and shall discharge exhaust to the rear or left side of the school bus.

(2) An exhaust system that has its exit on the left side shall have the exit point located no further forward than behind the driver’s position.

(3) An exhaust system, that is not an EPA 2007 or newer diesel engine, subject to emissions standards in 40 CFR 86.007-11, may discharge out of the right if located behind the rear wheels.

(4) An exhaust system that exits at the rear shall extend to, but not beyond, the rear limit of the bumper.

(5) Every exhaust system exit shall extend to, but not over one inch beyond the body limits of the bus. The exhaust shall be directed to prevent an accumulation of exhaust gases underneath the bus.

(5m) Buses equipped with diesel engines may be equipped with a turn-down exhaust pipe. The turn-down exhaust pipe may not exceed 6 inches forward of the rearmost part of the bus.

(6) The complete exhaust system shall be tightly connected and free from leaks.

(7) All emission control systems, components and parts shall be maintained in accordance with manufacturer’s specifications.

(8) School buses operated in interstate commerce shall comply with 49 CFR 393.83, exhaust system location.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83; am. (1), (5), cr. (5m), (7), (8), Register, February, 1995, No. 470, eff. 3-1-95; am. (1) and (5m), Register, December, 1997, No. 504, eff. 1-1-98; CR 15-069; am. (1), cr. (1m), am. (3) Register April 2016 No. 724, eff. 5-1-15.

Trans 300.41 Fire extinguisher. (1) Each bus shall be equipped with a fire extinguisher mounted in full view in the driver’s compartment or mounted inside a compartment in the driver’s area if the compartment is in plain view and is labeled “Fire Extinguisher” in red letters to indicate its location.

(2) The fire extinguisher may be locked or kept in a locked compartment provided it is not locked when passengers are being transported.

(3) Any fire extinguisher purchased after July 1, 1977, or utilized on a bus that was manufactured after January 1, 1978, shall utilize dry powder or Halon 1211. The fire extinguisher shall be 10 BC rating or a combination of 2 extinguishers with a total of at least 10 BC rating. Any bus manufactured after January 1, 1984, shall use only a single extinguisher.

(4) Each extinguisher shall be kept fully charged and sealed.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83; am. (1), (3), r. (5), Register, February, 1995, No. 470, eff. 3-1-95.

Trans 300.42 First aid kit. (1) Each school bus shall carry a first aid kit. The container shall be moistureproof and dust-proof and of rigid construction. The kit shall be mounted in full view in the driver’s compartment, or it may be placed in an enclosed unlocked compartment in the driver’s area providing the compartment is labeled “FIRST AID KIT” or marked with a red cross emblem in plain view indicating the location of the kit. The kit shall be removable without the use of any tools or keys.

(2) School buses shall carry a 16 unit kit or larger containing at least the following items:

Adhesive bandage, 1-inch	2 packets
Bandage compress, 2-inch	2 packets
Bandage compress, 4-inch	4 packets
Gauze bandage, 4-inch	2 packets
Gauze compress, 3-inch x 3-inch	2 packets
Gauze compress, 24-inch x 24-inch minimum . .	1 packet
Triangular bandage, 40-inch	2 packets
Wire splint	1 packet

(3) All units shall be in sanitized packages.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83; am. (2), r. (3), (4), renun. (5) to (3), Register, February, 1995, No. 470, eff. 3-1-95.

Trans 300.43 Fenders. Each school bus shall provide protection from debris thrown by the tires by the use of fenders or body construction. The tire tread shall be within the fender or body construction.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83.

Trans 300.44 Floor covering. (1) The floor in the underseat, driver's compartment, step-well and the toeboard areas, including the tops of the wheel housings, shall be covered with a fire-resistant material.

(2) Type A-II buses shall have the floor covering secured so it cannot shift. The edges and seams shall be secured. The covering shall be of a slip resistant material.

(3) Type A-I, B, C or D school buses shall have floor covering on the total floor area. The aisle, step-well and entrance shall be of slip resistant rubber type material or equivalent material as certified by the manufacturer, when either wet or dry. The covering may not be cracked and shall be securely bonded or fastened to the floor. All seams shall be sealed.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83; am. (1), (3), Register, February, 1995, No. 470, eff. 3-1-95; am. (2) and (3), Register, December, 1997, No. 504, No. 1-1-98.

Trans 300.45 Frame. (1) Alterations to the frame side members may only be made by the chassis or body manufacturer.

(2) Holes are not permitted except where originally provided in the chassis frame. There may be no welding to the frame except by the chassis or body manufacturer.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83; am. (2), Register, December, 1997, No. 504, eff. 1-1-98.

Trans 300.46 Fuel tank and fuel system integrity. (1) All fuel systems and tanks must be maintained free of leaks. The fuel tank shall be attached to the bus in a manner that prevents any movement of the tank while the bus is in motion.

(2) All fuel lines shall be secured in a manner that will prevent wear.

(3) The filler pipe or device shall be located so that the fuel, if spilled or overfilled, will not drip or drain on any part of the exhaust system.

(4) Every fuel system shall be properly vented to prevent any accumulation of fumes.

(5) The fuel systems and tanks shall meet FMVSS 301, fuel system integrity, and all other federal and state standards and regulations applicable for the type of fuel used at the time of manufacture.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83; am. (5), Register, February, 1995, No. 470, eff. 3-1-95.

Trans 300.47 Heaters. (1) An inside temperature of not less than 50° fahrenheit at average minimum January temperatures as established by the U.S. department of commerce, weather bureau, for the area in which the bus is to be operated shall be maintained throughout the bus.

(2) The heater hose shall be adequately supported to guard against excessive wear or abrasion and may not interfere with or restrict the operation of any engine function. Heater lines inside the passenger compartment shall be shielded to prevent accidental contact by the driver or passengers.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83; am. (2), Register, December, 1997, No. 504, eff. 1-1-98.

Trans 300.48 Horn. Every bus used to transport pupils shall be equipped with a horn in good working order and capable of emitting a sound audible under normal traffic from a distance of not less than 200 feet.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83.

Trans 300.49 Inside height. (1) The inside height of the school bus shall be 72 inches or more, measured metal to metal, at any point on longitudinal center line from front vertical bow to rear vertical bow.

(2) Type A-II school buses need not comply with this section.
History: Cr. Register, February, 1983, No. 326, eff. 3-1-83; am. (2), Register, December, 1997, No. 504, eff. 1-1-98.

Trans 300.50 Insulation. The ceilings and walls of buses manufactured in 2 stages and all type A-I, B, C and D buses shall be insulated to reduce heat and cold transfer.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83; am. Register, December, 1997, No. 504, eff. 1-1-98.

Trans 300.51 Instruments, gauges. (1) Every school bus shall be equipped with the following illuminated instruments to indicate malfunctions or gauges to indicate a measure or capacity:

- (a) Air pressure or vacuum, where air or vacuum brakes are used with low energy supply warning systems.
- (b) Ammeter or voltmeter.
- (c) Fuel gauge.
- (d) Odometer and speedometer.
- (e) Oil pressure.
- (f) Coolant temperature.

(2) All instruments and gauges shall be in operating condition and shall be mounted so as to be clearly visible to the seated driver.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83; am. (1) (a), (c), (d), (f), Register, February, 1995, No. 470, eff. 3-1-95.

Trans 300.52 Interior. (1) Every school bus shall have a fire resistant inner lining on the ceilings and walls. The interior rearward metal panels shall be lapped over forward panels to reduce the likelihood of injury in the event of separation. The exposed edges of all interior panels shall be beaded, hemmed or flanged.

(2) Projections from the ceiling may not be allowed in the entrance way or aisle. Except for the driver's compartment, all speakers and accessory lighting devices shall be flush mounted or may extend up to one inch if edges are rounded or tapered. Accessory lighting shall be maintained in proper working condition.

(3) A convex mirror may be mounted on the inside rear of the school bus.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83; am. (2), cr. (3), Register, February, 1995, No. 470, eff. 3-1-95; am. (2), Register, December, 1997, No. 504, eff. 1-1-98.

Trans 300.53 Ladders. A school bus may not have a ladder attached to the interior or exterior while it is in motion.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83; am. Register, December, 1997, No. 504, eff. 1-1-98.

Trans 300.54 Lights, lamps, and reflectors. (1) The following lights, lamps, and reflectors are required on a school bus. Each lamp shall be operational and meet the applicable SAE specifications as provided in this section.

(a) A school bus painted in accordance with s. 347.44 (1), Stats., shall be equipped with alternating flashing lights which conform to the following requirements:

1. The bus shall be equipped with 2 red warning lamps at the rear of the bus and 2 red warning lamps at the front of the bus, which shall be controlled by a manually actuated switch and shall flash alternately at rate of 60 to 120 cycles per minute. A brake or door operated switch is not permitted. The "on" period shall be long enough to permit bulb filament to come to full brightness. Two additional red warning lamps to the front and 2 to the rear may be installed inboard and at the same level as the required lamps. If so equipped, the system of red warning lamps shall be of equal size and wired so that the inboard lamps are energized manually. The outboard lamps shall be automatically energized and the inboard lamps automatically de-energized when the stop signal arm is extended.

a. An option is permitted whereby 2 additional alternating flashing red lights may be mounted on both the front and rear of the bus. The additional front facing lights shall be located

between the bottom of the windshield and the top of the highest headlamp. They may be mounted on the fender or the cowl.

b. The additional rear facing lights may be separate lamps mounted within 12 inches above or below the directional turn signals or may be incorporated in an existing lamp. Any incorporation with an existing unit may not interfere with or override the existing unit's function. If the optional lighting system utilizes the rear directional signals, it shall be so designed that if both the directional signal lamp and the flashing red lights are activated during the same period of time, the flashing warning signals shall revert to only the 2 required warning signals until such time as the directional signal lamp is deactivated. The optional system may not be incorporated with the stop signal lamp.

c. The optional system shall have units with a red lens of at least the same size as the required alternating lights. The alternating "on," "off" positions shall be opposite from those of the required alternating lights. The effect will produce the required top mounted flashing light and an optional mid-height mounted light to flash on opposite sides simultaneously. The result can be described as a "wig-wag" or "cross-arm" effect.

d. A school bus shall be equipped with warning signal lights mounted at the same level as high and widely spaced laterally as practicable. The warning signal lights shall be mounted at the front above the windshield and at the rear so that the lower edge of the lens is not lower than the top line of the side window openings. These lights must be capable of displaying to the front 2, and to the rear 2, overhead alternately flashing red lights.

1m. On or after August 16, 2016, the following requirements shall apply to school buses:

a. The school bus body shall be equipped with, in addition to the 4 red warning lights described in subd. 1., amber warning light shall be installed near each red warning light, at the same level, but closer to the vertical center line of the bus. The system of red and amber warning signal lights shall be wired so that the amber warning lights are activated manually, and the red warning lights are automatically activated, with the amber warning lights being automatically deactivated, when the stop signal arm is extended.

b. An amber and a red flashing pilot light shall be installed in the driver's forward field of view indicating to the driver which warning light system is activated.

c. The amber and red warning lights shall flash alternately at a rate of 60 to 120 cycles per minute. The "on" period shall be long enough to permit bulb filament to come to full brightness. A double flash effect shall be counted as a single flash.

d. The above requirements in this subd. do not apply to school buses whose body was manufactured before January 1, 2005.

2. The amber and red warning lights shall be of seal beam construction or other approved type such as strobe or light emitting diode, not less than 5 inches in diameter or with a surface area of at least 19 square inches if not round and visible from a distance of at least 500 feet along the axis of the vehicle in bright sunlight.

3. There shall be a visible or audible means of giving clear and unmistakable indication to the driver when the signaling system is turned on.

4. Each amber and red warning light shall be mounted with its axis substantially parallel to the longitudinal axis of the bus.

5. The front and rear amber and red warning lights shall be spaced as far apart laterally as practicable, and in no case shall the spacing between lamp centers be less than 3 feet.

6. The front amber and red warning lights shall be located so that they can be clearly distinguished when headlamps are lighted on low beam.

7. The amber and red warning lights shall be mounted at the front above the windshield and at the rear so that the lower edge of the lens is not lower than the top line of the side window openings.

8. The front and the rear warning lights shall be unobstructed by any part of the bus from 5 degrees above to 10 degrees below horizontal and from 30 degrees to the right and 30 degrees to the left of the centerline of the bus.

9. The body immediately surrounding the area around the lens of each alternately flashing amber and red warning light shall have a black background extending outward a minimum of 3 inches. Where this is not practicable the background shall extend as wide as possible, with a minimum of a 1 inch black background required.

10. Amber and red warning signal lights may be equipped with hoods to shield from rays of sun for improved visibility.

11. Lamps shall meet the requirements of SAE J887.

12. Vehicles painted other than glossy yellow are prohibited from having the alternating amber and red flashing warning lights mounted on the vehicle except as otherwise provided by statute.

(am) Each school bus first registered on or after October 1, 1998, shall be equipped with a strobe light that conforms to the following requirements:

1. The strobe light shall be of solid state construction. It shall emit a white light by flashing, not rotating, 360 degrees around the vertical axis.

2. The strobe light shall be capable of operating continuously without any significant change in the flash rate under all operating conditions or weather extremes experienced in this state. The flash rate shall be no less than 60 nor more than 120 per minute. The double flash effect shall be counted as a single flash.

3. The electronic power supply circuit shall provide a minimum of 10 joules to the strobe tube. The flash shall be so designed that there is a single or double flash or pulsing of the flash tube. A double flash unit may have different intensities with the first flash having the highest intensity.

4. The strobe light shall be permanently mounted on the centerline of the bus roof not less than 3 feet from the front or rear of the bus. A strobe unit may not extend more than 8 inches above the roof.

5. The unit may be wired with an independent switch with an indicator light in the driver's compartment showing when the light is in operation.

6. The strobe light shall be actuated whenever the bus is in operation on a highway for purposes specified in s. 340.01 (56) (a) and (am), Stats., and may be actuated when the bus is in operation on a highway and is transporting children for any other purpose.

(b) Two backup lamps shall be provided which shall conform to SAE J593e.

(c) There shall be 2 red clearance lamps on the rear and 2 amber clearance lamps on the front, mounted as high and wide as practicable to indicate the vehicle's extreme width. Buses less than 80 inches wide are exempt from this paragraph.

(d) The bus shall be equipped with direction or turn signal lamps.

1. There shall be at or near the front, facing forward, one amber turn signal light on each side of the vertical centerline mounted at the same height, as wide as practicable. The bus may be equipped with signals mounted in the body or chassis. If not equipped with body or chassis mounted front turn signals, double faced signals shall be installed either on the fender or hood and shall be as wide as practicable. Mounting of double faced signals may not be higher than the bottom of the windshield or lower than the headlamps.

2. There shall be on the rear, one red or amber signal on each side of the vertical centerline as wide as practicable mounted at the same height.

3. Rear turn signals shall be mounted no less than 15 inches nor more than 83 inches above the roadway.

4. Both the front and the rear direction signals shall comply with SAE J588f.

5. An auxiliary side mounted signal shall be installed on the sides of the body at approximately seat level, rub rail height, just to the rear of the service door on the right side and approximately opposite the driver's seat on the left side. These shall operate in conjunction with the turn signals. This subdivision applies to school buses of 30 feet or more in length. These lamps shall comply with SAE J914b.

(e) Each bus shall be equipped with a 4-way hazard warning operating unit which shall operate independently of the ignition or equivalent switch and when activated shall cause the turn signal lamps to flash simultaneously.

(f) The headlamps shall comply with SAE J579c.

(g) Each bus shall be equipped with a light designed to indicate when the high beam headlamps are lit and located to be visible to the driver.

(h) Each bus, 80 or more inches wide, shall be equipped with 3 amber identification lamps to the front and 3 red identification lamps to the rear with lamp centers no less than 6 inches nor more than 12 inches apart. No part of the front lamp or mountings shall be below the top of the bus windshield.

(i) Each bus, 30 feet or more in length, shall be equipped with intermediate side marker lamps meeting SAE J592f mounted no less than 15 inches above the road surface and at or near mid-point between the front and rear side marker lamps.

(j) Each bus shall have a license plate lamp to illuminate the rear license plate. The lamp shall meet the standards of SAE J587.

(k) Each bus shall be equipped with side marker lights. One amber lamp shall be located on the side as far forward as possible and one red lamp shall be located as far rearward as practicable. The lamps shall conform to SAE J592.

(L) There shall be 2 red stop lamps meeting the requirements of SAE J586 mounted on the rear, one on each side of the vertical centerline at the same height and as far apart as practicable. Type A-I, B, C or D buses shall be equipped with lamps at least 7 inches in diameter or with at least 38 square inches of surface area if not round. The stop lamps shall activate upon application of the service brakes.

(m) There shall be 2 red tail lamps meeting the requirements of SAE J585e mounted on the rear, one on each side of the vertical centerline at the same height and as far apart as practicable. The tail lamps shall activate in conjunction with the headlamps. Two additional tail lamps may be utilized and incorporated in the stop lamp described in par. (L).

(n) There shall be reflex reflectors mounted on the bus located as follows:

1. On the rear, 2 red reflectors equally spaced as far apart from the center as practicable.

2. On the side, 2 reflectors; one amber at or near the front and one red at or near the rear.

3. On the side of buses 30 feet or more in length, one amber reflector located at or near the center.

4. Each reflector shall be mounted no less than 15 inches nor more than 60 inches above the road surface.

(2) Noncontrasting reflective tape or sheeting may be used on a school bus as an additional warning device.

(3) Any lamp, light, or reflector shall be replaced only with a unit meeting the standards of this section.

(4) School buses painted as provided in s. 347.44, Stats., and registered prior to October 1, 1998, may be equipped with a strobe light meeting the requirements of sub. (1) (am).

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83; am. (1) (intro.), (a) 1. intro., b., 2., 11., 12., (c), (d) 1., 5., (e), (h) to (m), (2), (4) (c), (d), Register, February, 1995, No. 470, eff. 3-1-95; am. (1) (a) 1. intro., b., 3. and 9., (d) 1., (L) and (4) (a), Register, December, 1997, No. 504, eff. 1-1-98; cr. (1) (am) (intro.), 6. and (4), r. (4) (intro.), renum. (4) (a) to (d) to be (1) (am) 1. to 4. renum. and am. (4) (e) to be (1) (am) 5., Register, April, 1999, No. 520, eff. 5-1-99; CR 03-116: am. (1) (a) 1. c., 2., 9., (d) 1. and (L) Register April 2004 No. 580, eff. 5-1-04; CR 15-069: am. (1) (intro.), (a) (intro.), cr. (1) (a) 1. d., 1m., am. (1) (a) 2., 4. to 10., 12., (am) (intro.), 1.

Register April 2016 No. 724, eff. 5-1-16; correction in (1) (a) (intro.) made under s. 35.17, Stats. Register April 2016 No. 724.

Trans 300.55 Mirrors. (1) School bus mirrors shall comply with the requirements in 49 CFR 571.111 and FMVSS 111. In addition, type A-I, B, C or D buses shall comply with the following:

(a) There shall be one interior rearview mirror of at least 6 by 30 inches. The mirror shall be so constructed that the corners are rounded and the edges are smooth or protected.

(b) An optional convex mirror may be mounted on the inside rear of the school bus.

(c) There shall be 2 outside rearview mirrors, one to the right and one to the left of the driver. Each mirror shall have not less than 50 square inches of unobstructed reflective surface and shall be firmly supported and adjustable to give the driver a clear view past both the right and left rear of the bus.

(d) There shall be an adjustable convex mirror or equivalent "banana type mirror" mounted on the right side to provide an additional close-in field of vision from the front of the bus rearward. This mirror may be mounted on the bracket required for the cross view mirror. The mirror required in this paragraph shall be independently adjustable. It shall have at least a 7 inch diameter face.

(2) Type A-II buses shall have an interior and 2 exterior rearview mirrors, one on the right and one on the left side of the bus capable of reflecting a view past the rear of the bus. Mirrors may not have sharp corners or edges.

(3) All buses shall be equipped with 2, 7-inch diameter convex mirrors or an equivalent "banana type mirror" which shall be mounted on the right and left sides in such a manner that the driver may observe a reflection of the road from beneath the front bumper forward to a point where direct observation is possible through each mirror.

(4) Each mirror required in this section may not be broken, cracked or discolored.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83; am. (1) (intro.), (3), renum. (1) (b) and (c) to be (1) (c) and (d) and am., cr. (1) (b), Register, February 1995, No. 470, eff. 3-1-95; am. (1) (intro.), (2) and (4), Register, December, 1997, No. 504, eff. 1-1-98.

Trans 300.56 Mounting of body. (1) The chassis frame for body-on-chassis type buses shall extend to the rear edge of the rear body cross member. Insulating material used at body to frame contact points shall be so attached that it will remain in position under any anticipated maintenance or bus operating conditions.

(2) The body shall be securely fastened to the chassis frame. Every body attachment device shall be securely fastened and maintained with proper tension.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83.

Trans 300.57 Openings. (1) All openings in the floorboard or firewall, between chassis and passenger compartment, such as for the gear shift lever and auxiliary brake lever, shall be sealed to prevent fumes or foreign material from entering the passenger compartment.

(2) Every school bus shall be free of rusted or deteriorated areas which could permit the entrance of foreign substance into the interior of the vehicle.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83.

Trans 300.58 Rub rails. (1) Every bus shall contain a rub rail located at seat cushion level. Except at the emergency door, rear compartment or special service door, the seat cushion level rub rail shall extend from the rear side of the service door completely around the bus body, to a point of curvature near the front of the body on the left side. On a type A-II bus, the seat cushion level rub rail is not required to extend around the rear corners of the bus and may terminate at the radii of the right and left rear corners.

(2) There shall be one floor line rub rail. This rub rail shall be located in an area so that the center of the rub rail is located at or between the following points:

(a) No more than 7 inches above the top of the steel floor, or

(b) No more than 5 inches below the top of the steel floor. The floor line rub rail shall extend over the same longitudinal distance as the seat level rub rail, except where it meets the wheel housing, fuel filler caps, fuel fill doors, side marker lights and may terminate at the radii of the right and left rear corners.

(3) Rub rails shall be constructed of 16 gauge longitudinally corrugated or ribbed steel, or material with strength at least equivalent to all-steel, as certified by the bus body manufacturer, of 4-inch minimum width, flange to flange. Each rub rail flange shall be attached at each body post and all other upright structural members.

(4) Rub rails that are pressed in or snapped on do not meet the requirements of this section and are not permitted.

(5) Rub rails applied to transit type buses with the engine in the rear may terminate at the forward edge of the engine compartment.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83; am. (1), (2), r. (6), Register, February, 1995, No. 470, eff. 3-1-95; am. (1) and (3), Register, December, 1997, No. 504, eff. 1-1-98.

Trans 300.59 Seating. (1) All seats shall be forward facing and securely fastened to that part or parts of the body which support them. Passenger seat cushions shall be fastened to prevent the cushions from disengaging from the seat frames in event of an accident. There shall be a minimum space of 24 inches between the forward surface of a seat back and the rear surface of the seat or barrier ahead measured across the seat cushion without depressing any surface. The forward surface of seat backs may have side bolsters that briefly reduce the width to less than 24 inches provided the remainder of the seat measures at least 24 inches.

(2) The forwardmost seat on the right side of the bus shall be located so as not to interfere with the driver's vision.

(3) A minimum of 36 inches of headroom for the sitting position above the top of the undepressed cushion line of all seats shall be provided. The measurement shall be made vertically not more than 11 inches from the side wall at cushion height and at the fore and aft center of the cushion.

(4) (a) The backs of seats of similar size shall be of the same width at the top and of the same height from the floor and shall slant at the same angle with the floor. The top corners, and at least 10 inches of the top of the back surface of the seat backs shall be padded sufficiently to reduce the likelihood of injury upon impact. Seat cushions and seat backs may not have any torn or worn-through covering material.

(b) The seat back of the rearmost seat shall be of the same dimension as the seat immediately forward. Failure to comply with this standard will result in the loss of one seating position, or 2 seating positions if this situation occurs in both rows, when determining the capacity of the bus. This requirement shall apply only to type A-I, B, C or D school buses manufactured after January 1, 1984.

(5) Fold down, fold up or reclining seats or seat backs is not permitted in a school bus except as allowed in s. Trans 300.33 (3).

(6) A child restraint seat may be installed in place of a standard seat. The replacement seat shall meet all of the requirements in this section, except that the seat back may exceed the seat height of the remaining bus seats by not more than 4 inches.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83; am. (4) (b), (5), cr. (6), Register, February, 1995, No. 470, eff. 3-1-95; am. (4) and (5), Register, December, 1997, No. 504, eff. 1-1-98; CR 03-116: am. (1) Register April 2004 No. 580, eff. 5-1-04.

Trans 300.60 Service door. (1) The service door shall be under control of the driver and so designed as to prevent acci-

dental opening. When a hand lever is used, no parts shall come together so as to shear or crush any fingers.

(2) The service door shall be located on the right side of the bus and within the view of the driver.

(3) The service door shall have a minimum horizontal opening of 24 inches and a minimum vertical opening of 68 inches.

(4) The upper and lower glass panels of the service door shall be of safety glass. The bottom of the lower glass panel may not be more than 35 inches from the ground when the bus is unloaded. The top of the upper glass panel may not be more than 6 inches from the top of door. The upper glass panel shall be of insulated glass or of a thermo electric design that performs at least as well as insulated glass.

(5) Any lock used in conjunction with the service door must be constructed to insure that the door is not in the locked position while transporting passengers.

(6) The service door shall be equipped with a seal to prevent dust and cold air from entering the vehicle.

(7) Type A-II buses need not comply with subs. (3) and (4).

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83; am. (4), (5), r. (8), Register, February, 1995, No. 470, eff. 3-1-95; am. (4) and (7), Register, December, 1997, No. 504, eff. 1-1-98; CR 03-116: am. (4) Register April 2004 No. 580, eff. 5-1-04.

Trans 300.61 Signs and lettering. (1) Only signs and lettering approved by state law or rule shall appear on or in the bus.

(2) The body shall bear words "School Bus" in black letters at least 8 inches high and one-inch stroke on both front and rear or on yellow signs attached thereto. The lettering shall be placed above the rear window and the front windshield. This lettering shall only appear on buses painted the yellow and black school bus colors and meeting all the requirements of this chapter.

(3) Each school bus painted the yellow and black color scheme shall have a fleet number consisting of no more than 4 digits. The fleet number shall appear on the front and the rear of the bus. Additional fleet number locations may be utilized at the owner's option.

(4) Fleet numbers shall be no less than 3 inches nor more than 6 inches high with a 1/2 inch brush stroke.

(5) Fleet numbers are prohibited in the black area around the alternately flashing red lights.

(6) The name and address (and telephone number, if desired) of the owner or operator shall be displayed below the window line in the panel to the rear of, and as close as possible to, the service door in letters not less than 2 inches high nor more than 3 inches high by 1/4 inch stroke. If desired, this marking may also be painted on the left side of the bus below the driver's window. Owner's decals may be used to comply with this subsection if the decals do not violate other provisions of this section.

(7) The name of the school bus firm may appear on the sides of the bus between the seat line rub rail and the bottom window line in contrasting yellow or black letters not more than 10 inches high. The owner's name may also appear on the rear bumper in school bus yellow. The lettering may not exceed 6 inches in height with a 1/2 inch brush stroke. These options do not relieve the owner or operator from the requirements of sub. (6).

(8) The vehicle's registration card or a photocopy of the card shall be displayed in the driver's compartment and shall be mounted in a holder so the card can be read without removal. The passenger capacity shall appear on the inside of the bus above the front windshield so it can be easily read. It shall indicate the number of seated passengers that may legally be transported. Each wheelchair position shall be counted as a seated passenger.

(9) Each school bus with an emergency exit shall have the exit identified as required in s. Trans 300.39.

(9m) On or after August 1, 2016, each school bus equipped with an eight light warning system shall have contrasting black lettering indicating the word "STOP" centered on the rear emer-

gency door panel in 8 x 1 inch minimum letters with the words "ON FLASHING RED" directly below and centered in 4 ½ x ½ inch minimum letters. When a rear emergency door is not present this lettering shall be placed in a visible location on the rear of the school bus body as close to the centerline as practicable. This lettering may be reflective material or have a reflective background. An optional driver alert message board may be used in lieu of the required lettering if utilizing a high intensity or LED lights that flash similar cautionary messages in two inch high minimum letters. Amber cautionary messages may flash when the hazard lights or amber warning lights are activated and a red warning message, similar to the required lettering, shall flash when the red warning lights are activated.

(10) The following signs are the only other decals, stickers, or lettering that may appear on the bus:

(a) No smoking, eating or drinking, (maximum 2-inch high letters).

(b) Any signs required by the federal bureau of motor carrier safety or national highway traffic safety administration.

(c) Identification as to location of emergency equipment.

(d) Seat belt use required in this vehicle.

(e) A seating chart, which shall not exceed a maximum size of 8½ x 11 inches. Numbers designating rows may be placed above the windows on both sides. They shall be black, no taller than 2 inches. They shall be permanent and legible by either painting or decal placement. They shall not interfere with emergency door or window markings.

(f) One page of rules pertaining to passenger conduct located in the drivers compartment above the windshield on the front bulkhead, which shall not exceed a maximum of 8½ x 11 inches.

(g) Any decal denoting membership in an association dealing with school transportation. The decal shall be placed within 12 inches to the rear of service door and below window line. It may not exceed 36 square inches.

(gm) For vehicles powered by alternative fuels such as liquefied petroleum gas, compressed natural gas or electric propulsion a designator may be placed on a lower rear corner. This designator may also be on the right side and displayed below the window line in the panel to the rear of, and as close as possible to, the service door. If desired, this designator may also be displayed on the left side, below the driver's window. It may not exceed 64 square inches and shall identify the alternative fuel used. A school bus that is utilizing an alternative fuel may have the manufacturer's logo or background colored green.

(h) A sign or lettering indicating the type of fuel used. This may be an industry recognized symbol as the background containing the appropriate lettering or abbreviation designating the type of fuel.

(i) A placard, decal or other device, not to exceed 90 square inches in size, to identify the bus to the children.

(j) Emergency telephone number may be placed in the driver's compartment in accordance with the following criteria:

1. The device the numbers are displayed on may not exceed 5 inches by 7 inches and may include a current calendar.

2. Acceptable emergency telephone numbers: police, fire, rescue squad, school bus contractor, and school transportation director or administrator.

(k) A legal disclaimer, not to exceed 5 x 7 inches, may be displayed in the drivers compartment to advise passengers that they may be video or audio recorded.

(L) A United States flag decal or magnet, not to exceed 6 inches on any side, may be displayed in the drivers compartment provided it does not interfere with any operating controls or other safety signs and equipment. It shall not include any sayings or slogans and may not be placed on the mirror, visor, windshield or any other window.

(m) A decal, sticker or lettering stating, "DO NOT USE THE LAST TWO SEATS UNLESS BUS IS FULL", is permissible to be placed on the rear bulkheads. The letters are to be black and are not to exceed 2 inches high. They are to be permanent and legible by either painting or decal placement.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83; am. (7), cr. (10) (gm), (j), r. (11), Register, February, 1995, No. 470, eff. 3-1-95; am. (7) and (10) (j) 1., Register, December, 1997, No. 504, eff. 1-1-98; CR 15-069: am. (2), (7), cr. (9m), am. (10) (e), (f), r. and recr. (10) (gm), am. (10) (h), cr. (10) (k) to (m); correction in (10) (k) made under s. 35.17, Stats., Register April 2016 No. 724, eff. 5-1-16.

Trans 300.62 Steering. (1) Steering systems shall comply with 49 CFR 393.209. No changes may be made in the steering apparatus without the approval of the chassis manufacturer.

(2) There shall be a clearance of at least 2 inches between the steering wheel and the cowl, instrument panel, windshield, or any other surface.

(3) The steering components may not be loose, worn, or binding and steering stops shall be adjusted so the tire does not rub at any point. The steering wheel lash may not exceed that found in 49 CFR 393.209 (b).

(4) The power steering system may not leak nor shall the drive belt be cracked, frayed or worn.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83; am. (1), (3), Register, February, 1995, No. 470, eff. 3-1-95; am. (4), Register, December, 1997, No. 504, eff. 1-1-98.

Trans 300.63 Steps. (1) The first step at the service door may not be more than 16 inches from the ground.

(2) The riser of any step may not be more than 15 inches. If there are 2 or more risers, they shall be approximately equal in height.

(3) The step may not protrude beyond the widest part of the body.

(4) Each step shall be covered with or constructed of nonskid material.

(5) All steps shall be enclosed to prevent the accumulation of ice or snow except the first step of a type A-II bus which may have an exposed step with a slip resistant surface.

(6) Each bus shall be equipped with a stepwell light which activates automatically upon opening of the service door to illuminate the steps. This light is not required to be operational during daylight hours. However, it must be in a working condition at all times.

(7) Each school bus shall be equipped with a grab handle at least 10 inches in length, located inside the service door entrance for providing assistance to enter or leave the bus.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83; am. (2), (6), (7), Register, February, 1995, No. 470, eff. 3-1-95; am. (1), (2) and (5), Register, December, 1997, No. 504, eff. 1-1-98.

Trans 300.64 Stop signal arm. (1) A stop signal arm which meets FMVSS 131 and SAE J1133 is required on every school bus painted with the yellow and black color scheme. The stop signal arm may not be extended until the bus is completely stopped.

(2) The stop signal arm shall be installed in such a manner that it cannot be activated unless the alternately flashing red lamps are in operation.

(3) The following specifications shall govern installation of the stop signal arm:

(a) It shall be a metal, or material with strength at least equivalent to all-steel, as certified by the bus body manufacturer, octagon-shaped sign at least 18 inches wide and 18 inches long exclusive of the mounting bracket. All sheet metal parts shall be 16 gauge or heavier.

(b) It shall have the word "STOP" on both sides in white letters at least 6 inches high and 7/8 inch wide on a bright red background. The outer edge shall have a white border at least ½ inch wide. All other parts of the assembly shall be painted black.

(c) It shall be equipped with 2, 4-inch or larger, double faced alternating flashing red lamps to be mounted near the perimeter of the sign with a minimum of 12 inches spacing between lamp centers. These lamps shall be wired to the circuit of the flashing red warning lamps mounted on the front and rear of the bus. These lamps may be strobe lamps or light emitting diodes. In lieu of the 2 double faced alternating flashing red lamps, the stop signal arm may be equipped with red flashing, high visibility light-emitting diodes incorporated into the word "STOP," in accordance with the requirements of sub. (3) (b).

(4) Reflectorizing of the sign shall be optional.

(5) The stop signal arm shall be mounted on the left side of bus as close to the driver's window as practicable.

(6) The requirements of this section for the operation of the stop signal arm does not apply to school buses which are operated only in areas where use of the flashing red warning lights is not permitted.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83; am. (1), (3) (c), (6), Register, February, 1995, No. 470, eff. 3-1-95; emerg. am. (3) (a) and (c), eff. 7-1-97; am. (1), (2) (3) (a), (c) and (6), Register, December, 1997, No. 504, eff. 1-1-98; CR 03-116: am. (2) and (3) (c) Register April 2004 No. 580, eff. 5-1-04.

Trans 300.65 Sunshield. Each school bus shall have an interior sunshield installed above the windshield. Each type A-I, B, C or D bus shall have one of a size not less than 6 by 16 inches.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83; am. Register, December, No. 504, eff. 1-1-98.

Trans 300.66 Suspension system. (1) (a) The suspension system shall comply with the requirements in 49 CFR 393.207. The bus shall be equipped with front and rear shock absorbers.

(b) The shock absorbers shall be maintained free of leaks and all mountings shall be in good working order.

(2) A school bus may not be operated with any broken spring-leaf or worn, loose, mislocated shackles or "U" bolts.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83; renum. (1) to (3) to be (1) (a), (b) and (2) and am. (1) (a), Register, February, 1995, No. 470, eff. 3-1-95; am. (2), Register, December, 1997, No. 504, eff. 1-1-98.

Trans 300.67 Tires. (1) The front tires shall have tread depth of at least 4/32-inch and rear tires shall have tread depth of at least 2/32-inch around the entire periphery measured at 2 points no less than 15 inches apart in any major tread groove.

(2) A school bus may not be operated with regrooved, recapped, or retreaded tires on the front wheels.

(3) A school bus may not be operated with cuts or chunks missing exposing the cord, recaps peeled loose or off, or showing an indication of ply separation.

(4) Tires of different size or ply rating may be used except that all tires on an axle must be the same size and type. Bias and radial tires may not be mixed.

(5) All tires shall be maintained to meet the manufacturer's GAWR and GVWR.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83; am. (4), Register, February, 1995, No. 470, eff. 3-1-95; am. (2) and (3), Register, December, 1997, No. 504, eff. 1-1-98.

Trans 300.68 Wheels. (1) A bus may not be operated with any cracked rims, loose lug bolts or nuts or elongated stud holes.

(2) The wheel bearings may not have more than 1/4 inch free play when measured at the tire level.

(3) The following measurements are the maximum amount of play permitted in the king pins or ball joints when measured at the outside of the tire:

(a) When the wheel diameter is 16 inches or less, not more than 1/4 inch play is permitted.

(b) When the wheel diameter is greater than 16 inches the play permitted is 3/8 inch.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83; am. (2), (3) (a) and (b), Register, December, 1997, No. 504, eff. 1-1-98.

Trans 300.69 Windows. (1) In this section:

(a) "ANS Z26.1" means the standards for glazing in land vehicles adopted by reference in s. Trans 300.20 (1) (k), under 49 CFR part 571, motor vehicle safety standard 205, glazing materials.

(b) "AS 1" to "AS 11" have the same meaning as in section 6 of ANS Z26.1.

(c) "AS 12" means a safety plastic material that includes all of the following:

1. Complies with tests 10, 13, 16, 17, 21, and 24 of ANS Z26.1.

2. Complies with tests 19 and 20 of ANS Z26.1 with the exception of the test for resistance to undiluted denatured alcohol.

3. In new buses or in replacement glazing has affixed a manufacturer's label specifying instructions and agents for cleaning the glazing that will minimize the loss of transparency.

(d) "AS 13" means a safety plastic material that includes all of the following:

1. Complies with tests 16, 22 and either 23 or 24 of ANS Z26.1.

2. Complies with tests 19 and 20 of ANS Z26.1 with the exception of the test for resistance to undiluted denatured alcohol.

3. In new buses or in replacement glazing has affixed a manufacturer's label specifying instructions and agents for cleaning the glazing that will minimize the loss of transparency.

(2) The glazing in windows to the right and left of the driver shall be identified by the designation AS 1 or AS 2. The rearmost windows shall be designated AS 1, AS 2, AS 4 or AS 5, except that the lower glazed portion of the emergency door may be designated AS 8. Any other side push-out or kick-out windows may be identified with glazing designated as AS 1, AS 2, AS 3, AS 4, AS 5, AS 12, or AS 13.

(3) On type A-I, B, C or D buses, the window to the driver's immediate left and the window immediately to the rear of the service door shall be of insulated glass or of a thermo electric design that performs at least as well as insulated glass. Exceptions are cutaway van based vehicles manufactured in 2 stages equipped with a driver's door and a roll-up window. If a lift and lift door are located immediately to the rear of the service door, the window in the lift door is not required to meet this requirement. The window to the rear of the lift door may be glazing applicable to other windows.

(4) Each full side window shall provide a vertical opening of at least 9 inches, obtained by lowering the top portion of the window. The driver's window may be of a sliding forward and rearward construction. A type A-II bus having windows which do not open from the top shall have no more than a 5-inch wide opening.

(5) All windows shall operate freely. The side window latches shall be capable of holding the window securely in place in all positions.

(6) All exposed edges shall be banded or ground.

(7) A distinctive audible signal automatically operated shall clearly indicate to the driver the unlatching of an emergency window when the ignition is in the "on" position. A cut-off may not be installed in the circuit.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83; am. (1) (a), (c) 3., (d) 3., (2), (3), Register, February, 1995, No. 470, eff. 3-1-95; am. (1) (c) (intro.), 1., 2., (d) (intro.), 1., 2., (3), (4) and (7), Register, December, 1997, No. 504, eff. 1-1-98; CR 03-116: am. (3) Register April 2004 No. 580, eff. 5-1-04.

Trans 300.70 Windshield. (1) The glass in the windshield shall be laminated safety glass identified by the designation AS 1. This mark shall be visible and legible. The glass shall be of such quality as to prevent distortion of view in any direction.

(2) The windshield may not be obstructed.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83; am. (2), Register, December, 1997, No. 504, eff. 1-1-98.

Trans 300.71 Windshield washer. (1) Each school bus shall be equipped with an operational windshield washer system that provides fluid for the windshield wipers to effectively clean the windshield.

(2) The washer shall be maintained and operational.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83.

Trans 300.72 Windshield wipers. Every school bus shall be equipped with 2 complete and operational windshield wipers. The system shall have at least 2 speeds.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83.

Trans 300.73 Wiring. All circuits of the bus shall be protected by a circuit breaker, field effect transistors, or fuse of sufficient rating to handle the current load.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83; CR 03-116: am. Register April 2004 No. 580, eff. 5-1-04.

Subchapter III—Special Additional Requirements

Trans 300.75 Special service opening. (1) Every school bus used for transporting persons in wheelchairs shall have an enclosed door opening located on the right side of the vehicle which will permit the use of a ramp or lift.

(2) The door of the special opening shall be equipped with a device to hold it open.

(3) Each door shall have a window.

(4) The opening shall be equipped with material which seals out dirt, water, and fumes.

(5) There shall be a light which illuminates the platform and the area outside the opening.

(6) A drip molding shall be installed to effectively divert water from the opening.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83; am. (6), Register, February, 1995, No. 470, eff. 3-1-95.

Trans 300.76 Power lift or ramps. (1) Every school bus transporting persons in wheelchairs shall be equipped with either a power lift or ramp which utilizes the special service opening specified in s. Trans 300.75.

(2) If a school bus uses a ramp it shall have a nonslip material on the surface or may have a metal nonslip surface construction. The ramp shall be in a secured position while the bus is in motion. The ramp shall be at least 30 inches wide on the surface.

(3) A power lift may be of varying design and operation. A lift may be designed to cause only minor vehicle design change other than for the special service opening, or a different design lift may be built to raise or lower through the floor of the vehicle. Each of these designs shall have a minimum lifting capacity of 700 pounds. A label stating that the lift meets this requirement shall be either permanently affixed to the power lift in a visible location or the information may be permanently stamped in a visible location.

(4) The power source and mechanism of the lift shall be enclosed.

(5) The platform of the power lift shall be covered with nonslip material or it may be of nonslip construction. The surface shall be at least 30 inches wide.

(6) Every platform of a power lift shall be designed and constructed to prevent any movement when it is in the stored position. This requirement may be met by either a mechanical locking device or by the internal design of the lift.

(7) The power lift shall be so designed that the operator has positive control to move, stop, or reverse the lift travel at will. In addition, the lift shall be controlled by a limit switch or by-pass

valve which will immediately stop the direction of travel upon contact with the ground or a foreign object.

(8) The power lift shall be so designed that the platform does not fall in the event of a power failure.

(9) The platform shall have a device on the curb side to prevent any wheelchair from rolling off when the lift is in any horizontal position other than at ground level.

(10) The power lift shall be designed to prevent the operator or the person being transported from becoming entangled or crushed during the lift operation.

(11) When in the stored position, every power lift or ramp and its associated super structure shall have all exposed sharp edges, corners, and projecting parts padded to prevent injury in the event of contact in an accident. This requirement does not apply to the platform surface but shall apply to the sides of the platform if they are exposed and not concealed by a padded super structure or a padded barrier.

(12) If the lift does not include a padded super structure, the top of the door opening shall be covered with padding at least 2 inches high the entire width of the door opening.

(13) The lift control shall be interlocked with the vehicle brakes, transmission or door, or shall provide other appropriate mechanisms or systems, to ensure that the vehicle cannot be moved when the lift is not stowed and so the lift cannot be deployed unless the interlocks or systems are engaged.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83; am. (1), (3), (11), cr. (12), (13), Register, February, 1995, No. 470, eff. 3-1-95; am. (11), Register, December, 1997, No. 504, eff. 1-1-98.

Trans 300.77 Wheelchair fasteners. (1) Each wheelchair shall be secured to the bus with a fastening device with sufficient strength to:

(a) Retain the chair in the event the bus overturns.

(b) Prevent the chair from moving.

(c) Prevent the chair's wheels from leaving the floor in the event of a sudden stop or start.

(2) The fastening device may be either a metal locking unit that secures the wheelchair to the wall or floor or a webbing belt system that accomplishes the same purpose.

(3) No wheelchair may be attached to any door.

(4) A webbing belt system shall be secured to the bus at not less than 2 points. It shall be anchored in the bus frame, body posts or other metal structure. Interior paneling is not considered an adequate anchorage.

(5) A webbing belt used to secure the wheelchair to the body frame may not be used to also secure the passenger to the wheelchair.

(6) School buses manufactured and placed in operation after January 17, 1994, and transporting passengers in wheel chairs shall comply with FMVSS 222, school bus seating and crash protection. The wheel chairs shall be secured in the following manner:

(a) In a forward facing position.

(b) By wheel chair securement devices at 2 locations in the front and 2 locations in the rear.

(c) If a 3-wheel chair, each wheel location shall be secured.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83; cr. (6), Register, February, 1995, No. 470, eff. 3-1-95; am. (4) and (5), Register, December, 1997, No. 504, eff. 1-1-98.

Trans 300.78 Seats and restraints. (1) Seat frames may be equipped to accept seat belts or other types of restraints.

(2) Every occupant shall be secured to the wheelchair while being transported. This securement shall be separate and in addition to that required in s. Trans 300.77.

(3) Aisle-facing seats in buses transporting wheelchairs are permitted only over the wheel housing provided they are equipped

with a device to prevent a passenger from sliding off either end. These seats shall be permanently mounted and may not have a retractable seating surface.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83; am. (3), Register, February, 1995, No. 470, eff. 3-1-95; am. (3), Register, December, 1997, No. 504, eff. 1-1-98.

Trans 300.79 Communications. Every school bus used to transport special education or disabled students shall comply with the communication requirements found in s. Trans 301.14.

History: Cr. Register, February, 1995, No. 470, eff. 3-1-95.

Trans 300.80 Optional equipment. A school bus owner or operator shall use the following procedure to obtain authorization for equipment that is not specifically authorized by this chapter:

(1) Submit an authorization request for equipment installation to the administrator, division of state patrol, P.O. Box 7912, Madison, Wisconsin, 53707-7912.

(2) Equipment installation may only proceed following receipt of a letter of authorization from the administrator, or designee, of the division of state patrol.

(3) Provide for inspection of the vehicle and equipment if necessary.

History: Cr. Register, February, 1995, No. 470, eff. 3-1-95.

Trans 300.81 Authorized optional equipment. The following equipment is approved:

(1) **PUBLIC ADDRESS SYSTEM.** A school bus may be equipped with a permanently mounted public address system that allows the driver to communicate directions by voice to students outside the bus. Mounting of any external speakers may not interfere with driver visibility, mirrors or outside lights. Speakers may be mounted under the hood.

(2) **WIDE ANGLE REAR VIEW LENS.** A school bus may be equipped with a wide angle rear view lens mounted on the upper window of the emergency door. The lens may not cover more than 220 square inches. The lens shall be centered on the window and shall be permanently attached.

(3) **RESTROOM.** A restroom facility may be installed at the rearmost section of a school bus. Installation shall meet all statutes and rules related to such installation. The following conditions shall also apply:

(a) The restroom door shall be locked during pupil transportation.

(b) All walls shall be constructed of rigid material.

(c) The restroom or restroom door may not interfere with access to emergency exits.

(d) There may be no sharp edges or protrusions.

(4) **BACK-UP ALARM.** A school bus may be equipped with a back-up alarm system manufactured in accordance with any federal or state specifications.

(5) **AIR CONDITIONING UNITS.** A school bus may be equipped with air conditioning systems. The system shall be approved by the Wisconsin division of state patrol prior to installation.

(6) **AIR FOIL.** A school bus may be equipped with a yellow or black air foil system on the top rear. An air foil system shall be mounted so as not to interfere with the visibility of required lights and lettering.

(7) **CAMERA, AUDIO MONITOR OR RECORDING DEVICE / COMPUTER ANTENNA.** A school bus may be equipped with a camera, audio monitor or recording device, or computer antenna subject to the following conditions:

(a) When a device is mounted in the driver's compartment it shall be located so as to not interfere with movement into and out of step well area. When a camera is placed to view through the windshield it shall not be located to the left of the centerline of the school bus. The camera shall be mounted not more than 2 inches

below the upper edge of the area swept by the windshield wipers and located outside the driver's sight lines to the road, mirrors, highway signs and signals.

(b) The device may not interfere with driver visibility and passenger entrance and aisle.

(c) A device mounted in the rear of the school bus shall not protrude more than 6 inches forward of the rear bulkhead or from the ceiling.

(d) A maximum of two devices may be located near the middle of a school bus, if they do not protrude more than 4 inches and are located no more than 15 inches above the side windows that are not emergency exits, measured from the edge of the window frame directly to the device. The device or devices shall be mounted parallel to a seat back. If flush mounted, the device or devices may be located beyond the 15 inch separation from the side window.

(e) All devices shall be securely fastened and contained within a shatterproof housing. All exposed edges or sharp corners shall be protected or designed to prevent injury upon contact.

(f) External devices shall be contained within a shatterproof housing.

(g) A video display, if utilized, shall be mounted in the driver's compartment and within or in close proximity to the forward field of view of the driver. It shall not restrict visibility of the driver's sight lines to the road, mirrors, highway signs and signals, or affect operation of the school bus controls. The video display may be incorporated as part of the interior rear view mirror and display an image when the parking brake is applied, warning lamps are activated, or transmission is in reverse.

(8) **BLOOD-BORNE PATHOGEN KIT.** A school bus may be equipped with a blood-borne pathogen kit subject to the following conditions:

(a) The kit shall be mounted or located in the driver's compartment.

(b) The kit shall be labeled.

(9) **AIRFOIL.** A school bus may be equipped with an airfoil designed to reduce the accumulation of snow on the rear of the bus.

(10) **PASSENGER ADVISORY OR THEFT SYSTEM.** A school bus may be equipped with a passenger advisory / theft system as long as the system does not interfere with operation or identification of other school bus standards set forth in this rule.

(11) **NAVIGATIONAL DEVICE OR LAPTOP COMPUTER INSTALL.** A school bus may be equipped with a navigational device that meets the following requirements:

(a) The device is mounted within the driver's compartment.

(b) The device shall be mounted in a position where it does not obscure the driver's sight lines to the road, mirrors, highway signs and signals and it may not impede space within the aisle.

(c) The device shall be securely mounted.

(d) The display shall activate for navigational purposes only while the school bus is in motion. Distractive manipulation of the device is prohibited while the school bus is being driven. For the purposes of this section only, driven means operating a commercial motor vehicle, with the motor running, including while temporarily stationary because of traffic, a traffic control device, or other momentary delays such as picking up or discharging students. Driven does not include operating a school bus, with or without the motor running, when the school bus is legally stopped or parked upon the highway.

(e) Software programs, if utilized, shall be specific to school bus operations such as, but not limited to, passenger accountability, routing, navigation, emergency notification, tracking, messaging and equipment monitoring.

(f) The device shall be used with due regard to passenger safety. At no time shall operation of this device cause a distraction while operating the school bus.

(12) ADDITIONAL DRIVER OR PASSENGER SAFETY ITEMS. A school bus may be equipped with additional safety items such as a seat belt cutter with recessed razor blade, hand sanitizer, and automated external defibrillator or AED. These items shall be kept in the driver's compartment. Additional items may be authorized upon written approval of the Division of State Patrol.

History: Cr. Register, February, 1995, No. 470, eff. 3-1-95; am. (1), (3) (c) and (d), Register, December, 1997, No. 504, eff. 1-1-98; CR 03-116; r. and recr. (6) Register April 2004 No. 580, eff. 5-1-04; CR 15-069; am. (7) (intro.), r. and recr. (7) (a), am. (7) (b), cr. (7) (c) to (g), (9) to (12) Register April 2016 No. 724, eff. 5-1-16.

Subchapter IV—General Requirements

Trans 300.85 Replacement equipment. Any item of equipment if covered by a standard in this chapter shall, upon replacement, be replaced with an item meeting the original standard. Any modification of a school bus shall be in conformity with state rules in effect at the time of the modification.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83.

Trans 300.86 Enforcement policy. (1) The enforcement policy of the division of state patrol shall take into consideration the age, condition, and equipment of buses before granting approval for their continued use. The division may not permit the use of any bus for school transportation purposes which is deemed to be unsafe or unfit for such service.

(2) In construing and enforcing the provisions of this chapter, the act, omission or failure of any officer, agent, servant or other person acting for or employed by the registered owner or the lessee of the bus, whoever has control, done within the scope of employment is deemed to be the act, omission or failure of such registered owner or lessee. This subsection does not apply to violations of ch. 346, Stats., and s. Trans 300.16.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83; am. (2), Register, February, 1995, No. 470, eff. 3-1-95; correction in (2) made under s. 13.93 (2m) (b) 5., Stats., Register, August, 1996, No. 488; am. Register, December, 1997, No. 504, eff. 1-1-98.

Trans 300.87 Inspection procedures. (1) Upon notification by the department of transportation, or the department of public instruction, or any public school official, the owner or operator shall present all school buses for inspection at the time and

place designated or the department may, at its option, inspect the school buses at the owner's place of business. All school buses shall be inspected annually.

(2) A school bus inspection report shall be completed for each school bus inspected. A copy of the report shall be provided to the school bus owner and the respective school district. Upon completion of an inspection, a school bus shall be approved or disapproved. A school bus is approved when it is found that all requirements of this chapter are met. A school bus is disapproved if defects are noted and the school bus inspection report indicates that the vehicle is "out-of-service."

(3) It is unlawful for a person to operate or permit to be operated any school bus that:

(a) Is in violation of any requirement of this chapter.

(b) Requires repairs prior to any operation.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83; renum. to be (1) and am., cr. (2), (3), Register, February, 1995, No. 470, eff. 3-1-95.

Trans 300.88 Applicability. (1) School buses manufactured prior to March 1, 1995 shall be subject to the rules applicable at the time the vehicle was first registered as a school bus in Wisconsin. School buses subject to previous standards are less stringent.

(2) All school buses manufactured on March 1, 1995 or later shall be subject to this chapter and to the referenced federal motor vehicle safety standards in effect on the date of manufacture. The department shall consider the date of manufacture as being the date on which the second stage manufacturer or the school bus body manufacturer completes the installation of the body on the chassis or the date a single manufacturer completes the unit. In the case of a rebod, the completed rebod school bus has been remanufactured on March 1, 1995 or later and shall meet the requirements of this chapter and the referenced federal motor vehicle safety standards in effect on the date of the rebod.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83; renum. from Trans 300.89 and am., Register, February, 1995, No. 470, eff. 3-1-95.

Trans 300.89 Penalties. Violations of any provisions of this chapter shall be prosecuted under the governing statute. Where no penalty is provided, the violation shall be prosecuted as set forth in s. 85.16 (2), Stats.

History: Cr. Register, February, 1983, No. 326, eff. 3-1-83; renum. from Trans 300.91 and am., Register, February, 1995, No. 470, eff. 3-1-95.