WISCONSIN STATE ELECTRICAL CODE

Volume 2

History: The Electrical Code as it existed on November 30, 1961 was repealed and a new Electrical Code was created effective December 1, 1961.

TABLE OF CONTENTS

Volume 2

General Requirements and Definitions

ıg
Gase
G WASC
g

Chapter E 324 Concealed Knob-and-Tube Work E 328 Bare-Conductor Feeders E 330 Mineral Insulated-Metal Sheathed Cable, Type MI E 334 Armored Cable, Types AC, ACT, ACV and ACL E 336 Non-Metallic Sheathed Cable, Types NM and NMC E 338 Service-Entrance Cable, Types ASE, SE and USE E 339 Underground Feeder and Branch Circuit Cable, Type UF E 342 Non-Metallic Surface Extensions Underplaster Extensions E 344 Rigid Metal Conduit E 346 E 348 Electrical Metallic Tubing E 350 Flexible Metal Conduit Liquid-Tight Flexible Metal Conduit E 351 E 352 Surface Metal Raceways E 354 Underfloor Raceways E 356 Cellular Metal Floor Raceways E 358 Cellular Concrete Floor Raceways E 362 E 364 Wireways Busways E 370 Outlet, Switch and Junction Boxes, and Fittings E 373 Cabinets and Cutout Boxes E 374 Auxiliary Gutters E 380 Switches \mathbf{E} 384 Switchboards and Panelboards E 390 Prefabricated Buildings E 391 Trailers

Special Occupancies

Equipment for General Use

Lighting Fixtures, Lampholders, Lamps, Receptacles and

Transformers and Transformer Vaults (Including Secondary

		Special Occupancies
E	500	Hazardous Locations
Е	501	Class I Installations—Hazardous Locations
E	502	Class II Installations—Hazardous Locations
E	503	Class III Installations—Hazardous Locations
E	510	Hazardous Locations—Specific
E	511	Commercial Garages, Repair and Storage
\mathbf{E}	512	Residential Storage Garages

Motors, Motor Circuits and Controllers

E 513 Aircraft Hangars

E 400

E 402

E 410

E 422

E 430

E 445

E 450

E 470

E 480

Flexible Cords

Fixture Wires

Rosettes

Appliances

Generators

Ties) Capacitors

Resistors and Reactors

Storage Batteries

Chapter				
E 514 Gasoline Dispensing and Service Stations E 515 Bulk-Storage Plants				
E 516 Finishing Processes				
E 517 Flammable Anesthetics				
E 520 Theaters and Assembly Halls				
E 530 Motion Picture Studios and Similar Locations E 540 Motion Picture Projectors				
E 560 Farm Wiring				
Special Equipment				
E 600 Electric Signs and Outline Lighting				
E 610 Cranes and Hoists E 620 Elevators, Dumbwaiters, and Escalators				
E 620 Elevators, Dumbwaiters, and Escalators E 630 Electric Welders				
E 640 Sound-Recording and Similar Equipment				
E 650 Organs E 660 X-Ray Equipment				
E 665 Inductive and Dielectric Heat Generating Equipment				
E 670 Machine Tools				
Special Conditions				
E 700 Emergency Systems				
E 710 Over 600 Volts—General	Over 600 Volts—General			
720 Circuits and Equipment Operating at Less than 50 Volts 725 Remote-Control, Low-Energy Power, Low-Voltage Power and Signal Circuits				
E 730 Outside Branch Circuits and Feeders				
Communication Systems				
E 800 Communication Circuits				
E 810 Radio and Television Equipment				
Tables and Examples				
Tables Examples				
DDYNGID AL MADY EG				
PRINCIPAL TABLES				
Table Description				
E 210.25 Branch Circuit Requirements E 220.02 (3) (a) 2. General Lighting Loads by Occupancies				
E 220.04 (2) Calculation of Feeder Loads by Occupancies				
E 220.05 Demand Loads for Household Cooking Appli-				
ances Over 1% KW Rating E 220.06 Demand Factors for Household Electric Clothes				
Dryers E 220.07 Optional Calculation for One-Family Residence				
E 240.28 Number of Overcurrent Units, Such as Trip Coils or Relays, for Protection of Circuits				

i	Table	Description
	E 250.094 (1)	Sizes of Grounding Conductors
	E 250.094 (2)	Sizes of Grounding Conductors
	E 250.095	Sizes of Grounding Conductors
	E 310.02 (1)	Conductor Application
		Conductor Application Conductor Insulations
	E 310.02 (2)	
	E 310.02 (8) (a)	Thickness of Rubber Insulation for Rubber- Covered Wire and Cable, in 64ths of an Inch
	E 310.02 (8) (b)	Thickness of Varnished-Cambric Insulation for Single-Conductor Cable, in 64ths of an Inch
<u>.</u>	E 310.02 (8) (c)	Thickness of Varnished-Cambric Insulation for Multiple-Conductor Cable, in 64ths of an Inch
:	E 310.02 (8) (d)	Thickness of Asbestos and Varnished-Cambric Insulation for Single-Conductor Cable, Types AVA, AVB and AVL, in Mils
	E 310.12	Allowable Current-Carrying Capacities of Insulated Copper Conductors in Amperes
-	E 310.13	Allowable Current-Carrying Capacities of Insulated Copper Conductors in Amperes
]	E 310.14	Allowable Current-Carrying Capacities of Insulated Aluminum Conductors in Amperes
. 1	E 310.15	Allowable Current-Carrying Capacities of Insulated Aluminum Conductors in Amperes
]	E 346.10	Radius of Conduit Bends
1	E 350.03	Maximum Number of Conductors in %" Flexible Metal Conduit
]	E 370.06 (1) (a)	Deep Boxes
	E 370.06 (1) (b)	Shallow Boxes
]	E 370.06 (2)	Other Boxes
j	E 373.06 (1)	Width of Gutters
	E 374.09 (4)	Maximum Width of the Widest Surface of Gutters
	E 384.26	Spacings Between Bare Metal Parts
	E 400.09 (2)	Current-Carrying Capacity of Flexible Cord in Amperes
	E 400.11 E 402.04	Flexible Cord
		Allowable Current-Carrying Capacity of Fixture Wire
	E 402.06 E 430.007 (2)	Fixture Wire Locked Rotor Indicating Code Letters
	E 430.146	Overcurrent Protection for Motors
	E 430.147	Full Load Currents in Amperes—Direct Current Motors
I	E 430.148	Full Load Currents in Amperes, Single Phase Alternating Current Motors
I	E 430.149	Full-Load Current, Two-Phase AC Motors (4-wire)
	E 430.150	Full-Load Current, Three-Phase AC Motors
	E 430.151	Locked-Rotor Current Conversion Table
I	E 430.152	Maximum Rating or Setting of Motor-Branch- Circuit Protective Devices for Motors Marked with a Code Letter Indicating Locked Rotor KVA
•		

ş

Table	Description				
E 430.153	Maximum Rating or Setting of Motor-Branch- Circuit Protective Devices for Motors not Marked with a Code Letter Indicating Locked Rotor KVA				
E 610.14 (1)	Current-Carrying Capacity in Amperes of Insulated Conductors in Raceway or Cable Used with Short Time Rated Crane and Hoist Motors				
E 710.05 E 710.33	Shielding of Rubber-Insulated Conductors Minimum Air Separation in Inches, Indoors—				
	Circuits over 600 Volts				
E 710.37 E 710.38	Isolation by Elevation—Circuits over 600 Volts Working Space—Circuits over 600 Volts				
Chapter E 900—Tables and Examples					
	A. Tables				
1	Number of Conductors in Conduit or Tubing, Rubber and Thermoplastic				
2	Number of Conductors in Conduit or Tubing, Lead Covered				
3	Combination of Conductors				
4	Dimensions and Per Cent Area of Conduit and of Tubing				
5	Dimensions of Rubber-Covered and Thermoplas- tic-Covered Conductors				
6	Dimensions of Lead-Covered Conductors				
7	Dimensions of Asbestos-Varnished-Cambric Insulated Conductors				
8	Properties of Conductors				
9	Multiplying Factors for Converting DC, Resistance ance to 60 Cycle AC Resistance				
	B. Examples				
1	Single Family Dwelling				
2	Small Roadside Fruitstand With No Show Windows				
3	Store Building				
4	Multi-Family Dwelling				
5	Calculation of Neutral Feeder				
6	Maximum Demand for Range Loads				
7	Ranges on a 3-Phase System				
8	Motors, Conductors, and Overcurrent Protection				