



STATE OF WISCONSIN NATURAL RESOURCES BOARD

.....  
IN THE MATTER of creating Chapter .  
NR 221 of the Wisconsin Administrative .  
Code pertaining to Asbestos .  
Manufacturing .  
.....

ORDER NO. W-11-75 (I)

ORDER OF THE STATE OF WISCONSIN NATURAL RESOURCES BOARD

CREATING RULES

Pursuant to authority vested in the State of Wisconsin Natural Resources Board by sections 147.04(2), 147.04(5), 147.06, 147.07(2) and Chapter 227, Wisconsin Statutes, the State of Wisconsin Natural Resources Board hereby creates rules as follows:

## CHAPTER NR 221

### EFFLUENT LIMITATIONS AND STANDARDS

#### ASBESTOS MANUFACTURING

NR 221.01 Purpose. The purpose of this chapter is to establish effluent limitations, standards of performance, and pretreatment standards for discharges of process wastes from the asbestos manufacturing category of point sources and subcategories thereof.

NOTE: The authority for promulgation of this chapter is set forth in Wis. Adm. Code chapter NR 205.

NR 221.02 Applicability. The effluent limitations, standards of performance, pretreatment standards, and other provisions in this chapter are applicable to pollutants or pollutant properties in discharges of process waste resulting from manufacture or activities in any of the following subcategories.

(1) Asbestos - cement pipe. This subcategory covers the manufacture of pipe using asbestos, portland cement, silica, and other ingredients.

(2) Asbestos - cement sheet. This subcategory covers the manufacture of sheets using asbestos, portland cement, silica, and other ingredients excluding the manufacture of sheet laboratory tops.

(3) Asbestos paper - starch binder. This subcategory covers the manufacture of asbestos paper using asbestos, starch binders, and other ingredients.

(4) Asbestos paper - elastomeric binder. This subcategory covers the manufacture of asbestos paper using asbestos, elastomeric binders, and other ingredients.

(5) Asbestos millboard. This subcategory covers the manufacture of asbestos millboard using asbestos in combination with other materials such as cement, starch, clay, lime, and mineral wool.

(6) Asbestos roofing. This subcategory covers the manufacture of roofing products by saturating asbestos paper with asphalt or coal tar and applying various surface treatments.

(7) Asbestos floor tile. This subcategory covers the manufacture of asbestos floor tile using asbestos, polyvinyl chloride resin, chemical stabilizers, limestone, and other fillers.

(8) Asbestos textiles, coating or finishing. This subcategory covers the process of coating or impregnating asbestos textiles with materials to impart specific desired qualities to the finished product.

(9) Solvent recovery. This subcategory covers the process of solvent recovery in the manufacture of asbestos products.

(10) Vapor absorption. This subcategory covers the process of removing volatilized organic materials from atmospheric emissions by means of wet scrubbers.

(11) Wet dust collection. This subcategory covers the process of removing dust (particulates) from atmospheric emissions by means of wet scrubbers.

NR 221.03 Definitions. The following definitions are applicable to terms used in this chapter. Definitions of other terms and meanings of abbreviations are set forth in Wis. Adm. Code chapter NR 205.

- (1) "COD" means COD added to the process wastewater.
- (2) "Mpc" means 1,000 pieces of floor tile.
- (3) "pieces" means floor tile in the standard 12x12x3/32 inch size.
- (4) "std" means standard conditions for measuring gas volume.

NR 221.04 Compliance with effluent limitations and standards. Discharge of pollutants from facilities subject to the provisions of this chapter shall not exceed, as appropriate:

(1) by July 1, 1977 effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available;

(2) by July 1, 1977 pretreatment standards for existing discharges to publicly owned treatment works;

(3) by July 1, 1983 effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable;

(4) standards of performance for new sources; or

(5) pretreatment standards for new sources discharging to publicly owned treatment works.

NR 221.05 Modification of effluent limitations. (1) Effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available may be modified in accordance with this section.

(2) An individual discharger or other interested person may submit evidence to the department that factors relating to the equipment or facilities involved, the process applied, or other such factors related to such discharger are fundamentally different from the factors considered in the establishment of the effluent limitations. On the basis of such evidence or other available information the department will make a written determination that such factors are or are not fundamentally different from that facility compared to those specified in either the Building, Construction, and Paper or the Textiles, Friction, and Sealing Devices Development Documents, respectively EPA 440/1-74-017-a published February 1974, or EPA 440/1-75-035-a published January 1975. If such fundamentally different factors are found to exist, the department shall establish for the discharge effluent limitations in the WPDES permit either more or less stringent than the limitations in this chapter, to the extent dictated by such fundamentally different factors. Such limitations must be approved by EPA which may approve, disapprove, or specify other limitations. Copies of these Development Documents are available for inspection at the office of the department of natural resources, the secretary of state's office, and the office of the revisor of statutes, and may be obtained for personal use from the Superintendent of Documents, U.S. Government Printing Office, Washington, D. C. 20460.

NR 221.06 Application of effluent limitations and standards. (1) The effluent limitations and standards set forth in this chapter shall be used in accordance with this section to establish the quantity or quality of pollutants or pollutant properties which may be discharged by a point source subject to the provisions of this chapter, except as;

- (a) they may be modified in accordance with section NR 221.05,
- (b) they may be superseded by more stringent limitations and standards necessary to achieve water quality standards or meet other legal requirements, or
- (c) they may be supplemented or superseded by standards or prohibitions for toxic pollutants or by additional limitations for other pollutants required to achieve water quality.

(2) The production basis for application of the limitations and standards set forth in this chapter shall be the daily average of a maximum month in each subcategory subject to the provisions of this chapter.

NR 221.10 Effluent limitations, best practicable treatment. The following effluent limitations for all or specific subcategories establish, except as provided in section NR 221.05, the quantity or quality of pollutants or pollutant properties which may be discharged by a facility subject to the provisions of this chapter after application to process wastes of the best practicable control technology currently available.

(1) For subcategories (5), (8) and (10) identified in section NR 221.02 there shall be no discharge of process wastewaters to surface waters.

(2) The pH of all discharges shall be within the range of 6.0 to 9.0.

(3) The 30-day average and daily maximum limitations for suspended solids and COD are set forth in table 1;

(a) for subcategories (1), (2), (3), (4), (6) and (9) in lbs/1000 lbs. or kg/1000 kg. of product,

(b) for subcategory (7) in lbs/Mpc and below that in parenthesis in kg/Mpc, and

(c) for subcategory (11) in lbs/million std.cu.ft. and below that in parenthesis in kg/1000 std.cu.m. of air scrubbed.

TABLE 1  
BPT EFFLUENT LIMITATIONS

Subcategory*	Suspended Solids		COD	
	Average	Maximum	Average	Maximum
1	0.19	0.57		
2	0.23	0.68		
3	0.35	0.55		
4	0.35	0.55		
6	0.006	0.01	0.008	0.015
7	0.08 (0.04)	0.013 (0.06)	0.18 (0.09)	0.30 (0.14)
9	0.09	0.18	0.15	0.30
11	2.50 (0.04)	5.0 (0.08)		

\*Subcategories are as identified in section NR 221.02

NR 221.11 Effluent limitations, best available treatment. The following effluent limitations for all or specific subcategories establish the quantity or quality of pollutants or pollutant properties which may be discharged by a facility subject to the provisions of this chapter after application to process wastes of the best available technology economically achievable.

(1) For subcategory (9) identified in section NR 221.02 the pH of all discharges shall be within the range of 6.0 to 9.0 and the 30-day average and daily maximum limitations for suspended solids and COD are set forth in table 1 in lbs/1000 lbs. or kg/1000 kg. of product.

(2) For all other subcategories subject to the provisions of this chapter there shall be no discharge of process wastewaters to surface waters.

NR 221.12 Standards of performance. The following effluent limitations for all or specific subcategories establish the quantity or quality of pollutants or pollutant properties which may be discharged by a facility which is a new source subject to the provisions of this chapter.

(1) For subcategories (1), (4) and (9) identified in section NR 221.02 the pH of all discharges shall be within the range of 6.0 to 9.0 and the 30-day average and maximum daily limitations for BOD, suspended solids as are set forth in table 1 in lbs/1000 lbs. or kg/1000 kg. or product.

(2) For all other subcategories subject to the provisions of this chapter there shall be no discharge of process wastewaters to surface waters.

NR 221.13 Pretreatment standards for new sources. The pretreatment standards for discharges to publicly owned treatment works from new sources subject to the provisions of this chapter shall be as set forth in Wis. Adm. Code chapter NR 211. In addition the limitations for incompatible pollutants shall be those set forth in section NR 221.12, except as provided in Wis. Adm. Code section NR 211.30(2). For the purpose of this section COD is considered a compatible pollutant. Wastewaters from such new sources may not be discharged to publicly owned treatment works except in compliance with this section.

NR 221.14 Pretreatment standards for existing sources. (Reserved)


The foregoing rules were approved and adopted by the State of Wisconsin Natural Resources Board on December 20, 1974.

The rules contained herein shall take effect upon publication in the official state newspaper.

Dated at Madison, Wisconsin February 11, 1975

STATE OF WISCONSIN DEPARTMENT OF NATURAL RESOURCES

By

  
\_\_\_\_\_  
L. P. Voigt, Secretary

(SEAL)