

Chapter NR 295

SUGAR PROCESSING

(Interim Effluent Limitations)

NR 295.01	Purpose	NR 295.10	Effluent limitations, best practicable treatment
NR 295.02	Applicability	NR 295.11	Effluent limitations, best available treatment
NR 295.03	Definitions	NR 295.12	Standards of performance
NR 295.04	Compliance with effluent limitations and standards	NR 295.13	Pretreatment standards for new sources
NR 295.05	Modification of effluent limitations	NR 295.14	Pretreatment standards for existing sources
NR 295.06	Application of effluent limitations and standards		

Note: Pursuant to chapter 147 Wis. Stats. and under the procedure of section 227.027 Wis. Stats., the department of natural resources has promulgated interim effluent limitations which were effective February 28, 1975 and will remain in effect for one year. These interim effluent limitations will be periodically replaced by permanent effluent limitations.

NR 295.10 Purpose. The purpose of this chapter is to establish effluent limitations, standards of performance, and pretreatment standards for discharges of process wastes from the sugar processing category of point sources and subcategories thereof. 295.01

Note: The authority for promulgation of this chapter is set forth in Wis. Adm. Code chapter NR 205.

History: Cr. eff. 2-28-75.

NR 295.02 Applicability. The effluent limitations, standards of performance, pretreatment standards, and other provisions in this chapter are applicable to pollutants or pollutant properties in discharges of process waste resulting from operations in any of the following subcategories.

- (1) **BEET SUGAR.** This subcategory covers the processing of sugar beets to produce sugar.
- (2) **CRYSTALLINE CAN SUGAR.** This subcategory covers the processing of raw cane sugar into crystalline refined sugar.
- (3) **LIQUID CANE SUGAR REFINING.** This subcategory covers the processing of raw cane sugar into liquid refined sugar.

History: Cr. eff. 2-28-75.

NR 295.03 Definitions. The following definitions are applicable to terms used in this chapter. Definitions of other terms and meanings of abbreviations are set forth in Wis. Adm. Code chapter NR 205.

- (1) "Barometric condensing operations" means those operations or processes directly associated with or related to the concentration and crystallization of sugar solutions.
- (2) "Melt" means the amount of raw sugar in the aqueous solution at the beginning of the process of producing refined cane sugar.
- (3) "Net basis" means the amount of process pollutants added above those amounts present in the process water used.

- (4) "Product" means crystalized refined beet sugar.

History: Cr. eff. 2-28-75.

NR 295.04 Compliance with effluent limitations and standards. Discharge of pollutants from facilities subject to the provisions of this chapter shall not exceed, as appropriate:

(1) By July 1, 1977 effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available;

(2) By July 1, 1977 pretreatment standards for existing discharges to publicly owned treatment works;

(3) By July 1, 1983 effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable;

(4) Standards of performance for new sources; or

(5) Pretreatment standards for new sources discharging to publicly owned treatment works.

History: Cr. eff. 2-28-75.

NR 295.05 Modification of effluent limitations. (1) Effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available may be modified in accordance with this section.

(2) An individual discharger or other interested person may submit evidence to the department that factors relating to the equipment or facilities involved, the process applied, or other such factors related to such discharger are fundamentally different from the factors considered in the establishment of the effluent limitations. On the basis of such evidence or other available information the department will make a written determination that such factors are or are not fundamentally different for that facility compared to those specified in either the Beet Sugar Processing or Cane Sugar Processing Development Document, respectively EPA 440/1-74-002-b published January 1974, or EPA 440/1-74-002-c published March 1974. If such fundamentally different factors are found to exist, the department shall establish for the discharge effluent limitations in the WPDES permit either more or less stringent than the limitations in this chapter, to the extent dictated by such fundamentally different factors. Such limitations must be approved by EPA which may approve, disapprove, or specify other limitations. Copies of these Development Documents are available for inspection at the office of the department of natural resources, the secretary of state's office, and the office of the revisor of statutes, and may be obtained for personal use from the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20460.

History: Cr. eff. 2-28-75.

NR 295.06 Application of effluent limitations and standards.

(1) The effluent limitations and standards set forth in this chapter shall be used in accordance with this section to establish the quantity or quality of pollutants or pollutant properties which may be

discharged by a point source subject to the provisions of this chapter, except as;

- (a) They may be modified in accordance with section NR 295.05, ✓
- (b) They may be superseded by more stringent limitations and standards necessary to achieve water quality standards or meet other legal requirements, or
- (c) They may be supplemented or superseded by standards or prohibitions for toxic pollutants or by additional limitations for other pollutants required to achieve water quality.

(2) The production basis for application of the limitations and standards set forth in this chapter shall be the daily average of a maximum month in each subcategory subject to the provisions of this chapter.

History: Cr. eff. 2-28-75.

NR 295.10 Effluent limitations, best practicable treatment. The following effluent limitations for all or specific subcategories establish, except as provided in section NR 295.05, ✓ the quantity or quality of pollutants or pollutant properties which may be discharged by a facility subject to the provisions of this chapter after application to process wastes of the best practicable control technology currently available.

(1) The pH limitations and the 30-day average and daily maximum limitations for BOD₅ and suspended solids are set forth in table 1 for two types of discharges from each subcategory;

- (a) Discharges from barometric condensing operations only, and
- (b) Discharges from barometric condensing operations combined with discharges of other process wastes.

(2) The limitations for BOD₅ and suspended solids in table 1 are in lbs/1000 lbs. or kg/1000 kg. of product for the beet sugar subcategory and of melt for both cane sugar subcategories, and shall be on the net basis for either of the cane sugar subcategories where the type of discharges described in (b) ✓ above are mixed and cannot be separated for measurement.

(3) In addition to the limitations of (2) above, discharges from the beet sugar subcategory shall also be limited; ✓

- (a) For discharges described in (1) (a) ✓ above to the temperature acceptable for recirculation to the heat source or in any event not to exceed 90°F (32°C), and

- (b) For discharges described in (1) (b) ✓ above to a temperature of 90°F (32°C) and a fecal coliform MPN of 400/100 ml.

TABLE 1
BPT EFFLUENT LIMITATIONS

Subcategory*	Type of Discharge	Suspended Solids		BOD ₅		pH Range
		Average	Maximum	Average	Maximum	
(1)	(a)			2.2	3.3	6.0-9.0
	(b)	2.2	3.3	2.2	3.3	6.0-9.0
(2)	(a)			.34	1.02	
	(b)	.09	.27	.43	1.19	6.0-9.0
(3)	(a)			.15	.45	
	(b)	.17	.50	.32	.78	6.0-9.0

*Subcategory as identified in section NR 295.02

History: Cr. eff. 2-28-75.

NR 295.11 Effluent limitations, best available treatment. The following effluent limitations for all or specific subcategories establish the quantity or quality of pollutants or pollutant properties which may be discharged by a facility subject to the provisions of this chapter after application to process wastes of the best available technology economically achievable.

(1) For facilities in the beet sugar subcategory processing more than 2,300 tons (2,090 kkg) daily of sliced beets and located where the soil filtration rate in available areas is more than 1/16-inch (0.159 cm) per day there shall be no discharge of process wastes to surface waters.

(2) For facilities in the sugar beet subcategory processing a smaller quantity of sliced beets than is set forth in (1) above, and/or located where the soil filtration rate is less than set forth therein, the discharges shall be limited as set forth in (3) and (4) below.

(3) For facilities subject to the provisions of this chapter other than (1) above the pH limitations and the 30-day average and daily maximum limitations for BOD₅, and suspended solids are set forth in table 2. Limitations are set forth for two types of discharges from facilities described in (2) above;

(a) Discharges from barometric condensing operations only, and

(b) Discharges from barometric condensing operations combined with discharges of other process wastes.

(4) In addition to the limitations of (3) above discharges from facilities described in (2) above shall be limited as set forth in section NR 295.10 (3) (a) and (b).

TABLE 2
BAT EFFLUENT LIMITATIONS

Subcategory*	Type of Discharge	Suspended Solids		BOD ₅		pH Range
		Average	Maximum	Average	Maximum	
(1)	(a)			1.3	2.0	6.0-9.0
	(b)	1.3	2.0	1.3	2.0	6.0-9.0
(2)		.035	.11	.09	.18	6.0-9.0
(3)		.03	.09	.15	.30	6.0-9.0

*Subcategory as identified in section NR 295.02

History: Cr. eff. 2-28-75.

NR 295.12 Standards of performance. The following effluent limitations for all or specific subcategories establish the quantity or quality of pollutants or pollutant properties which may be discharged

by a facility which is a new source subject to the provisions of this chapter.

(1) For the beet sugar subcategory there shall be no discharge of process wastes to surface waters.

(2) For both cane sugar subcategories the pH limitations and the 30-day average and maximum daily limitations for BOD₅ and suspended solids are set forth in table 2.

History: Cr. eff. 2-28-75.

NR 295.13 Pretreatment standards for new sources. The pretreatment standards for discharges to publicly owned treatment works from new sources subject to the provisions of this chapter shall be as set forth in Wis. Adm. Code chapter NR 211. In addition the limitations for incompatible pollutants shall be those set forth in section NR 295.12, except as provided in Wis. Adm. Code section NR 211.30 (2). Wastewaters from such new sources may not be discharged to publicly owned treatment works except in compliance with this section.

History: Cr. eff. 2-28-75.

NR 295.14 Pretreatment standards for existing sources. The pretreatment standards for discharges to publicly owned treatment works from existing point sources subject to the provisions of this chapter shall be as set forth in Wis. Adm. Code chapter NR 211 except that section NR 211.30 shall not apply.

History: Cr. eff. 66-10-75.