Chapter ILHR 20

ADMINISTRATION AND ENFORCEMENT

Subchapter I—Purpose and Scope ILHR 20.01 Purpose. ILHR 20.02 Scope. ILHR 20.03 Effective date. ILHR 20.04 Applications. ILHR 20.05 Exemptions. Subchapter II—Jurisdiction	Subchapter V—Approval and Inspection of Manufactured Dwellings and Their ComponentsILHR 20.12Scope.ILHR 20.13Manufacture, sale and installation of dwellings.ILHR 20.14Approval procedures.ILHR 20.15Effect of approval.ILHR 20.16Suspension and revocation of approval.ILHR 20.17Effect of suspension and revocation.
ILHR 20.06 Procedure for municipalities exercising jurisdiction.	Subchapter VI—Approval of Materials
Subchapter III—Definitions	ILHR 20,18 Materials.
ILHR 20.07 Definitions.	Subchapter VII—Variances, Appeals, Violations and Penalties
Subchapter IV—Approval and Inspection of One- and 2-Family Dwellings ILHR 20.08 Wisconsin uniform building permit. ILHR 20.09 Procedures for obtaining uniform building permit.	ILHR 20.19 Petition for variance. ILHR 20.20 Municipal variance from the code. ILHR 20.21 Appeals of orders, determinations, and for extension of time. ILHR 20.22 Penaltics and violations.
ILHR 20.10 Inspections.	Subchapter IX—Adoption of Standards
ILHR 20.11 Suspension or revocation of Wisconsin uniform building permit.	ILHR 20.24 Adoption of standards.

Subchapter I—Purpose and Scope

1

ILHR 20.01 Purpose. The purpose of this code is to establish uniform statewide construction standards and inspection procedures for one- and 2-family dwellings and manufactured dwellings in accordance with the requirements of ss. 101.60 and 101.70, Stats.

Historyi Cr. Register, November, 1979, No. 287, eff. 6-1-80; am. Register, March, 1992, No. 435, eff. 4-1-92.

ILHR 20.02 Scope. The provisions of chs. ILHR 20 to 25 shall apply to the construction and inspection procedures used for all new one- and 2-family dwellings, manufactured buildings for dwellings and newly constructed community-based residential facilities providing care, treatment and services for 3 to 8 unrelated adults.

(1) MUNICIPAL ORDINANCES. (a) A municipality may not adopt an ordinance on any subject falling within the scope of this code including establishing restrictions on the occupancy of dwellings for any reason other than noncompliance with the provisions of this code as set forth in s. ILHR 20.10 (1) (c). This code does not apply to occupancy requirements occurring after the first occupancy for residential purposes following the final inspection required under s. ILHR 20.10 (1) (b) 4.

(b) This code shall not be construed to affect local requirements relating to land use, zoning, fire districts, side, front and rear setback requirements, property line requirements or other similar requirements. This code shall not affect the right of municipalities to establish safety regulations for the protection of the public from hazards at the job site.

(c) Any municipality may, by ordinance, require permits and fees for any construction, additions, alterations or repairs not within the scope of this code.

(d) Any municipality may, by ordinance, adopt the provisions of chs. ILHR 20 to 25 to apply to any additions or alterations to existing dwellings.

(2) LEGAL RESPONSIBILITY. The department or the municipality having jurisdiction shall not assume legal responsibility for the design or construction of dwellings.

(3) RETROACTIVITY. The provisions of this code are not retroactive, except as specified in s. ILHR 21.09.

(4) INNOVATIVE DWELLINGS. No part of this code is intended to prohibit or discourage the construction of innovative dwellings such as a dwelling built below ground, a geodesic dome, a concrete house, a fiber-glass house or any other nonconventional structure.

(5) LANDSCAPING. Except for construction erosion control, the scope of this code does not extend to driveways, sidewalks, landscaping and other similar features not having an impact on the dwelling structure.

History: Cr. Register, November, 1979, No. 287, eff. 6-1-80; am. (1) (intro.), cr. (1) (d), r. andreer. (6), Register, February, 1985, No. 350, eff. 3-1-85; r. (6), Register, January, 1989, No. 397, eff. 2-1-89; am. (3), Register, April, 1990, No. 412, eff. 5-1-90; am. (5), Register, September, 1992, No. 441, eff. 12-1-92; am. (1) (a), Register, November, 1995, No. 479, eff. 12-1-95.

ILHR 20.03 Effective date. The effective date of ch. ILHR 22 is December 1, 1978. The effective date of chs. ILHR 20, 21, 23, 24 and 25 is June 1, 1980.

History: Cr. Register, November, 1979, No. 287, eff. 6-1-80; am. Register, January, 1989, No. 397, eff. 2-1-89; correction made under s. 13.93 (2m) (b) 4., Stats., Register, January, 1989, No. 397.

ILHR 20.04 Applications. (1) NEW DWELLINGS. This code applies to all dwellings, dwelling units and foundations for dwelling units, for which the building permit application was made or construction commenced on or after the effective date of this code.

(2) ADDITIONS OR ALTERATIONS. Additions or alterations to dwellings covered by this code shall comply with all provisions of this code, including the soil erosion provisions, at the time of permit application for addition or alteration.

(3) RECREATIONAL DWELLINGS. Recreational dwellings, the initial construction of which was commenced on or after the effective date of this code, shall comply with all structural requirements of this code. The installation of any permanent heating, air conditioning, electrical or plumbing systems shall not be required; however, if such systems are installed, those systems shall comply with the provisions of this code. Any addition or alteration to such recreational dwelling or system therein shall comply with the provisions of the code at the time the permit for the addition or alteration is issued.

(4) BED AND BREAKFAST ESTABLISHMENTS. The third floor of bed and breakfast establishments, as defined under s. 50.50 (1), Stats., when used for other than storage, shall comply with the provisions of this code.

(5) CHANGE OF USE. A building previously used for another purpose, such as a barn or garage, shall comply with this code upon conversion to residential use.

History: Cr. Register, November, 1979, No. 287, eff. 6-I-80; cr. (3), Register, January, 1989, No. 397, eff. 2-1-89; am. (1), r. and rccr. (3), Register, March, 1992,

No. 435, eff. 4–1–92; r. and recr. (1), renum. (2) and (3) to be (3) and (4), cr. (2) and (5), Register, November, 1995, No. 479, eff. 12–1–95.

ILHR 20.05 Exemptions. (1) EXISTING DWELLINGS. The provisions of this code shall not apply to dwellings and dwelling units, the construction of which was commenced prior to the effective date of this code, or to additions or alterations to such dwellings.

Note: The provisions of chs. ILHR 20 to 25 may be adopted by a municipality to apply to any additions or alterations to existing dwellings.

(2) MULTIFAMILY DWELLINGS. The provisions of this code shall not apply to residences occupied by 3 or more families living independently or occupied by 2 such families and used also for business purposes.

(3) REPAIRS. The provisions of this code do not apply to repairs or maintenance to dwellings or dwelling units, or to the repair of electrical, plumbing, heating, ventilating, air conditioning and other systems installed therein.

(4) MOVING OF DWELLINGS. The status of a dwelling, new or existing, shall not be affected by the moving of the dwelling.

(5) ACCESSORY BUILDINGS. With the exception of s. ILHR 21.08 (5), the provisions of this code do not apply to detached garages or to any accessory buildings detached from the dwelling.

(6) FARM BUILDINGS. The provisions of this code do not apply to the buildings used exclusively for farm operations.

(7) INDIAN RESERVATIONS. The provisions of this code do not apply to dwellings located on Indian reservation land held in trust by the United States.

(8) RECREATIONAL VEHICLES AND MANUFACTURED (MOBILE) HOMES. The provisions of this code shall not apply to recreational vehicles or manufactured (mobile) homes, but shall apply to the onsite construction of additions to recreational vehicles and manufactured homes if the recreational vehicle or manufactured home was produced after June 1, 1980.

History: Cr. Register, November, 1979, No. 287, eff. 6–1–80; am. (5), r. (9), Register, January, 1989, No. 397, eff. 2–1–89; r. and recr. (8), Register, March, 1992, No. 435, eff. 4–1–92; am. (3), Register, November, 1995, No. 479, eff. 12–1–95.

Subchapter II—Jurisdiction

ILHR 20.06 Procedure for municipalities exercising jurisdiction. (1) MUNICIPAL JURISDICTION. Pursuant to ss. 101.65 and 101.76, Stats., cities, villages, towns and counties may exercise jurisdiction over the construction and inspection of new dwellings. Municipalities intending to exercise jurisdiction shall adopt the Uniform Dwelling Code in its entirety. No additional standards within the scope of this code shall be adopted by the municipality unless specific approval has been granted by the department pursuant to s. ILHR 20.20. No such municipality shall exercise jurisdiction except in accordance with the following procedure.

(a) Intent to exercise jurisdiction. Municipalities intending to exercise jurisdiction shall notify the department, in writing, at least 30 days prior to the date upon which the municipality intends to exercise jurisdiction under this code. The notification of intent shall include a statement by the municipality as to which of the following methods will be used for enforcement:

1. Individual municipal enforcement;

2. Joint municipal enforcement;

3. Contract with certified UDC inspector or inspectors or independent inspection agency;

4. Contract with another municipality;

5. Contract with the department.

(b) Submission of ordinances. Municipalities intending to exercise jurisdiction shall submit all ordinances adopting the uniform dwelling code to the department at the same time as the notice of intent. The department shall review and make a determination regarding municipal intent to exercise jurisdiction over new dwellings within 15 business days of receipt of the municipal

ordinances adopting the uniform dwelling code. A municipality may appeal a determination by the department that an ordinance does not comply with the code. Any appeal shall follow the procedure set out in s. ILHR 20.21 (2).

(c) *Passage of ordinances*. A certified copy of all adopted ordinances and subsequent amendments thereto shall be filed with the department within 30 days after adoption.

Note: A copy of a model ordinance for adoption is available from the department. (2) COUNTY JURISDICTION. A county ordinance shall apply in any city, village or town which has not enacted ordinances pursuant to this section. No county ordinance may apply until after 30 business days after the effective date of this code unless a municipality within the county informs the department of its intent to have this code administered and enforced by the county. This section shall not be construed to prevent or prohibit any municipality from enacting and administering this code at any time after the effective date of this code. The department shall

review and make a determination regarding county jurisdiction over new buildings within 15 business days of receipt of the county ordinances adopting the uniform dwelling code.

Note: Section 101.651 (3m) and (3s), Stats., allows counties to adopt just the provisions of this code relating to construction site crossion control.

Note: Section [01.651 (3m) and (3s), Stats., state that counties with a uniform dwelling code crosion control ordinance enforcement program shall enforce the erosion control ordinance provisions on a county-wide basis in all townships which have not adopted the Uniform Dwelling Code and may do so in cities and villages which have not adopted the Uniform Dwelling Code.

(3) DEPARTMENTAL JURISDICTION. Pursuant to ss. 101.63 and 101.73, Stats., the department will administer and enforce this code in any municipality which has not adopted; or is not covered by, an ordinance adopted in accordance with this section.

Note: Every 3 years the department will perform performance audits of the erosion control programs of the municipalities administering the program and issue a written determination on whether the municipality complies with the erosion control ordinances and the erosion control standards.

History: Cr. Register, November, 1979, No. 287, eff. 6–1–80; am. (1) (b) and (2), Register, February, 1985, No. 350, eff. 3–1–85; am. (1) (a) 3., Register, October, 1996, No. 490, eff. 11–1–96.

Subchapter III—Definitions

ILHR 20.07 Definitions. In chs. ILHR 20 to 25;

(1) "Accessory building" means a detached building, not used as a dwelling unit but is incidental to that of the main building and which is located on the same lot. Accessory building does not mean farm building.

(2) "Addition" means new construction performed on a dwelling which increases the outside dimensions of the dwelling.

(3) "Allowable stress" means the specified maximum permissible stress of a material expressed in load per unit area.

(4) "Alteration" means an enhancement, upgrading or substantial change or modification other than an addition or repair to a dwelling or to electrical, plumbing, heating, ventilating, air conditioning and other systems within a dwelling.

(4m) "Annual fuel utilization efficiency" or "AFUE" means the efficiency rating of the heating plant model determined on average usage conditions as set out in the U.S. department of energy test procedures.

Note: The higher the AFUB rating, the higher the heating plant efficiency will be.

(5) "Approved" means an approval by the department or its authorized representative. (Approval is not to be construed as an assumption of any legal responsibility for the design or construction of the dwelling or building component.)

(6) "Attic" means a space under the roof and above the ceiling of the topmost part of a dwelling.

(7) A "balcony" is a landing or porch projecting from the wall of a building.

(7m) "Base flood elevation" means the depth or peak elevation of flooding, including wave height, which has a one percent or greater chance of occurring in any given year. (8) "Basement" means that portion of a dwelling below the first floor or groundfloor with its entire floor below grade.

(8m) "Best management practices" is defined in s. 101.653, Stats., and means practices, techniques or measures that the department determines to be effective means of preventing or reducing pollutants of surface water generated from construction sites.

(9) "Building component" means any subsystem, subassembly or other system designed for use in or as part of a structure, which may include structural, electrical, mechanical, plumbing and fire protection systems and other systems affecting health and safety.

(10) "Building system" means plans, specifications and documentation for a system of manufactured building or for a type or a system of building components, which may include structural, electrical, mechanical, plumbing and variations which are submitted as part of the building system.

(11) "Ceiling height" means the clear vertical distance from the finished floor to the finished ceiling.

(12) "Certified inspector" means a person certified by the department to engage in the administration and enforcement of this code.

(13) A "chimney" is one or more vertical, or nearly so, passageways or flues for the purpose of conveying flue gases to the atmosphere.

(14) "Chimney connector". Same as smoke pipe.

(15) "Closed construction" means any building, building component, assembly or system manufactured in such a manner that it cannot be inspected before installation at the building site without disassembly, damage or destruction.

(15m) "Coastal floodplain" means an area along the coast of Lake Michigan or Lake Superior below base flood elevation that is subject to wave runup or wave heights of 3 feet or more.

(16) "Code" means chs. ILHR 20 to 25, the Wisconsin uniform dwelling code.

(17) "Coefficient of performance (COP)" means the ratio of the rate of net heat removal or net heat output to the rate of total energy input, expressed in consistent units and under designated rating conditions.

(19) "Compliance assurance program" means the detailed system documentation and methods of assuring that manufactured dwellings and dwelling components are manufactured, stored, transported, assembled, handled and installed in accordance with this code.

(20) "Cooling load" is the rate at which heat must be removed from the space to maintain a selected indoor air temperature during periods of design outdoor weather conditions.

(21) "Dead load" means the vertical load due to all permanent structural and nonstructural components of the building such as joists, rafters, sheathing, finishes and construction assemblies such as walls, partitions, floors, ceilings and roofs, and systems.

(21m) "Deck" means an unenclosed exterior structure, attached or adjacent to the exterior wall of a building, which has a floor, but no roof.

(22) "Degree day" means a unit of temperature and time which may be used to determine heating requirements for buildings. A degree day accrues for every degree the mean outdoor temperature for a 24 hour period falls below 65° F.

Note: For example, if, on December 15, the low temperature was $+30^{\circ}$ F and the high temperature was $+50^{\circ}$ F, the mean temperature would equal $(30^{\circ} + 50^{\circ}) \div 2 = 40^{\circ}$; therefore, $65^{\circ} - 40^{\circ} = 25$ degree days.

(23) "Department" means the department of commerce.

(24) "Detached building" means any building which is not physically connected to the dwelling.

(25) "Dwelling" means any building, the initial construction of which is commenced on or after the effective date of this code, which contains one or 2 dwelling units.

(26) "Dwelling contractor" means any person, firm or corporation engaged in the business of performing erosion control or construction work such as framing, roofing, siding, insulating, masonry or window replacement work covered under this code and who takes out a building permit. "Dwelling contractor" does not include the owner of an existing dwelling, an owner who will reside in a new dwelling or a person, firm or corporation engaging exclusively in electrical, plumbing, or heating, ventilating and air conditioning work.

(27) "Dwelling unit" means a structure, or that part of a structure, which is used or intended to be used as a home, residence or sleeping place by one person or by 2 or more persons maintaining a common household, to the exclusion of all others.

(27m) "Electrically heated" means provided with permanently installed electrical space heating equipment which has an input capacity of 3 kilowatts or more to meet all or part of the space heating requirements.

(28) "Energy efficiency ratio" or "EER" is the ratio of net cooling capacity in Btu per hour to total rate of electric input, in watts, under designated operating conditions.

(28r) "Equivalent leakage area" or "ELA" means the estimated area of a hole in the thermal envelope of a building which would exist if all the leakage openings were gathered into one location.

(28t) "Erosion" means the detachment and movement of soil, sediment or rock fragments by water, wind, ice or gravity.

(28v) "Erosion control procedure" means a practice or a combination of practices implemented to prevent or reduce erosion and the resulting deposition of soil, sediment or rock fragments into waters of the state, public sewers or off the owner's land. These procedures include, but are not limited to, silt or filter fences, straw or hay bales, tarps or riprap, berms, sediment basins or vegetative strips.

Note: See Appendix for examples and illustrations.

(29) "Exit" means a continuous and unobstructed means of egress to a street, alley or open court and includes intervening doors, doorways, corridors, halls, balconies, ramps, fire escapes, stairways and windows.

(29m) "Existing dwelling" means a dwelling erected prior to the effective date of this code, one for which a valid building permit exists, or one for which lawful construction has commenced prior to the effective date of this code.

Note: See s. ILHR 20.03 for the effective date of chs. ILHR 20-25.

(30) "Farm operation" is the planting and cultivating of the soil and growing of farm products substantially all of which have been planted or produced on the farm premises.

Note: According to s. 102.04 (3), Stats., the farm operation includes the management, conserving, improving and maintaining of the premises, tools, equipment improvements and the exchange of labor or services with other farmers; the processing, drying, packaging, freezing, grading, storing, delivery to storage, earrying to market or to a carrier for transportation to market and distributing directly to the consumer; the clearing of such premises and the salvaging of timber and the management and use of wood lots thereon but does not include logging, lumbering and wood–cutting operations unless the operations are conducted as an accessory to other farm operations.

(31) "Farm premises" is defined to be the area which is planted and cultivated. The farm premises does not include greenhouses, structures or other areas unless used principally for the production of food or farm products.

(32) "Farm products" are defined as agricultural, horticultural and arboricultural crops. Animals considered within the definition of agricultural include livestock, bees, poultry, fur-bearing animals, and wildlife or aquatic life.

(33) "Farming" means the operation of a farm premises owned or rented by the operator.

(34) "Firebox" means that part of the fireplace used as the combustion chamber.

(34e) "First floor" means the first floor level above any groundfloor or basement or, in the absence of a groundfloor or basement, means the lowest floor level in the dwelling.

(34g) "Floodfringe area" means that portion of the floodplain outside of the floodway that is at or below base flood elevation. The term "floodfringe" is intended to designate an area of standing, rather than flowing, water.

(34h) "Floodplain" means land which is subject to flooding which is at or below base flood elevation. The floodplain includes the floodway and floodfringe areas.

(34i) "Floodway" means the channel of a river or stream and those portions of the floodplain adjoining the channel required to carry the flood discharge. The term "floodway" is intended to designate an area of flowing, rather than standing, water.

(34m) "Floor area" means the area of a room that has a ceiling height of at least 7 feet. Rooms with ceilings less than 7 feet in height for more than 50% of the room are not considered to be floor areas.

(35) "Garage" means an unenclosed or enclosed portion of a dwelling used for storing motorized vehicles.

(36) "Gas appliance" means any furnace or heater, air conditioner, refrigerator, stove having an electrical supply cord, dishwasher, dryer, swimming pool heater, or other similar appliance or device used in a dwelling or dwelling unit which uses a gaseous fuel for operation.

(36m) "Groundfloor" means that level of a dwelling, below the first floor, located on a site with a sloping or multilevel grade and which has a portion of its floor line at grade.

(37) "Habitable room" means any room used for sleeping, living or dining purposes, excluding such enclosed places as kitchens, closets, pantries, bath or toilet rooms, hallways, laundries, storage spaces, utility rooms, and similar spaces.

(38) "Hearth" means the floor area within the fire chamber of a fireplace.

(38m) "Hearth extension" means the surfacing applied to the floor area extending in front of and at the sides of the fireplace opening.

(39) "Heated space" is any space provided with a supply of heat to maintain the temperature of the space to at least 50° F. Heat supplied by convection from the energy-consuming systems may satisfy this requirement in basements if the energy-consuming systems are not insulated.

(40) "Heating load" is the estimated heat loss of each room or space to be heated, based on maintaining a selected indoor air temperature during periods of design outdoor weather conditions. The total heat load includes: the transmission losses of heat transmitted through the wall, floor, ceiling, glass or other surfaces; and either the infiltration losses or heat required to warm outdoor air used for ventilation.

Note: Infiltration losses include heat required to warm outside air which leaks through cracks and crevices, around doors and windows or through open doors and windows.

(40m) "Hollow unit" means a masonry unit which has a net cross-sectional area parallel to the bearing face which is less than 75% of the gross cross-sectional area.

(41) "Independent inspection agency" means any person, firm, association, partnership or corporation certified by the department to perform certified inspections under this code.

(41m) "Infiltration barrier" means a material which restricts the movement of air and liquid water, but is permeable to water vapor.

(42) "Initial construction" means the date of issuance of the Wisconsin uniform building permit.

(43) "Insignia." See "Wisconsin insignia."

(44) "Installation" means the assembly of a manufactured building on site and the process of affixing a manufactured building to land, a foundation, footing or an existing building.

(45) "Intermittent ignition device" means an ignition device which is actuated only when a gas appliance is in operation.

(46) "Kitchen" means an area used, or designed to be used, for the preparation of food.

(47) "Landing" means the level portion of a stairs located within a flight of stairs or located at the base and foot of a stairs.

(48) "Listed and listing" means equipment or building components which are tested by an independent testing agency and accepted by the department.

(49) "Live load" means the weight superimposed on the floors, roof and structural and nonstructural components of the dwelling through use and by snow, ice or rain.

(50) "Loft" means an upper room or floor which has at least 50% of the common wall open to the floor below. The opening may be infringed upon by an open guardrail constructed in compliance with s. ILHR 21.04 (2), but not by a window or half-wall guardrail. All habitable rooms of lofts are open to the floor below.

(51) "Manufacture" means the process of making, fabricating, constructing, forming or assembling a product from raw, unfinished, semifinished or finished materials.

(52) (a) "Manufactured dwelling" means any structure or component thereof which is intended for use as a dwelling and:

1. Is of closed construction and fabricated or assembled on site or off site in manufacturing facilities for installation, connection or assembly and installation at the building site; or

2. Is a building of open construction which is made or assembled in manufacturing facilities away from the building site for installation, connection, or assembly and installation on the building site and for which certification is sought by the manufacturer.

(b) The term manufactured dwelling does not include a building of open construction which is not subject to par. (a) 2. A single or double width manufactured (mobile) home is not considered a manufactured dwelling and is not subject to this code.

(54) A "multi-wythe wall" is a masonry wall composed of 2 or more wythes of masonry units tied or bonded together.

(55) "Municipality" means any city, village, town or county in this state.

(56) "Open construction" means any building, building component, assembly or system manufactured in such a manner that it can be readily inspected at the building site without disassembly, damage or destruction.

(56m) "Overall thermal transmittance" or "Uo" means the area-weighted average of the thermal transmittance values of all materials, including framing and fenestration, which make up a building section.

Note: Additional explanatory material is contained in the appendix.

(57) "Owner" means any person having a legal or equitable interest in the dwelling.

(58) "Perm" means a unit of permeance which is measured in grains per (hour) (square foot) (inch of mercury vapor pressure difference).

Note: The lower the perm rating of a material is, the more difficult it is for water vapor to pass through it.

(59) "Pilaster" is a projection of masonry or a filled cell area of masonry for the purpose of bearing concentrated loads or to stiffen the wall against lateral forces.

(59m) "Porch" means an unenclosed exterior structure at or near grade attached or adjacent to the exterior wall of any building, and having a roof and floor.

(60) "Recreational dwelling unit" means a permanent structure occupied occasionally or seasonally solely for recreational purposes and not used as a principal residence. (61) "Repair" means the act or process of restoring to original soundness, including, but not limited to, redecorating, refinishing, nonstructural repairs, maintenance repairs or replacement of existing fixtures, systems or equipment.

5

(62) "Shingle" means a unit of roof covering material that has been manufactured to specific dimensions and is applied in overlapping fashion. 'Shingle' includes all of the following:

(a) "Fiberglass asphalt shingle" means a type of shingle with an internal mat composed of nonwoven, resin-bonded glass fibers, that is impregnated and coated with asphalt.

(b) "Laminated shingle" means a shingle with a second layer of asphalt and mat laminated to the first layer, usually in a design pattern to simulate the dimensional appearance of natural slate or wood shakes.

(c) "Organic asphalt shingle" means a shingle with an internal mat composed of organic fibers, such as cellulose, that is saturated and coated with asphalt.

(d) "Strip shingle" means a rectangular shingle that relies either on a sealant or on a combination of weight and stiffness to resist wind uplift, rather than using interlocking tabs.

(63) A "single-wythe wall" is a masonry wall consisting of one unit of thickness.

(63m) "Site" means all contiguous property under single ownership where land-disturbing activity has been proposed for the purpose of constructing a dwelling.

(64) A "smoke chamber" is that part of a fireplace which acts as a funnel to compress the smoke and gases from the fire so that they will enter the chimney above.

(65) A "smoke pipe" is a connector between the solid or liquid fuel-burning appliance and the chimney.

(65m) "Solid unit" means a masonry unit which has a net cross-sectional area parallel to the bearing face which is 75% or more of the gross cross-sectional area.

(65r) "Stabilized" means actions taken at a site to minimize erosion by mulching and seeding, sodding, landscaping, placing concrete or gravel, or other techniques to prevent soil loss.

(66) A "stairway" is one or more flights of steps, and the necessary platforms or landings connecting them, to form a continuous passage from one elevation to another.

(67) "Step(s)" is a unit(s) consisting of one riser and one tread, alone or in series.

(68) A "story" is that portion of a building located above the basement, between the floor and the ceiling.

(69) A "stove" is a nonportable solid-fuel-burning, vented, nonducted heat-producing appliance located in the space that it is intended to heat. This definition does not include cooking appliances.

(70) Stovepipe. Same as smoke pipe.

(71) "Strain" means a change in the physical shape of a material caused by stress.

(72) "Stress" means internal resistance to an external force expressed in load per unit area; stresses acting perpendicular (compression or tension) to the surface, shear stresses acting in the plane of the surface, or bending stresses which cause curving.

(73) "Structural analysis" is a branch of the physical sciences which uses the principles of mechanics in analyzing the impact of loads and forces and their effect on the physical properties of materials in the form of internal stress and strain.

(73m) "Thermal envelope" means the collective assemblies of the building which enclose the heated space and define the surface areas through which the design heating loss is calculated. The components which make up the thermal envelope form a continuous, unbroken surface.

(73r) "Thermal resistance" or "R" means a measure of the ability to retard the flow of heat. The R-value is the reciprocal of the thermal transmittance or U (R = 1/U).

Note: The higher the R-value of a material, the more difficult it is for heat to be transmitted through the material.

(74) "Thermal transmittance" or "U" means the time rate of heat flow through a body or assembly which is located in between 2 different environments, expressed in Btu per (hour) (square foot) (°F). The U-value applies to combinations of different materials used in series along the heat flow path and also to single materials that comprise a building section, and includes cavity air spaces and air films on both sides.

Note: The lower the U-value of a material, the more difficult it is for heat to be transmitted through the material.

Note: The thermal transmittance is also referred to as the coefficient of heat transfer or the coefficient of heat transmission.

(75) The "throat" of a fireplace is the slot-like opening above the firebox through which flames, smoke and other products of combustion pass into the smoke chamber.

(76) "Vent" means a vertical flue or passageway to vent fuelburning appliances.

(77) A "vent connector" is a connector between a fuel-burning appliance and the chimney or vent.

(77m) "Waters of the state" includes those portions of Lake Michigan and Lake Superior within the boundaries of Wisconsin, and all lakes, bays, rivers, streams, springs, ponds, wells, impounding reservoirs, marshes, watercourses, drainage systems and other surface waters or groundwaters, natural or artificial, public or private, within the state or its jurisdiction.

(78) "Window" means a glazed opening in an exterior wall, including glazed portions of doors, within a conditioned space.

(78m) "Wisconsin Administrative Permit" means a permit issued by a municipality that does not conduct inspections or plan reviews under this code.

(79) "Wisconsin insignia" means a device or seal approved by the department to certify compliance with this code.

the department to certify compliance with this code. History: Cr. Register, November, 1979, No. 287, eff. 6–1-80; cr. (34m) and (36m), Register, February, 1985, No. 350, eff. 3–1-85; an. (8), (22), (36m), (50), (58), (62) and (74), r. (18) and (53), renum. (26) to (29m) and am., cr. (34r), (38m), (40m), (59m) and (65m), r. and recr. (38), Register, January, 1989, No. 397, eff. 2–1–89; am. (16), (34m), (40), (52) (a) (intro.) and (b), cr. (21m), Register, March, 1992, No. 435, eff. 4–1–92; am. (16), cr. (intro), (8m), (28), (28v), (63m), (57) and (77m), Register, September, 1992, No. 441, eff. 12–1–92; am. (4) and (65r), renum. (62) to be (73r), cr. (26), (62), (78m), Register, November, 1995, No. 479, eff. 12–1–95; energ. cr. (7m), (34L) and (400, eff. 5–8–96; correction in (23) made under s. 13.93 (2m) (b) 7., Stats., Register, October, 1996, No. 490; emerg. cr. (7m), (34L) and (400), eff. 5–8–96; cr. (7m), (15m), (34g), (34h) and (34i), renum. (34k) to be (34e), Register, February, 1997, No. 494, eff. 3–1–97.

Subchapter IV—Approval and Inspection of One- and 2-Family Dwellings

ILHR 20.08 Wisconsin uniform building permit. A Wisconsin uniform building permit shall be obtained from the department or the municipality administering and enforcing this code before any on-site construction, including excavation for a structure, within the scope of this code is commenced, except where a permit to start construction has been issued in accordance with s. ILHR 20.09 (5) (b) 2. A Wisconsin uniform building permit shall not be required for repairs.

Note: Section ILHR 20.09 (5) (b) 2. permits the issuance of a footing and foundation permit prior to the issuance of the Wisconsin uniform building permit.

History: Cr. Register, November, 1979, No. 287, eff. 6-1-80; am. Register, Scptember, 1992, No. 441, eff. 12-1-92.

ILHR 20.09 Procedures for obtaining uniform building permit. (1) APPLICATION FOR A WISCONSIN UNIFORM BUILD-ING PERMIT. Application for a Wisconsin uniform building permit shall be on the forms obtained from the department or the municipality administering and enforcing this code. No application shall be accepted that does not contain all the information requested on the form.

Note: See appendix for a copy of the Wisconsin uniform building permit and application.

Note: Any municipality exercising jurisdiction may require reasonable supplementary information not contained on the Wisconsin building permit application.

(2) FILING OF PERMITS. (a) Wisconsin uniform building permit application. The Wisconsin uniform building permit application

Register, February, 1997, No. 494

shall be filed with the municipality administering and enforcing this code or its authorized representative. The municipality shall forward a copy of all applications to the department within 30 business days after permit issuance. Pursuant to s. 101.65 (1m), Stats., a municipality may not issue a building permit for construction work covered under chs. ILHR 21 and 22 to a dwelling contractor unless the contractor has a dwelling contractor financial responsibility certification issued by the department.

Note: See s. ILHR 20.07 (26) for the definition of "dwelling contractor".

(b) Wisconsin administrative permit. The Wisconsin administrative permit shall be filed with the municipality and the department when the dwelling is located in a municipality that does not enforce the code.

(3) FEES. (a) *Municipal fees*. Fees shall be submitted to the municipality at the time the Wisconsin uniform building permit application for new construction is filed. The municipality shall, by ordinance, determine fees to cover expenses of plan examination, inspection and the issuance of the Wisconsin uniform building permit. The municipality shall collect and send to the department the fee for Wisconsin uniform building permits issued for new dwellings in accordance with s. Comm 2.34.

(b) Department fees. Where the department administers and enforces the code, the fees for plan examination, inspection, and the issuance of the Wisconsin uniform building permit, in accordance with s. Comm 2.34, shall be submitted to the department, or its authorized representative, at the time the Wisconsin uniform building permit application is filed.

(c) Soil erosion fees. Counties enforcing construction site erosion control provisions of the code shall collect and submit the fee for Wisconsin uniform building permits to the department.

(4) SUBMISSION OF PLANS. At least 2 sets of plans for all oneand 2-family dwellings shall be submitted to the department, or the municipality administering and enforcing this code, for examination and approval at the time the Wisconsin uniform building permit application is filed. A municipality exercising jurisdiction may require a third set of plans at its option.

(a) Required building plans. The required building plans shall be legible and drawn to scale or dimensioned and shall include the following:

1. Plot plan. a. The plot plan shall show the location of the dwelling and any other buildings, wells, surface waters and disposal systems on the site with respect to property lines. The location of the non-tracking access roadway, as required under s. ILHR 21.125 (1) (c), shall be shown. For sites greater than 5 acres, the plot plan shall indicate the area of land-disturbing activity within the site.

b. The plot plan shall show the direction of all slopes on the site. Sectors within the area of land disturbing activity shall be designated and labeled on the plot plan in the appropriate slope category: less than 12% slope; 12% to 20% slope; and greater than 20% slope. The plot plan shall indicate initial erosion control measures as specified in s. ILHR 21.125 based on slopes existing immediately prior to building construction.

Note: A 12% slope equals 6.8 degrees from the horizontal and has a rise to run ratio of 3 to 25.

Note: A 20% slope equals 11.3 degrees from the horizontal and has a rise to run ratio of 1 to 5.

Note: See Appendix for examples of plot plans indicating erosion control measures.

2. Floor plans. Floor plans shall be provided for each floor. The size and location of all rooms, doors, windows, structural features, exit passageways and stairs shall be indicated. The use of each room shall be indicated. The location of plumbing fixtures, chimneys, and heating and cooling appliances, and, when requested, a heating distribution layout shall be included.

3. Elevations. The elevations shall contain information on the exterior appearance of the building, indicate the location, size and configuration of doors, windows, roof, chimneys, exterior grade,

footings and foundation walls, and include the type of exterior materials.

(b) Data required. All required plans submitted for approval shall be accompanied by sufficient data, calculations and information to determine if the dwelling will meet the requirements of this code. The data and information for determining compliance with the energy conservation standards shall be submitted on forms provided by the department or other approved forms. Except as required under s. JLHR 21.33, a municipality exercising jurisdiction may not require plans or calculations to be stamped by an architect or engineer.

(c) *Master plans.* Where a dwelling is intended to be identically and repetitively constructed at different locations, a master plan may be submitted for approval. The plans shall include floor plans, elevations and data as required in par. (a) 2. and 3. If the plans conform to the provisions of the code, an approval and a master plan number shall be issued. The number issued may be used in lieu of submitting building plans for each location. A plot plan shall be submitted for each location at the time of application for the Wisconsin uniform building permit.

(5) APPROVAL OF PLANS AND ISSUANCE OF PERMITS. (a) *Plan* approval. If the department, or the municipality administering and enforcing the code, determines that the plans, including the plans indicating the erosion control procedures as specified in sub. (4), submitted for a one- or 2-family dwelling substantially conform to the provisions of this code and other legal requirements, an approval shall be issued. The plans shall be stamped "conditionally approved" by a certified inspector. One copy shall be returned to the applicant; one copy shall be retained by the department or the municipality administering and enforcing the code. The conditions of approval shall be indicated by a letter or on the permit. All conditions of the approval shall be met during construction.

(b) *Issuance of permits.* 1. 'Uniform building permit'. a. The Wisconsin uniform building permit shall be issued if the requirements for filing and fees are satisfied and the plans have been conditionally approved.

b. Pursuant to s. 101.65 (1m), Stats., a Wisconsin uniform building permit may not be issued to a person unless the person holds a credential issued by the department as a dwelling contractor financial responsibility registration under s. Comm 5.31, except as provided under s. 101.654 (1) (b), Stats.

Note: Section 101.654 (1) (b), Stats., exempts an owner of a dwelling who resides or will reside in the dwelling and who applies for a building permit to perform work on the dwelling from obtaining a dwelling contractor financial responsibility registration.

2. Permit to start construction of footings and foundation. Construction may begin on footings and foundations prior to the issuance of the Wisconsin uniform building permit where a permit to start construction is obtained. Upon submittal of the application for a permit to start construction, a plot plan as specified in sub. (4) (a) 1., complete footing and foundation information including exterior grading, and a fee, the department or the municipality enforcing this code may issue a permit to start construction of the footings and foundation. The issuance of a permit to start construction shall not influence the approval or denial of the Wisconsin uniform building permit application.

Note: Section 66.036, Stats., prohibits issuance of building permits by counties, cities, towns or villages for structures requiring connection to a private domestic sewerage treatment and disposal system unless such system satisfies all applicable requirements and all necessary permits for such system have been obtained.

(c) Posting of permit. The Wisconsin uniform building permit shall be posted in a conspicuous place at the dwelling site.

Note: Section 101.63 (7), Stats., requires the name and license number of the master plumber to be identified on the Wisconsin uniform building permit card.

(6) DISAPPROVAL OF PLANS AND DENIAL OF PERMITS. If the department, or the municipality administering and enforcing the code, determines that the Wisconsin uniform building permit application or the plans, including the plans indicating the erosion control procedures as specified in sub. (4), do not substantially

conform to the provisions of this code or other legal requirements are not met, approval shall be denied.

(a) Denial of application. A copy of the "denied" application, accompanied by a written statement specifying the reasons for denial, shall be sent to the applicant and to the owner as specified on the Wisconsin uniform building permit application.

(b) Stamping of plans. Plans which do not substantially conform to the provisions of the code shall be stamped "not approved." One copy shall be returned to the person applying for the Wisconsin uniform building permit; one copy shall be retained by the department or the municipality administering and enforcing the code.

(c) Appeals. The applicant may appeal a denial of the application in accordance with the procedure outlined in s. ILHR 20.21.

(7) ACTION TO APPROVE OR DENY. Action to approve or deny a uniform building permit application shall be completed within 10 business days of receipt of all forms, fees, plans and documents required to process the application, and completion of other local prerequisite permitting requirements.

History: Cr. Register, November, 1979, No. 287, eff. 6–1–80; r. and recr. (7), Register, February, 1985, No. 350, eff. 3–1–85; am. (4) (b) and (5) (b) 1., Register, January, 1989, No. 397, eff. 2–1–89; am. (3) (a) and (4) (a) 2., Register, March, 1992, No. 435, eff. 4–1–92; am. (4) (a) 1., (5) (a), (b) 2. and (6) (intro.), Register, September, 1992, No. 441, eff. 12–1–92; renum. (2) to be (2) (a) and am., am. (3) and (7), cr. (2) (b), (3) (c), Register, November, 1995, No. 479, eff. 12–1–95; r. and recr. (3) (b) 1., Register, October, 1996, No. 490, eff. 11–1–96; am. (4) (a) 1. a. and (b), r. and recr. (4) (a) 1. b., r. (4) (a) 1. c. and d., Register, February, 1997, No. 494, eff. 3–1–97.

ILHR 20.10 Inspections. All inspections, for the purpose of administering and enforcing this code, shall be performed by a certified inspector.

(1) REQUIRED INSPECTIONS. Inspections shall be conducted by the department or the municipality administering and enforcing this code to ascertain whether or not the construction or installations conform to the conditionally approved plans, the Wisconsin uniform building permit application and the provisions of this code and shall notify the permit holder and the owner of any violations to be corrected.

(a) Inspection notice. The applicant or an authorized representative shall, in writing or orally, request inspections of the department or the municipality administering and enforcing this code. The department, or the municipality administering and enforcing this code, shall perform the requested inspection within 2 business days after notification, except the final inspection. Construction shall not proceed beyond the point of inspection until the inspection has been completed. Construction may proceed if the inspection has not taken place within 2 business days of the notification, except if otherwise agreed between the applicant and the department or the municipality administering and enforcing the code.

(b) Inspection types. The following sequence of inspections shall be performed for the purpose of determining if the work complies with this code:

1. 'Footing and foundation inspection'. The excavation shall be inspected after the placement of forms, shoring and reinforcement, where required, and prior to the placement of footing materials. Where below-grade drain tiles, waterproofing or exterior insulation is required, the foundation shall be inspected prior to backfilling.

2. 'Rough inspection'. A rough inspection shall be performed for each inspection category listed in subd. 2. a. through e. after the rough work is constructed but before it is concealed. All categories of work for rough inspections may be completed before the notice for inspection is provided. The applicant may request one rough inspection or individual rough inspections. A separate fee may be charged for each individual inspection.

- a. General construction, including framing.
- b. Rough electrical.
- c. Rough plumbing.
- d. Rough heating, ventilating and air conditioning.

e. Basement drain tiles.

3. 'Insulation inspection'. An inspection shall be made of the insulation and vapor retarder after they are installed but before they are concealed.

4. 'Final inspection'. The dwelling may not be occupied until a final inspection has been made which finds that no violations of this code exist that could reasonably be expected to affect the health and safety of the occupant.

a. The basement portion of the dwelling may be occupied prior to completion of the dwelling, but only if the basement portion to be occupied would otherwise comply with the provisions of this code, particularly those relating to construction of underground dwellings.

5. 'Erosion control inspection'. Erosion control inspections shall be performed concurrently with all other required construction inspections. Additional inspections for erosion control may be performed by the delegated authority.

(c) Notice of compliance and noncompliance. 1. 'General'. Notice of compliance or noncompliance with this code shall be written on the building permit and posted at the job site. Upon finding of noncompliance, the department or municipality enforcing this code shall also notify the applicant of record and the owner, in writing, of the violations to be corrected. Except as specified in subd. 2., the department or municipality shall order all cited violations corrected within 30 days after written notification, unless an extension of time is granted under s. ILHR 20.21.

2. 'Soil erosion control requirements'. a. The department or municipality shall order all cited violations of erosion control requirements under s. ILHR 21.125 (1) (a) to (c) and (e) to (f) corrected within 72 hours after notification and may issue a special order directing an immediate cessation of work for failure to comply with the corrective order. Work may continue when the conditions of the cessation order have been met.

Note: The sediment cleanup requirements of s. ILHR 21.125 (1) (d) have different time limits and are unaffected by the 72-hour notice provision.

b. If written notification is delivered in person, the 72-hour compliance period shall begin at the time of delivery. If faxed or sent through the mail, the compliance period shall begin at the time the notification was received by the applicant of record.

c. If verbal notification, in person or by telephone, is given prior to delivery of written notification, the 72-hour notification shall begin at the time of verbal notification. The written notification shall then be delivered, in person or via mail or fax, to the applicant of record at their business address and shall include the date and time of verbal notification.

(2) VOLUNTARY INSPECTION. The department or its authorized representative may, at the request of the owner or the lawful occupant, enter and inspect dwellings, subject to the provisions of this code, to ascertain compliance with this code.

History: Cr. Register, November, 1979, No. 287, eff. 6-1--80; am. (1) (a), Register, February, 1985, No. 350, eff. 3-1-85; cr. (1) (b) 2. f., Register, January, 1989, No. 397, eff. 2-1-89; correction (1) (b) 2. intro. made under s. 13.93 (2m) (b) 4. Stats, Register, January, 1989, No. 397; r. (1) (b) 2. e., renum. (1) (b) 2. f. and 3. and (3) to be (1) (b) 2. e. and 4. and (2), cr. (1) (b) 3., Register, March, 1992, No. 455, eff. 4-1-92; am. (1) (c), Register, September, 1992, No. 441, eff. 12-1-92; cr. (1) (b) 5., Register, November, 1995, No. 479, eff. 12-1-95; am. (intro.), Register, October, 1996, No. 490, eff. 11-1-96; r. and recr. (1) (c), Register, February, 1997, No. 494, eff. 3-1-97.

ILHR 20.11 Suspension or revocation of Wisconsin uniform building permit. The department, or the municipality administering and enforcing this code, may suspend or revoke any Wisconsin uniform building permit where it appears that the permit or approval was obtained through fraud or deceit, where the applicant has willfully refused to correct a violation order or where the inspector is denied access to the premises. No construction shall take place on the dwelling after suspension or revocation of the permit. (1) Any person aggrieved by a determination made by the municipality exercising jurisdiction may appeal the decision in accordance with s. ILHR 20.21.

(2) Any person aggrieved by a determination made by the department may appeal the decision in accordance with s. ILHR 20.21.

History: Cr. Register, November, 1979, No. 287, eff. 6-1-80.

Subchapter V—Approval and Inspection of Manufactured Dwellings and Their Components

ILHR 20.12 Scope. This part shall govern the design, manufacture, installation and inspection of manufactured dwellings, manufactured building systems and the components of the building systems displaying the Wisconsin insignia.

History: Cr. Register, November, 1979, No. 287, eff. 6-1-80.

ILHR 20.13 Manufacture, sale and installation of dwellings. (1) MANUFACTURE AND SALE. No manufactured dwelling, manufactured building system or component of the building system subject to this part shall be manufactured for use, sold for initial use or installed in this state unless it is approved by the department and it bears the Wisconsin insignia issued or a state seal or an insignia reciprocally recognized by the department.

(2) INSTALLATION. A Wisconsin uniform building permit shall be obtained in accordance with the procedures outlined in s. ILHR 20.09(1), (2), (3) and (4)(a) 1. before any on-site construction falling within the scope of this code is commenced for a manufactured dwelling. The permit shall be issued in accordance with s. ILHR 20.09(5) (b) 1.

History: Cr. Register, November, 1979, No. 287, eff. 6-1-80.

ILHR 20.14 Approval procedures. (1) APPLICATION FOR APPROVAL. An application for the approval of any manufactured dwelling, building system or component shall be submitted to the department, in the form required by the department, along with the appropriate fees in accordance with s. ILHR 2.34. The department shall review and make a determination on an application for approval of a manufactured dwelling within 3 months of receipt of all forms, fees, plans and documents required to complete the review.

(2) APPROVAL OF BUILDING SYSTEMS AND COMPONENTS. (a) *Approval of building systems.* 1. 'Plans and specifications'. All plans and specifications shall be submitted to the department according to subd. 1. a. or b.:

a. Three complete sets of building, structural, mechanical and electrical plans, (including elevations, sections and details), specifications and calculations shall be submitted to the department on behalf of the manufacturer for examination and approval.

b. At least one complete set of building, structural, mechanical and electrical plans, (including elevations, sections and details), specifications and calculations shall be submitted to the department on behalf of a manufacturer. All plans and specifications submitted to the department shall be stamped "conditionally approved" by a UDC certified inspector or inspectors.

2. 'Compliance assurance program'. Three sets of the compliance assurance program shall be submitted for examination and approval. The compliance assurance program submitted to the department on behalf of the manufacturer shall meet the standards of the Model Documents for the Evaluation, Approval, and Inspection of Manufactured Buildings as adopted under s. ILHR 20.24 (8) or equivalent as determined by the department.

(b) Approval of building components. 1. Plans and specifications. All plans and specifications shall be submitted to the department according to subd. 1. a. or b.:

a. At least 3 complete sets of plans and specifications for manufactured dwelling building components shall be submitted to the department on behalf of the manufacturer for examination and approval. b. At least one complete set of plans and specifications for manufactured dwelling building components shall be submitted to the department on behalf of the manufacturer. All plans and specifications submitted to the department shall be stamped "conditionally approved" by a UDC certified inspector or inspectors.

2. 'Compliance assurance program'. Three sets of the compliance assurance program shall be submitted to the department on behalf of the manufacturer for examination and approval of components. The compliance assurance program shall meet the requirements established by the department or, where applicable, be in the form of the NBS "Model Rules and Regulations" [ILHR 20.24 (3)].

(3) NOTIFICATION OF APPROVAL OR DENIAL OF PLANS, SPECIFICA-TIONS AND COMPLIANCE ASSURANCE PROGRAM. (a) Conditional approval. If the department determines that the plans, specifications, compliance assurance program and application for approval submitted for such building system or component substantially conform to the provisions of this code, a conditional approval shall be issued. A conditional approval issued by the department shall not constitute an assumption of any liability for the design or construction of the manufactured building.

1. Written notice. The conditional approval shall be in writing and sent to the manufacturer and the person submitting the application for approval. Any noncompliance specified in the conditional approval shall be corrected before the manufacture, sale or installation of the dwelling, building system or component.

2. Stamping of plans, specifications and compliance assurance program. Approved plans, specifications and compliance assurance programs shall be stamped "conditionally approved." At least 2 copies shall be returned to the person designated on the application for approval; one copy shall be retained by the department.

(b) Denial. If the department determines that the plans, specifications, compliance assurance program or the application for approval do not substantially conform to the provisions of this code, the application for approval shall be denied.

1. Written notice. The denial shall be in writing and sent to the manufacturer and the person submitting the application for approval. The notice shall state the reasons for denial.

2. Stamping of plans, specifications and compliance assurance program. Plans, specifications and compliance assurance programs shall be stamped "not approved." At least 2 copies shall be returned to the person submitting the application for approval; one copy shall be retained by the department.

(4) EVIDENCE OF APPROVAL. The manufacturer shall keep at each manufacturing plant where such building system or component is manufactured, one set of plans, specifications and compliance assurance program bearing the stamp of conditional approval. The conditionally approved plans, specifications and compliance assurance program shall be available for inspection by an authorized representative of the department during normal working hours.

(5) INSPECTIONS. Manufacturers shall contract with the department or an independent inspection agency to conduct inplant inspections to assure that the building system and components manufactured are in compliance with the plans, specifications and the compliance assurance program approved by the department. All inspections, for the purpose of administering and enforcing this code, shall be performed by a certified UDC inspector or inspectors.

(6) WISCONSIN INSIGNIA. Upon departmental approval of the plans, specifications and compliance assurance program, and satisfactory in-plant inspections of the building system and components, Wisconsin insignias shall be purchased from the department in accordance with the fee established in s. Comm 2.34. A manufacturer shall be entitled to display the Wisconsin insignia on any approved system or component.

(a) Lost or damaged insignia. 1. Notification. If Wisconsin insignias become lost or damaged, the department shall be notified immediately, in writing, by the manufacturer or dealer.

2. Return of damaged insignias. If Wisconsin insignias become damaged, the insignia shall be returned to the department with the appropriate fee to obtain a new insignia.

(b) Affixing Wisconsin insignias. Each Wisconsin insignia shall be assigned and affixed to a specific manufactured dwelling or component in the manner approved by the department before the dwelling is shipped from the manufacturing plant.

(c) Insignia records. 1. Manufacturer's insignia records. The manufacturer shall keep permanent records regarding the handling of all Wisconsin insignias, including construction compliance certificates, indicating the number of Wisconsin insignias which have been affixed to manufactured dwellings or manufactured building components (or groups of components); which Wisconsin insignias have been applied to which manufactured dwelling or manufactured building component; the disposition of any damaged or rejected Wisconsin insignias; and the location and custody of all unused Wisconsin insignias. The records shall be maintained by the manufacturer or by the independent inspection agency for at least 10 years. A copy of the records shall be sent to the department upon request.

2. Construction compliance certificate. Within 30 days after receiving the original Wisconsin insignias from the department, and at the end of each month thereafter, the manufacturer shall submit a construction compliance certificate, in the form determined by the department, for each manufactured dwelling intended for sale, use or installation in the state.

(d) Unit identification. Each manufactured dwelling and major transportable section or component shall be assigned a serial number. The serial number shall be located on the manufacturer's data plate.

(e) *Manufacturer's data plate*. The manufacturer's data plate for building systems shall contain the following information, where applicable:

1. Manufacturer's name and address;

2. Date of manufacture;

3. Serial number of unit;

4. Model designation;

5. Identification of type of gas required for appliances and directions for water and drain connections;

6. Identification of date of the codes or standards complied with;

7. State insignia number;

8. Design loads;

9. Special conditions or limitations of unit;

10. Electrical ratings; instructions and warnings on voltage, phase, size and connections of units and grounding requirements.

(7) RECIPROCITY. Upon request, the department will make available to any person a list of those states whose dwelling codes are considered equal to the codes established by the department and whose products are accepted reciprocally by Wisconsin.

and whose products are accepted reciprocally of wisconstin. **History:** Cr. Register, November, 1979, No. 287, eff. 6–1–80; am. (1) (a), r. and recr. (2) (a) 1. and (b) 1., Register, February, 1985, No. 350, eff. 3–1–85; correction in (6) (intro.) made under s. 13.93 (2m) (b) 7., Stats., Register, September, 1992, No. 441; an. (1), (2) (a) 2., Register, November, 1995, No. 479, eff. 12–1–95; am. (2) (a) 1. b., (b) 1. b., (5), Register, October, 1996, No. 490, eff. 11–1–96; correction in (6) (intro.) made under s. 13.93 (2m) (b) 7., Stats., Register, October, 1996, No. 490.

ILHR 20.15 Effect of approval. (1) RIGHT TO BEAR INSIGNIA. A manufactured dwelling or building component approved by the department, manufactured and inspected in accordance with this code, shall be entitled to bear the Wisconsin insignia.

(2) EFFECT OF INSIGNIA. Manufactured dwellings and manufactured building components bearing the Wisconsin insignia are deemed to comply with this code, except as to installation

site requirements, regardless of the provisions of any other ordinance, rule, regulation or requirement.

(3) RIGHT TO INSTALL. Manufactured dwellings and components bearing the Wisconsin insignia may be manufactured, offered for sale and shall be entitled to be installed anywhere in Wisconsin where the installation site complies with the other provisions of this code.

History: Cr. Register, November, 1979, No. 287, eff. 6-1-80.

ILHR 20.16 Suspension and revocation of approval. The department shall suspend or revoke its approval of a manufactured building system or manufactured building component if it determines that the standards for construction or the manufacture and installation of a manufactured building system or manufactured building component do not meet this code or that such standards are not being enforced as required by this code. The procedure for suspension and revocation of approval shall be as follows:

(1) FILING OF COMPLAINT. Proceedings to suspend or revoke an approval shall be initiated by the department or an independent inspection agency or UDC certified inspector having a contract with the manufacturer whose approval is sought to be suspended or revoked. Initiation shall be by a signed, written complaint filed with the department. Any alleged violation of the code shall be set forth in the complaint with particular reference to time, place and circumstance.

(2) INVESTIGATION AND NOTIFICATION. The department may investigate alleged violations on its own initiative or upon the filing of a complaint. If it is determined that no further action is warranted, the department shall notify the persons affected. If the department determines that there is probable cause, it shall order a hearing and notify the persons affected.

(3) MAILING. Unless otherwise provided by law, all orders, notices and other papers may be served by the department by certified mail to the persons affected at their last known address. If the service is refused, service may be made by sheriff without amendment of the original order, notice or other paper.

(4) RESPONSE. Upon receipt of notification of hearing from the department, the person charged with noncompliance or nonenforcement may submit to the department a written response within 30 days of the date of service. If the person charged files a timely written response, such person shall thereafter be referred to as the respondent.

(5) CONCILIATION AGREEMENT PRIOR TO HEARING. If the department and the respondent are able to reach agreement on disposition of a complaint prior to hearing, such agreement shall:

(a) Be transmitted in writing to the secretary;

(b) Not be binding upon any party until signed by all parties and accepted by the secretary;

(c) Not be considered a waiver of any defense nor an admission of any fact until accepted by the secretary.

(6) HEARINGS. (a) Subpoenas; witness fees. Subpoenas shall be signed and issued by the department or the clerk of any court of record. Witness fees and mileage of witnesses subpoenaed on behalf of the department shall be paid at the rate prescribed for witnesses in circuit court.

(b) Conduct of hearings. All hearings shall be conducted by persons selected by the department. Persons so designated may administer oaths or affirmations and may grant continuances and adjournments for cause shown. The respondent shall appear in person and may be represented by an attorney-at-law. Witnesses may be examined by persons designated by all parties.

(7) FINDINGS. The department shall make findings and enter its order within 14 days of the hearing. Any findings as a result of petition or hearing shall be in writing and shall be binding unless appealed to the secretary. (8) APPEALARGUMENTS. Appeal arguments shall be submitted to the department in writing in accordance with ch. 227, Stats., unless otherwise ordered. The department shall review and make a determination on an appeal of notification of suspension or revocation of approval within 45 business days of receipt of the appeal.

History: Cr. Register, November, 1979, No. 287, eff. 6-1-80; am. (8), Register, Pebmary, 1985, No. 350, eff. 3-1-85; am. (1), Register, October, 1996, No. 490, eff. 11-1-96.

ILHR 20.17 Effect of suspension and revocation. (1) BEARING OF INSIGNIA. Upon suspension or revocation by the department of the approval of any manufactured dwelling or manufactured building component, no further insignia shall be attached to any dwelling or building component manufactured with respect to which the approval was suspended or revoked. Upon termination of such suspension or revocation, insignias may again be attached to the dwelling or building component manufactured after the date approval is reinstated. Should any dwelling or building component have been manufactured during the period of suspension or revocation, it shall not be entitled to bear the Wisconsin insignia unless the department has inspected, or caused to be inspected, such manufactured dwelling or manufactured building component and is satisfied that all requirements for certification have been met.

(2) RETURN OF INSIGNIAS. The manufacturer shall return to the department all insignias allocated for a manufactured dwelling or manufactured building component no later than 30 days from the effective date of any suspension or revocation of the approval by the department. The manufacturer shall also return to the department all insignias which it determines for any reason are no longer needed.

History: Cr. Register, November, 1979, No. 287, eff. 6-1-80.

Subchapter VI—Approval of Materials

ILHR 20.18 Materials. (1) ALTERNATE MATERIALS. No provision in this code is intended to prohibit the use of an alternate material or method of construction if the alternate provides an equivalent level of safety and health protection. Approval of alternate materials or methods of construction shall be obtained from the department. Requests for approval shall be accompanied by a completed material approval application form, the appropriate fee in accordance with s. Comm 2.51 and evidence showing that the alternate material or method of construction performs in a manner at least equal to the material or method required by the code. The department may require claims regarding the equivalent performance of alternate materials or methods to be substantiated by test.

(a) Tests. The department may require that the materials, methods, systems, components, or equipment be tested to determine the suitability for the intended use. The department will accept results of tests conducted by a recognized independent testing agency. The cost of testing shall be borne by the person requesting the approval.

1. The test method used to determine the performance shall be one that is a nationally recognized standard.

2. If no nationally recognized standard exists, past performance or recognized engineering analysis may be used to determine suitability.

(2) UNGRADED OR USED MATERIALS. Ungraded or used building materials may be used or reused as long as the material possesses the essential properties necessary to achieve the level of performance required by the code for the intended use. The department or the municipality enforcing this code may require tests in accordance with sub. (1) (a).

(3) MATERIAL APPROVAL PROCESSING TIME. The department shall review and make a determination on an application for material, equipment or device approval within 30 business days of

receipt of all forms, fees, plans and documents required to complete the review.

History: Cr. Register, November, 1979, No. 287, eff. 6–1–80; cr. (3), Register, February, 1985, No. 350, eff. 3–1–85; am. (1), Register, November, 1995, No. 479, eff. 12–1–95; correction in (1) (intro.) made under s. 13.93 (2m) (b) 7., Stats., Register, October, 1996, No. 490.

Subchapter VII—Variances, Appeals, Violations and Penalties

ILHR 20.19 Petition for variance. The department may grant a variance to a rule only if the variance does not result in lowering the level of health, safety and welfare established or intended by the rule. The department may consider other criteria in determining whether a variance should be granted including the effect of the variance on uniformity.

(1) APPLICATION FOR VARIANCE. The applicant shall submit the petition for variance application to the municipality exercising jurisdiction in order to receive the municipal recommendation. Where no municipality exercises jurisdiction, the application shall be submitted to the department. The following items shall be submitted when requesting a variance:

(a) A clear written statement of the specific provisions of this code from which a variance is requested and the method of establishing equivalency to those provisions.

(b) A fee in accordance with s. Comm 2.52. The municipality may require a fee for the processing of the application in addition to the department's fee.

Note: A copy of the Petition for Variance form (SBD-9890) is contained in the Appendix.

(2) MUNICIPAL RECOMMENDATION. The municipality administering and enforcing this code shall submit all applications for variance to the department, together with a municipal recommendation within 10 business days after receipt of the application. The recommendation of the municipality shall include the following items:

(a) Inspections performed on the property.

(b) The issuance of correction orders on the property.

(c) An assessment of the overall impact of the variance on the municipality.

Note: A copy of the Municipal Recommendation form (SBD-9890) is contained in the Appendix.

(3) DEPARTMENTAL ACTION. Where a municipality administers and enforces the code, the department shall decide petitions for variance and shall mail notification to the municipality and the applicant within 5 business days after receipt of the application and municipal recommendation. Where the department enforces the code, the department shall decide petitions for variance within 15 business days after receipt of the application and fees.

(4) APPEALS. A person or municipality may appeal the determination of the department in the manner set out in s. 101.02 (6) (e) to (i) and (8), Stats.

History: Cr. Register, November, 1979, No. 287, cff. 6-1-80; am. Register, November, 1995, No. 479, cff. 12-1-95; correction in (1) (b) made under s. 13.93 (2m) (b) 7., Stats., Register, October, 1996, No. 490.

ILHR 20.20 Municipal variance from the code. Any municipality exercising or intending to exercise jurisdiction under this code may apply to the department for a variance permitting the municipality to adopt an ordinance not in conformance with this code. The department shall review and make a determination on a municipal request to adopt an ordinance not in conformance with this code within 60 business days of receipt of the request.

(1) APPLICATION FOR VARIANCE. The department may grant an application only under the following circumstances:

(a) The municipality has demonstrated that the variance is necessary to protect the health, safety or welfare of individuals within the municipality because of specific climate or soil conditions generally existing within the municipality. (b) The municipality has demonstrated that the granting of the variance, when viewed both individually and in conjunction with other variances requested by the municipality, does not impair the statewide uniformity of this code.

(2) DEPARTMENTAL INQUIRY. Prior to making a determination, the department shall solicit within the municipality and consider the statements of any interested persons as to whether or not said application should be granted.

(3) APPEALS. Any municipality aggrieved by the denial of an application may appeal the determination in accordance with the procedure set out in s. 101.02 (6) (e) to (i) and (8), Stats. The department shall review and make a determination on an appeal of denial of a municipal request to adopt an ordinance not in conformance with this code within 60 business days of receipt of the appeal.

(4) UNIFORMITY. This section shall be strictly construed in accordance with the goal of promoting statewide uniformity.

History: Cr. Register, November, 1979, No. 287, eff. 6-1-80; arm. (intro.) and (3), Register, February, 1985, No. 350, eff. 3-1-85.

ILHR 20.21 Appeals of orders, determinations, and for extension of time. (1) APPEALS OF ORDERS AND DETER-MINATIONS BY A MUNICIPALITY EXERCISING JURISDICTION. Appeals of an order or determination of a municipality exercising jurisdiction under this code, including denials of application for permits, shall be made in accordance with the procedure set out in ch. 68, Stats., except as follows:

(a) Appeals of final determinations by a municipality exercising jurisdiction. Appeals of final determination by municipalities shall be made to the department after the procedures prescribed in ch. 68, Stats., have been exhausted. All appeals to the department shall be in writing stating the reason for the appeal. All appeals shall be filed with the department within 10 business days of the date the final determination is rendered under ch. 68, Stats. The department shall render a written decision on all appeals within 60 business days of receipt of all calculations and documents necessary to complete the review.

Note: Chapter 68, Stats., provides that municipalities may adopt alternate administrative appeal procedures that provide the same due process rights as ch. 68, Stats. Municipalities having adopted such alternate procedures may follow those alternate procedures.

(2) APPEALS OF ORDERS AND DETERMINATIONS BY THE DEPART-MENT. Appeals of an order of the department made pursuant to the provisions of this code, including denials of application for permits, shall be in accordance with the procedure set out in s. 101.02 (6) (e) to (i) and (8), Stats. The department shall review and make a determination on an appeal of an order or determination within 60 business days of receipt of all calculations and documents necessary to complete the review.

(3) EXTENSIONS OF TIME. (a) The time for correction of cited orders as set out in s. ILHR 20.10 shall automatically be extended in the event that an appeal of said orders is filed. The extension of time shall extend to the termination of the appeal procedure and for such additional time as the department or municipality administering and enforcing this code may allow.

(b) The department or municipality administering and enforcing this code may grant additional reasonable time in which to comply with a violation order.

(4) APPEALS OF SOIL EROSION CONTROL ORDERS BY A MUNICI-PALITY FOR CESSATION OF WORK. (a) Appeals of orders for cessation of work issued under s. ILHR 20.10 (1) (c) may be made to the authority issuing the cessation of work order. The authority shall make a determination on such appeal within 3 business days. Determination of appeals by a municipality may be conducted in consultation with the department.

(b) Appeals of a final determination by a municipality on cessation of work orders may be made to the department. The department shall issue a final determination on the appeal within 3 business days after receipt of such appeal.

(c) If the issuing authority determines the site to be compliant with s. ILHR 21.125, orders shall be rescinded and work may commence.

History: Cr. Register, November, 1979, No. 287, eff. 6–1–80; am. (1) (a) and (2), Register, February, 1985, No. 350, eff. 3–1–85; cr. (4), Register, September, 1992, No. 441, eff. 12–1–92.

ILHR 20.22 Penalties and violations. (1) VIOLATIONS. No person shall construct or alter any dwelling in violation of any of the provisions of this code.

(a) *Injunction*. When violations occur, the department may bring legal action to enjoin any violations.

(b) Ordinances. This code shall not affect the enforcement of any ordinance or regulation, the violation of which occurred prior to the effective date of this code.

(2) PENALTIES. Pursuant to ss. 101.66 and 101.77, Stats., wheever violates this code shall forfeit to the state not less than \$25 nor more than \$500 for each violation. Each day that the violation continues, after notice, shall constitute a separate offense.

(3) MUNICIPAL ENFORCEMENT. Any municipality which administers and enforces this code may provide, by ordinance, remedies and penalties for violation of that jurisdiction exercised under s. 101.65, Stats. These remedies and penalties shall be in addition to those which the state may impose under subs. (1) and (2).

History: Cr. Register, November, 1979, No. 287, eff. 6-1-80; an. (3), Register, March, 1992, No. 435, eff. 4-1-92.

Subchapter IX—Adoption of Standards

ILHR 20.24 Adoption of standards. Pursuant to s. 227.21 (2), Stats., the attorney general and the revisor of statutes have consented to the incorporation by reference of the following standards. Copies of the standards are on file in the offices of the department, the secretary of state and the revisor of statutes. Copies may be purchased from the organizations listed.

(1) American Concrete Institute (ACI), P.O. Box 19150, Redford Station, Detroit, Michigan 48219.

(a) BUILDING CODE REQUIREMENTS FOR REINFORCED CONCRETE, ACI 318–89.

(b) BUILDING CODE REQUIREMENTS FOR STRUC-TURAL PLAIN CONCRETE, ACI 318.1–89.

(2) American Forest & Paper Association, 1250 Connecticut Avenue N.W., Washington, D.C. 20036.

(a) NATIONAL DESIGN SPECIFICATION FOR WOOD CONSTRUCTION, 1991 edition, except for section 4.1.7., including DESIGN VALUES FOR WOOD CONSTRUCTION, 1991, supplement.

(b) THE PERMANENT WOOD FOUNDATION SYSTEM, Basic Requirements, Technical Report No. 7, January, 1987, except for section 3.3.1.

(3) American Institute of Steel Construction (AISC), One E. Wacker Drive, Suite 3100, Chicago, IL 60601. SPECIFICATION FOR STRUCTURAL STEEL BUILDINGS, ALLOWABLE STRESS DESIGN AND PLASTIC DESIGN, WITH COM-MENTARY, June 1, 1989.

(4) American Society for Testing and Materials (ASTM), 1916 Race Street, Philadelphia, Pennsylvania 19103.

(a) STANDARD SPECIFICATION FOR BUILDING BRICK (SOLID MASONRY UNITS MADE FROM CLAY OR SHALE), ASTM C 62–92c.

(b) STANDARD SPECIFICATION FOR HOLLOW LOAD-BEARING CONCRETE MASONRY UNITS, ASTM C 90-94a.

(c) STANDARD SPECIFICATION FOR FACING BRICK (SOLID MASONRY UNITS MADE FROM CLAY OR SHALE), ASTM C 216-94a.

(d) STANDARD SPECIFICATION FOR MORTAR FOR UNIT MASONRY, ASTM C 270–94.

(c) STANDARD SPECIFICATION FOR HOLLOW BRICK (HOLLOW MASONRY UNITS MADE FROM CLAY OR SHALE), ASTM C 652–94.

(f) STANDARD SPECIFICATION FOR ASPHALT SHINGLES (ORGANIC FELT) SURFACED WITH MINERAL GRANULES, ASTM D 225–86.

(g) STANDARD SPECIFICATION FOR ASPHALT–SAT-URATED ORGANIC FELT USED IN ROOFING AND WATER PROOFING, ASTM D 226–89.

(h) STANDARD TEST METHOD FOR WIND-RESIS-TANCE OF ASPHALT SHINGLES (FAN-INDUCED METHOD), ASTM D 3161–93.

(i) STANDARD SPECIFICATION FOR ASPHALT SHINGLES MADE FROM GLASS FELT AND SURFACED WITH MINERAL GRANULES, ASTM D 3462–93a.

(j) STANDARD TEST METHODS FOR FIRE TESTS OF ROOF COVERINGS, ASTM E 108–93.

(k) STANDARD PRACTICE FOR MEASURING AIR LEAKAGE BY THE FAN PRESSURIZATION METHOD, ASTM E 779–87.

(5) American Society of Heating, Refrigerating, and Airconditioning Engineers, Inc. (ASHRAE), 1791 'Tullie Circle, N.E., Atlanta, Georgia 30329.

(a) ENERGY CONSERVATION IN NEW BUILDING DESIGN, ASHRAE Standard 90A-80.

(b) ASHRAE HANDBOOK, FUNDAMENTALS, 1993 edition.

(6) American Wood Preservers Association (AWPA), P.O. Box 849, Stevensville, Maryland 21666.

(a) STANDARD FOR COAL TAR CREOSOTE FOR LAND AND FRESH WATER AND MARINE (COASTAL WATER) USE, P1/P13-91.

(b) STANDARD FOR CREOSOTE SOLUTIONS, P2-90.

(c) STANDARD FOR CREOSOTE-PETROLEUM OIL SOLUTION, P3-67.

(d) STANDARDS FOR WATERBORNE PRESERVATIVES, P5–93.

(e) STANDARDS FOR OIL-BORNE PRESERVATIVES, P8-93.

(f) STANDARDS FOR SOLVENTS AND FORMULA-TIONS FOR ORGANIC PRESERVATIVE SYSTEMS, P9–92.

(g) ALL TIMBER PRODUCTS—PRESERVATIVE TREAT-MENT BY PRESSURE PROCESSES, C1–93.

(h) LUMBER, TIMBERS, BRIDGE TIES AND MINE TIES—PRESERVATIVE TREATMENT BY PRESSURE PRO-CESSES, C2-93. (j) POLES---PRESERVATIVE TREATMENT BY PRES-SURE PROCESSES, C4–93.

(k) PLYWOOD—PRESERVATIVE TREATMENT BY PRESSURE PROCESSES, C9–93.

(L) STANDARD FOR PRESSURE TREATED MATERIAL IN MARINE CONSTRUCTION, C18–92.

(m) LUMBER AND PLYWOOD FOR PERMANENT WOOD FOUNDATIONS—PRESERVATIVE TREATMENT BY PRESSURE PROCESSES, C23–93.

(n) ROUND POLES AND POSTS USED IN BUILDING CONSTRUCTION---PRESERVATIVE TREATMENT BY PRESSURE PROCESSES, C23–92.

(o) SAWN TIMBER PILES USED FOR RESIDENTIAL AND COMMERCIAL BUILDING, C24-93.

(p) STANDARD FOR PRESERVATIVE TREATMENT OF STRUCTURAL GLUED LAMINATED MEMBERS AND LAMINATIONS BEFORE GLUING OF SOUTHERN PINE, COASTAL DOUGLAS FIR, HEMFIR AND WESTERN HEM-LOCK BY PRESSURE PROCESSES, C28–91.

(q) STANDARD FOR THE CARE OF PRESERVATIVE-TREATED WOOD PRODUCTS, M4-91.

(7) National Fire Protection Association, Batterymarch Park, Quincy, Massachusetts 02269. NATIONAL FUEL GAS CODE, NFPA 54–1992, Parts 2 and 3.

(8) National Institute of Standards and Technology, U.S. Department of Commerce, Washington, D.C. 20234. MODEL DOCUMENTS FOR THE EVALUATION, APPROVAL, AND INSPECTION OF MANUFACTURED BUILDINGS, NBS Building Science Series 87, July 1976.

(9) Portland Cement Association, 5420 Old Orchard Road, Skokie, Illinois 60077, CONCRETE MASONRY HANDBOOK FOR ARCHITECTS, ENGINEERS, BUILDERS, fifth edition, 1991.

(10) Truss Plate Institute, Inc., 583 D'Onofrio Drive, Madison, Wisconsin 53719.

(a) DESIGN SPECIFICATION FOR METAL PLATE CON-NECTED WOOD TRUSSES, TPI-85.

(b) DESIGN SPECIFICATION FOR METAL PLATE CON-NECTED PARALLEL CHORD WOOD TRUSSES, PCT-80.

NECTED PARALLEL CHORD WOOD TRUSSES, PCI-80, History: Cr. Register, November, 1979, No. 287, eff. 6–1-80; am. (intro.) and (2), cr. (2m) and (2n), r. and recr. (4), Register, February, 1985, No. 350, eff. 3–1-85; renum. (2m) to be (2k) and am., cr. (2m), Register, July, 1986, No. 367, eff. 1–1-87; an. (intro.), (1), (2k) and (4), r. (2n), cr. (2p), (2s) and (3m), Register, January, 1989, No. 397, eff. 2–1-89; am. (intro.), (1), (2), (2k), (2m), (2p), (2s), (3m), (4), (5), cr. (6), Register, March, 1992, No. 435, eff. 4–1–92; r. and recr., Register, November, 1995, No. 479, eff. 12–1-95.