# Chapter NR 253

#### COPPER FORMING

NR 253.01	Purpose.	NR 253.12	Effluent limitations representing the degree of effluent reduction
NR 253.02	Applicability.		attainable by the application of the best available technology eco-
NR 253.03	General definitions.		nomically achievable.
NR 253,04	Monitoring and reporting requirements.	NR 253.13	New source performance standards.
NR 253.05	Compliance dates.	NR 253,14	Pretreatment standards for existing sources. Except as provided in ss.
Subchapter I NR 253.10 NR 253.11	The Copper Forming Subcategory     Applicability; description of the copper forming subcategory.     Effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.	NR 253,15	NR 211.13 and 211.14, any existing source subject to this sub- chapter which introduces pollutants into a POTW shall comply with ch. NR 211 and achieve the following PSES: Pretreatment standards for new sources.
	technology currently available.		The state of the s

NR 253.01 Purpose. The purpose of this chapter is to establish effluent limitations, standards of performance, and pretreatment standards for discharges of process wastes from the copper forming point source category and its subcategories.

History: Cr. Register, May, 1989, No. 401, eff. 6-1-89.

- NR 253.02 Applicability. This chapter applies to discharges resulting from hot rolling, cold rolling, drawing, extrusion, and forging of copper and copper alloys and the associated ancillary operations. This chapter does not apply to the forming of precious metals, which is regulated by 40 CFR 471, or the casting of copper or copper alloys, which is regulated by ch. NR 256. History: Cr. Register, May, 1989, No. 401, eff. 6–1–89.
- NR 253.03 General definitions. The following definitions are applicable to the terms used in this chapter. Definitions of other terms and abbreviations are set forth in ss. NR 205.03, 205.04 and 211.03.
- (1) "Alkaline cleaning bath" means a bath consisting of an alkaline cleaning solution through which a workpiece is processed.
- (2) "Alkaline cleaning rinse" means a rinse following an alkaline cleaning bath through which a workpiece is processed. A rinse consisting of a series of rinse tanks is considered as a single rinse.
- (3) "Alkaline cleaning rinse for forged parts" means a rinse following an alkaline cleaning bath through which a forged part is processed. A rinse consisting of a series of rinse tanks is considered as a single rinse.
- (4) "Ancillary operation" means an operation, such as surface and heat treatment, hydrotesting, sawing, and surface coating, associated with a primary forming operation.
- (5) "Annealing with oil" means the use of oil to quench a workpiece as it passes from an annealing furnace.
- (6) "Annealing with water" means the use of a water spray or bath, of which water is the major constituent, to quench a workpiece as it passes from an annealing furnace.
- (7) "Beryllium copper alloy" means any copper alloy that is alloyed to contain 0.10% or greater beryllium.
- (8) "Cold rolling" means the process of rolling a workpiece below the recrystallization temperature of the copper or copper alloy.
- (9) "Drawing" means pulling the workpiece through a die or succession of dies to reduce the diameter or alter its shape.
- (10) "Existing source" means any point source, except for a new source as defined in sub. (16), from which pollutants may be discharged either into waters of the state or into a publicly owned treatment works.
- (11) "Extrusion" means the application of pressure to a copper workpiece, forcing the copper to flow through a die orifice.

- (12) "Extrusion heat treatment" means the spray application of water to a workpiece for the purpose of heat treatment immediately following extrusion.
- (13) "Hot rolling" means the process of rolling a workpiece above the recrystallization temperature of the copper or copper alloy.
- (14) "Heat treatment" means the application of heat to or the removal of heat from a workpiece to change the physical properties of the metal.
- (15) "Miscellaneous waste stream" means hydrotesting, sawing, surface milling, and maintenance wastestreams when they are related to the forming of copper.
- (16) "New source", as defined for new source performance standards and pretreatment standards for new sources, means any point source for which construction commenced after November 12, 1982 and from which pollutants are or may be discharged directly to the waters of the state or to a publicly owned treatment works.
- (17) "Off kilogram" and "off pound" mean the mass of copper or copper alloy removed from a forming or ancillary operation at the end of a process cycle for transfer to a different machine or process.
- (18) "Pickling bath" means a chemical bath, other than an alkaline cleaning bath, through which a workpiece is processed.
- (19) "Pickling fume scrubber" means an air pollution control device which removes particulates and fumes from air above a pickling bath by entraining the pollutants in water.
- (20) "Pickling rinse" means a rinse, other than an alkaline cleaning rinse, through which a workpiece is processed. A rinse consisting of a series of rinse tanks is considered as a single rinse.
- (21) "Pickling rinse for forged parts" means a rinse, other than an alkaline cleaning rinse, through which forged parts are processed. A rinse consisting of a series of tanks is considered as a single rinse,
- (22) "Precious metals" means gold, platinum, palladium, silver, and their alloys when the alloy contains 30% or greater percent by weight of precious metals.
- (23) "Primary forming operation" means hot rolling, cold rolling, drawing, extrusion, and forging of copper and copper alloys.
- (24) "Rolling" means reducing the thickness or diameter of a workpiece by passing it between rollers.
- (25) "Solution heat treatment" means introducing a workpiece into a quench bath for purposes of heat treatment.
- (26) "Spent lubricant" means water or an oil and water mixture which has been used in forming operations to reduce friction, heat, and wear and which is discharged.

- (27) "Surface coating" means the process of coating a copper workpiece, as well as the associated surface washing and flatten-
- (28) "Total toxic organics" and "TTO" mean the sum of the masses or concentrations of each of the following organic compounds which is found at a concentration greater than 0.010 mg/l: anthracene

benzene chloroform 2,6-dinitrotoluene ethylbenzene methylene chloride naphthalene N-nitrosodiphenylamine

phenanthrene toluene

1,1,1-trichloroethane trichlorethylene.

(29) "Tumbling or burnishing" means polishing, deburring, removing sharp corners, and generally smoothing parts for both cosmetic and functional purposes and washing the finished parts and cleaning the abrasive media.

History: Cr. Register, May, 1989, No. 401, eff. 6-1-89.

#### NR 253.04 Monitoring and reporting requirements. The following special monitoring and reporting requirements apply to all facilities subject to this chapter:

- (1) The "monthly average" regulatory values shall be the basis for the monthly average discharge in direct discharge permits and for pretreatment standards. Compliance with the monthly discharge limit is required regardless of the number of samples analyzed and averaged.
- 2) As an alternate monitoring procedure for TTO, indirect dischargers may monitor for oil and grease and meet the alternate monitoring standards for oil and grease established for PSES and PSNS. Any indirect discharger meeting the alternate monitoring standards shall be considered to meet the TTO standard.

History: Cr. Register, May, 1989, No. 401, eff. 6-1-89.

NR 253.05 Compliance dates. (1) Any existing source subject to this chapter which discharges to waters of the state shall achieve:

- (a) The effluent limitations representing BPT by July 1, 1977; and
  - (b) The effluent limitations representing BAT by July 1, 1984.
- (2) Any new source subject to this chapter which discharges to waters of the state shall achieve NSPS at the commencement of discharge.
- (3) Any existing source subject to this chapter which introduces process wastewater pollutants into a POTW shall achieve PSES by August 15, 1986.
- (4) Any new source subject to this chapter which introduces process wastewater pollutants into a POTW shall achieve PSNS at the commencement of discharge.

History: Cr. Register, May, 1989, No. 401, eff. 6-1-89.

## Subchapter I - The Copper Forming Subcategory

NR 253.10 Applicability; description of the copper forming subcategory. This subchapter applies to the discharge of pollutants to waters of the state and the introduction of pollutants into POTWs from the forming of copper and copper alloys except beryllium copper alloys.

History: Cr. Register, May, 1989, No. 401, eff. 6-1-89.

NR 253.11 Effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available. Except as provided in 40 CFR 125.30 to 125.32, any existing source subject to this subchapter shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of BPT:

> Table 1 Hot Rolling Spent Lubricant

BPT Effluent Limitations			
	Maximum for any 1 day	Maximum for monthly average	
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy hot rolled		
Chromium	0.045	0.018	
Copper	0.195	0.103	
Lead .	0.015	0.013	
Nickel	0.197	0.130	
Zinc	0.150	0.062	
Oil and grease	2,060	1.236	
TSS	4.223	2.008	
pН	(1)	(1)	

(1) Within the range of 7.5 to 10.0 at all times

Table 2 Cold Rolling Spent Lubricant

	oning open Lubii	
BPT	Effluent Limitation	ns .
	Maximum for any 1 day	Maximum for monthly average
Poliutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy cold rolled	
Chromium	0.166	0.068
Copper	0.720	0,379
Lead	0.056	0.049
Nickel	0.727	0.481
Zinc	0.553	0,231
Oil and grease	7.580	4.548
TSS	15.539	7.390
pН	(1)	(1)

Table 3

Drawing Spent Lubricant (1)				
BPT Effluent Limitations				
	Maximum for any 1 day	Maximum for monthly average		
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy drawn			
Chromium	0.037	0.015		
Copper	0.161	0.085		
Lead	0.012	0.011		
Nickel	0.163	0.107		
Zinc	0.124	0.051		
Oil and grease	1.700	1.020		
TSS	3.485	1,657		
рН	(2)	(2)		

- (1) These effluent limitations are applicable only to those plants which actually discharge the drawing spent lubricant wastestream at the copper forming site. If these wastewaters are hauled off-site for disposal or are otherwise not discharged at the copper forming site, these limitations are neither applicable nor allowable.
- (2) Within the range of 7.5 to 10.0 at all times

Table 4
Solution Heat Treatment

3010	mon rieat freatme	
BPT	Effluent Limitation	ns
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pour , off-pounds) of c alloy heat treated	
Chromium	1,118	0.457
Copper	4,827	2.541
Lead	0.381	0.330
Nickel	4,878	3.227
Zinc	3.709	1.550
Oil and grease	50.820	30.492
TSS	104.181	49.549
Hq	(1)	(1)

Table 5
Extrusion Heat Treatment

BPT	Effluent Limitatio	ns
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy heat treated	
Chromium	0.00088	0.00036
Copper	0.003	0.002
Lead	0.0003	0.00026
Nickel	0.003	0.002
Zinc	0.002	0.001
Oil and grease	0.040	0.024
TSS	0.082	0.039
pН	(1)	(1)

(1) Within the range of 7.5 to 10.0 at all times

Table 6 Annealing With Water

Anneaning with water				
BPT	BPT Effluent Limitations			
	Maximum for any 1 day	Maximum for monthly average		
Pollutant or pollutant property mg/off-kg (poun off-pounds) of c alloy annealed w				
Chromium	2.439	1.020		
Copper	10.767	5.667		
Lead	0.850	0.736		
Nickel	10.880	7.197		
Zinc	8.273	3.456		
Oil and grease	113.340	68.004		
TSS	232.347	110.506		
pH	(1)	(1)		

(1) Within the range of 7.5 to 10.0 at all times

Table 7
Annealing With Oil

BPT Effluent Limitations			
	Maximum for any 1 day	Maximum for monthly average	
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy annealed with oil		
Chromium	0	0	
Copper	0	0	
Lead	0	0	
Nickel	0	0	
Zinc	0	0	
Oil and grease	0	0	
TSS	0	0	
pH	(1)	(1)	

(1) Within the range of 7.5 to 10.0 at all times

Table 8 Alkaline Cleaning Rinse

BPT Effluent Limitations				
	Maximum for any 1 day	Maximum for monthly average		
Pollutant or pollutant property mg/off-kg (pounds per 1,000,0 off-pounds) of copper or copper alloy alkaline cleaned		opper or copper		
Chromium	1.854	0.758		
Copper	8.006	4.214		
Lead	0.632	0.547		
Nickel	8.090	5.351		
Zinc	6.152	2.570		
Oil and grease	84.280	50,568		
TSS	172.774	82.173		
pН	(1)	(1)		

(1) Within the range of 7.5 to 10.0 at all times

Table 9
Alkaline Cleaning Rinse For Forged Parts

BPT Effluent Limitations			
	Maximum for any 1 day	Maximum for monthly average	
Pollutant or pollutant property	off-pounds) of c	mg/off–kg (pounds per 1,000,000 off–pounds) of copper or copper alloy forged parts alkaline cleaned	
Chromium	5.562	2.275	
Copper	24,019	12.642	
Lead	1.896	1.643	
Nickel	24.272	16,055	
Zinc	18.457	7.711	
Oil and grease	252.840	151.704	
TSS	518.322	246.519	
pН	(1)	(1)	

Table 10 Alkaline Cleaning Bath

Alkaline Cleaning Bain				
BPT Effluent Limitations				
	Maximum for any 1 day	Maximum for monthly average		
Pollutant or pollutant property	mg/off-kg(pounds per 1,000,000 off-pounds) of copper or copper alloy alkaline cleaned			
Chromium	0.020	0.0084		
Copper	0.089	0.046		
Lead	0.0070	0.0060		
Nickel	0.089	0.059		
Zinc	0.068	0.028		
Oil and grease	0.93	0.56		
TSS	1.91	0.91		
На	(1)	(1)		

Table 11 Pickling Rinse

BPT	BPT Effluent Limitations		
	Maximum for any 1 day	Maximum for monthly average	
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy pickled		
Chromium	1.593	0.651	
Copper	6.881	3.622	
Lead	0.543	0.470	
Nickel	6.954	4.599	
Zinc	5.288	2.209	
Oil and grease	72.440	43.464	
TSS	148.502	70.629	
pН	(1)	(1)	

(1) Within the range of 7.5 to 10.0 at all times

Table 12
Pickling Rinse For Forged Parts

BPT Effluent Limitations				
	Maximum for any 1 day	monthly average		
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off- pounds) of copper or copper alloy forged parts pickled			
Chromium	1.723	0.705		
Copper	7.444	3.918		
Lead	0.587	0.509		
Nickel	7.522	4.975		
Zinc	5.720	2.389		
Oil and grease	78.360	47.016		
TSS	160.638	76.401		
pН	(1)	(1)		

(1) Within the range of 7.5 to 10.0 at all times

Table 13 Pickling Bath

ВРТ	Effluent Limitation	ns
V. 1	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/offkg (pounds per 1,000,000 offpounds) of copper or copper alloy pickled	
Chromium	0.051	0.020
Соррег	0.220	0.116
Lead	0.017	0.015
Nickel	0,222	0.147
Zinc	0.169	0.070
Oil and grease	2.320	1.392
TSS	4.756	2,262
pН	(1)	(1)

(1) Within the range of 7.5 to 10.0 at all times

Table 14
Pickling Fume Scrubber

BPT	Effluent Limitation	ns ·
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy pickled	
Chromium	0.275	0.112
Copper	1.189	0.626
Lead	0.093	0.081
Nickel	1.201	0.795
Zinc	0.913	0.381
Oil and grease	12.520	7.512
TSS	25.666	12.207
pH	(1)	(1)

(1) Within the range of 7.5 to 10.0 at all times

Table 15
Tumbling or Burnishing

BPT	Effluent Limitation	ns
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy tumbled or burnished	
Chromium	0.256	0.104
Copper	1.107	0.583
Lead	0.087	0.075
Nickel	1.119	0.740
Zinc	0.851	0.355
Oil and grease	11.660	6.996
TSS	23.903	11.368
pH	(1)	(1)

Table 16
Surface Coating BPT Effluent Limitations

Surface Coau	ing de l'Enluein L	mmanons
	Maximum for any I day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pour off-pounds) of c alloy surface coa	
Chromium	0.326	0.133
Copper	1.411	0.743
Lead	0.111	0.096
Nickel	1.426	0.943
Zinc	1.084	0.453
Oil and grease	14.680	8.916
TSS	30,463	14.488
pН	(1)	(1)

(1) Within the range of 7.5 to 10.0 at all times

Miscellaneous Waste Streams

11115001	HILCOUS THUSEC DUC	41110
BPT	Effluent Limitation	ns
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy formed		
Chromium	0.009	0.003
Copper	0.041	0.021
Lead	0.003	0.002
Nickel	0.041	0.027
Zinc	0.031	0.013
Oil and grease	0.436	0.261
TSS	0.893	0.425
pH	(1)	(1)

(1) Within the range of 7.5 to 10.0 at all times
History: Cr. Register, May, 1989, No. 401, eff. 6-1-89.

NR 253.12 Effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable. Except as provided in 40 CFR 125.30 to 125.32, any existing source subject to this subchapter shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of BAT:

Table 18 Hot Rolling Spent Lubricant

BAT	Effluent Limitation	ns
after the first and antique of the second	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pour off-pounds) of c alloy hot rolled	nds per 1,000,000 copper or copper
Chromium	0,045	0.018
Copper	0.195	0.103
Lead	0.015	0.013
Nickel	0.197	0.130
Zinc	0.150	0.062

Table 19 Cold Rolling Spent Lubricant

BAT	'Effluent Limitation	ons
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy cold rolled	
Chromium	0.166	0.068
Copper	0.720	0.379
Lead	0.056	0,049
Nickel	0.727	0.481
Zinc	0.553	0.231

## Table 20 Drawing Spent Lubricant

BAT	Effluent Limitatio	ns	
	Maximum for any 1 day	Maximum for monthly average	
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy drawn		
Chromium	0.037	0.015	
Copper	0.161	0.085	
Lead	0.012	0.011	
Nickel	0.163	0.107	
Zinc	0.124	0.051	

## Table 21 Solution Heat Treatment

BAT Effluent Limitations			
: .	Maximum for any 1 day	Maximum for monthly average	
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy heat treated		
Chromium	0.284	0.116	
Copper	1,227	0.646	
Lead	0.096	0.083	
Nickel	1.240	0.820	
Zinc	0.943	0.394	

#### Table 22 **Extrusion Heat Treatment**

BAT	Effluent Limitatio	ns
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy heat treated	
Chromium	0.00088	0.00036
Copper	0.003	0.0020
Lead	0,0003	0.00026
Nickel	0.003	0.002
Zinc	0.002	0.001

Table 23			
Annealing	With	Water	

An	nearing with water	
BAT	Effluent Limitation	ns
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy annealed with water		
Chromium	0.545	0.223
Copper	2.356	1.240
Lead	0.186	0.161
Nickel	2.380	1.574
Zinc	1.810	0.756

Table 24 Annealing With Oil

BAT Effluent Limitations			
	Maximum for any 1 day	Maximum for monthly average	
mg/off-kg (pounds per 1,000,000			
Pollutant or pollutant	off-pounds) of copper or copper		
property	alloy annealed with oil		
Chromium	0	0 .	
Copper	0	0	
Lead	0	0	
Nickel	0 .	0	
Zinc	0	0	

Table 25 Alkaline Cleaning Rinse

- Alkamo Crauling Ruiso			
BAT Effluent Limitations			
	Maximum for any 1 day	Maximum for monthly average	
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy alkaline cleaned		
Chromium	1.854	0.758	
Copper	8.006	4.214	
Lead	0.632	0.547	
Nickel	8.090	5,351	
Zinc	6.152	2,570	

Table 26 Alkaline Cleaning Rinse For Forged Parts

BAT Effluent Limitations				
Maximum for Maximum for any 1 day monthly averag				
mg/off-kg (pounds per 1,000,000				
Pollutant or pollutant	off-pounds) of copper or copper			
property	alloy forged parts alkaline cleaned			
Chromium	5.562	2.275		
Copper	24.019	12.642		
Lead	1.896	1.643		
Nickel	24,272	16.055		
Zinc	18.457	7.711		

Table 27
Alkaline Cleaning Bath

rimanio Ordanio Dani			
BAT Effluent Limitations			
4	Maximum for any 1 day	Maximum for monthly average	
mg/off-kg (pounds per 1,000,000 Pollutant or pollutant property alloy alkaline cleaned			
Chromium	0.020	0.0084	
Copper	0.088	0.046	
Lead	0.0070	0.0060	
Nickel	0.089	0.059	
Zinc	0.068	0.028	

Table 28 Pickling Rinse

	Pickling Kinse		
BAT Effluent Limitations			
	Maximum for any 1 day	Maximum for monthly average	
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy pickled		
Chromium	0.574	0.235	
Copper	2.481	1.306	
Lead	0.195	0.169	
Nickel	2.507	1.658	
Zinc	1.906	0.796	

# Table 29 Pickling Rinse For Forged Parts

Treating tenner to tronger times			
BAT Effluent Limitations			
	Maximum for any 1 day	Maximum for monthly average	
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy forged parts pickled		
Chromium	1.723	0.705	
Copper	7.444	3.918	
Lead	0.587	0.509	
Nickel	7.522	4.975	
Zinc	5.720	2.389	

## Table 30 Pickling Bath

BAT Effluent Limitations			
	Maximum for any 1 day	Maximum for monthly average	
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy pickled		
Chromium	0.051	0.020	
Copper	0.220	0.116	
Lead	0.017	0.015	
Nickel	0.222	0.147	
Zinc	0.169	0.070	

Table 31
Pickling Fume Scrubber

1 ION	ing I allo berabor			
BAT Effluent Limitations				
	Maximum for any 1 day	Maximum for monthly average		
Pollutant or pollutant property mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy pickled				
Chromium	0.275	0.112		
Copper	1.189	0.626		
Lead	0.093	0.081		
Nickel	1,201	0.795		
Zinc	0.913	0.381		

Table 32
Tumbling or Burnishing

BAT Effluent Limitations			
	Maximum for any 1 day	Maximum for monthly average	
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy tumbled or burnished		
Chromium	0.256	0.104	
Copper	1.107	0.583	
Lead	0.087	0.075	
Nickel	1.119	0.740	
Zinc	0.851	0.355	

Table 33 Surface Coating

BAT Effluent Limitations			
All the hand of the best should	Maximum for Maximum for any 1 day monthly average		
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy surface coated		
Chromium	0.326	0.133	
Copper	1.411	0.743	
Lead	0.111	0.096	
Nickel	1.426	0.943	
Zinc	1.084	0.453	

Table 34
Miscellaneous Waste Streams

BAT	Effluent Limitatio	ns
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy formed	
Chromium	0.009	0.003
Copper	0.041	0.021
Lead	0.003	0.002
Nickel	0.041	0.027
Zinc	0.031	0.013

History: Cr. Register, May, 1989, No. 401, eff. 6-1-89.

NR 253.13 New source performance standards. The discharge of process wastewater pollutants from any new source subject to this subchapter may not exceed the following NSPS:

Table 35
Hot Rolling Spent Lubricant

	NSPS	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy hot rolled	
Chromium	0.038	0.015
Copper	0.131	0.062
Lead	0.010	0.0092
Nickel	0.056	0.038
Zinc	0.105	0.043
Oil and grease	1.030	1.030
TSS	1.545	1.236
pН	(1)	(1)

(1) Within the range of 7.5 to 10.0 at all times

Table 36
Cold Rolling Spent Lubricant

	NSPS	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy cold rolled	
Chromium	0.140	0.056
Copper	0.485	0,231
Lead	0.037	0.034
Nickel	0.208	0.140
Zinc	0.386	0,159
Oil and grease	3,790	3,790
TSS	5.685	4,548
рН	(1)	(1)

Table 37
Drawing Spent Lubricant

• • • • • • • • • • • • • • • • • • • •	NSPS	
Pollutant or pollutant property mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy drawn		
Chromium	0.031	0.012
Copper	0.108	0.051
Lead	0.0085	0.0076
Nickel	0.046	0.031
Zinc	0.086	0.035
Oil and grease	0.85	0.85
TSS	1.275	1.020
рН	(1)	(1)

<sup>(1)</sup> Within the range of 7.5 to 10.0 at all times

Table 38 Solution Heat Treatment

	NSPS	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pour off-pounds) of c alloy heat treated	
Chromium	0.239	0.096
Copper	0.826	0.394
Lead	0.064	0.058
Nickel	0.355	0,239
Zinc	0.658	0.271
Oil and grease	6.460	6.460
TSS	9.690	7,752
pH	(1)	(1)

<sup>(1)</sup> Within the range of 7.5 to 10.0 at all times

Table 39 Extrusion Heat Treatment

	NSPS	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy heat treated	
Chromium	0.00074	0.00030
Copper	0.0020	0.0010
Lead	0.00020	0.00018
Nickel	0.0010	0.00074
Zinc	0.0020	0.00084
Oil and grease	0.020	0.020
TSS	0.030	0.024
pН	(1)	(1)

<sup>(1)</sup> Within the range of 7.5 to 10.0 at all times

Table 40 Annealing With Water

	NSPS	
*****	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy annealed with water	
Chromium	0.458	0.186
Copper	1.587	0.756
Lead	0.124	0.111
Nickel	0.682	0.458
Zinc	1,264	0.520
Oil and grease	12.400	12.400
TSS	18,600	14.880
pН	(1)	(1)

Table 41
Annealing With Oil

	NSPS	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy annealed with oil	
Chromium	0	0
Copper	0	0
Lead	0	0
Nickel	0	0
Zinc	0	0
Oil and grease	0	0
TSS	0	0
pH	(1)	(1)

Table 42
Alkaline Cleaning Rinse

AIK	ume Cleaning Kins	ie
· · · · · · · · · · · · · · · · · · ·	NSPS	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy alkaline cleaned	
Chromium	1.559	0.632
Copper	5,393	2.570
Lead	0.421	0.379
Nickel	2,317	1.559
Zinc	4.298	1.769
Oil and grease	42.140	42.140
TSS	63,210	50.568
pH	(1)	(1)

<sup>(1)</sup> Within the range of 7.5 to 10.0 at all times

Table 43 Alkaline Cleaning Rinse For Forged Parts

	NSPS	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy alkaline cleaned	
Chromium	4.677	1,896
Copper	16,181	7.711
Lead	1.264	1,137
Nickel	6.953	4.677
Zinc	12.894	5.309
Oil and grease	126.420	126,420
TSS	189,630	151.704
nΗ	(I)	(1)

Table 44
Alkaline Cleaning Bath

Alkainie Cleaning Dani				
	NSPS			
	Maximum for any 1 day	Maximum for monthly average		
Pollutant or pollutant property	mg/off-kg (pour off-pounds) of c alloy alkaline cle			
Chromium	0.017	0.0070		
Copper	0.059	0.028		
Lead	0.0046	0.0042		
Nickel	0.025	0.017		
Zinc	0.047	0.019		
Oil and grease	0.46	0.46		
TSS	0.70	0.56		
pН	(1)	(1)		

(1) Within the range of 7.5 to 10.0 at all times

Table 45 Pickling Rinse

,	NSPS	
	Maximum for	Maximum for
	any 1 day	monthly average
	mg/off-kg (poun	ds per 1,000,000
Pollutant or pollutant	off-pounds) of c	opper or copper
property	alloy pickled	
Chromium	0.216	0.087
Copper	0.748	0.356
Lead	0.058	0.052
Nickel	0.321	0.216
Zinc	0.596	0.245
Oil and grease	5.850	5.850
TSS	8.775	7.020
pН	(1)	(1)
Lead Nickel Zinc Oil and grease TSS pH	0.058 0.321 0.596 5.850 8.775	0.052 0.216 0.245 5.850 7.020

(1) Within the range of 7.5 to 10.0 at all times

Table 46
Pickling Rinse For Forged Parts

	NSPS	notice 7
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy forged parts pickled	
Chromium	0.649	0.263
Copper	2.246	1.070
Lead	0.175	0.157
Nickel	0.965	0.649
Zinc	1.790	0.737
Oil and grease	17.550	17,550
TSS	26,325	21.060
pН	(1)	(1)

(1) Within the range of 7.5 to 10.0 at all times

Table 47 Pickling Bath

,	NSPS	
P. H. J H. J P	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy pickled	
Chromium	0.042	0.017
Copper	0.148	0.070
Lead	0.011	0.010
Nickel	0.063	0.042
Zinc	0.118	0.048
Oil and grease	1.160	1.160
TSS	1.740	1.392
pН	(1)	(1)

(1) Within the range of 7.5 to 10.0 at all times

Table 48
Pickling Fume Scrubber

	NSPS	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy pickled	
Chromium	0.231	0.093
Copper	0.801	0.381
Lead	0.062	0.056
Nickel	0.344	0.231
Zinc	0.638	0.262
Oil and grease	6.260	6.260
TSS	9.390	7.512
pН	(1)	(1)

Table 49 Tumbling or Burnishing

	NSPS	
:	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/offkg (pour offpounds) of c alloy tumbled or	
Chromium	0.215	0.087
Copper	0.746	0.355
Lead	0.058	0.052
Nickel	0.320	0.215
Zinc	0.594	0.244
Oil and grease	5.830	5.830
TSS	8.745	6.996
pН	(1)	(1)

Table 50 Surface Coating

	Surface Coating	
•	NSPS	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy surface coated	
Chromium	0.274	0.111
Copper	0.951	0.453
Lead	0.074	0.066
Nickel	0.408	0.274
Zinc	0.757	0.312
Oil and grease	7.430	7.430
TSS	11.145	8.916
pН	(1)	(1)

(1) Within the range of 7.5 to 10.0 at all times

Table 51
Miscellaneous Waste Streams

Miscellaneous waste Streams				
	NSPS			
	Maximum for any 1 day	Maximum for monthly average		
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy formed			
Chromium	0.008	0.003		
Copper	0.027	0.013		
Lead	0.0021	0.0019		
Nickel	0.011	0.008		
Zinç	0.022	0.009		
Oil and grease	0.218	0.218		
TSS	0.327	0.261		
pН	(1)	(1)		

(1) Within the range of 7.5 to 10.0 at all times

History: Cr. Register, May, 1989, No. 401, eff. 6-1-89.

NR 253.14 Pretreatment standards for existing sources. Except as provided in ss. NR 211.13 and 211.14, any

existing source subject to this subchapter which introduces pollutants into a POTW shall comply with ch. NR 211 and achieve the following PSES:

Table 52 Hot Rolling Spent Lubricant

<del></del>	PSES	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (poun off-pounds) of c alloy hot rolled	ds per 1,000,000 opper or copper
Chromium	0.045	0.018
Copper	0.195	0.103
Lead	0.015	0.013.
Nickel	0.197	0.130
' Zinc	0.150	0.062
TTO	0.066	0.035
Oil and grease(1)	2.060	1.236

(1) For alternate monitoring

Table 53
Cold Rolling Spent Lubricant

	PSES	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy cold rolled	
Chromium	0.166	0.068
Copper	0.720	0.379
Lead	0.056	0.049
Nickel	0.727	0.481
Zinc	0.553	0.231
TTO	0.246	0.128
Oil and grease(1)	7.580	4.548

(1) For alternate monitoring

Table 54
Drawing Spent Lubricant(1)

Drav	ing Spent Lubrica	nt(1)
	PSES	
1.40 10.70 10	Maximum for any 1 day	Maximum for monthly aver- age
Pollutant or pollutant property	mg/off-kg (pour off-pounds) of alloy drawn	nds per 1,000,000 of copper or copper
Chromium	0.037	0.015
Copper	0.161	0.085
Lead	0.012	0.011
Nickel	0.163	0.107
Zinc	0.124	0.051
TTO	0.055	0.028
Oil and grease(2)	1.700	1.020

<sup>(1)</sup> These standards are applicable only to those plants which actually discharge the drawing spent lubricant waste stream at the copper forming site. If these wastewaters are hauled off-site for disposal or are otherwise not discharged at the copper forming site, these standards are neither applicable nor allowable.

Table 55 Solution Heat Treatment

5014	mon neut rieumio.	
	PSES	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy heat treated	
Chromium	0.284	0.116
Copper	1.227	0.646
Lead	0.096	0.083
Nickel	1.240	0.820
Zinc	0.943	0.394
TTO	0.419	0.219
Oil and grease(1)	12.920	7.752

Table 56 Extrusion Heat Treatment

•	PSES	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy heat treated	
Chromium	0.00088	0.00036
Copper	0.0030	0.0020
Lead	0.00030	0.00026
Nickel	0.0030	0.0020
Zinc	0.0020	0.0010
TTO	0,0010	0.00068
Oil and grease(1)	0.040	0.024

(1) For alternate monitoring

Table 57 Annealing With Water

An	nearing with water	L
	PSES	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy annealed with water	
Chromium	0.545	0.223
Copper	2.356	1.240
Lead	0.186	0.161
Nickel	2.380	1.574
Zinc	1.810	0.756
TTO	0.806	0.421
Oil and grease(1)	24.800	14.880

(1) For alternate monitoring

Table 58
Annealing With Oil

	PSES	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy annealed with oil	
Copper	0	0
Lead	0	0
Nickel	0	0
Zinc	0	0
TTO	0	0
Oil and grease(1)	0	0

(1) For alternate monitoring

Table 59
Alkaline Cleaning Rinse

	Dana	*
	PŠES	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy alkaline cleaned	
Chromium	1.854	0.758
Copper	8.006	4.214
Lead	0.632	0.547
Nickel	8.090	5.351
Zinc	6.152	2.570
TTO	2.739	1.432
Oil and grease(1)	84.280	50,568

(1) For alternate monitoring

Table 60
Alkaline Cleaning Rinse For Forged Parts

	PSES	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy alkaline cleaned	
Chromium	5.562	2.275
Copper	24.019	12.642
Lead	1.896	1.643
Nickel	24.272	16.055
Zinc	18,457	7.711
TTO	8.217	4.298
Oil and grease(1)	252.840	151.704

Table 61 Alkaline Cleaning Bath

AIN	anne Cleaning Dau	
	PSES	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy alkaline cleaned	
Chromium	0.020	0.0084
Copper	0.088	0.046
Lead	0.0070	0.0060
Nickel	0.089	0.059
Zinç	0.068	0.028
TTO	0.030	0.015
Oil and grease(1)	0.93	0.56

Table 62 Pickling Rinse

	PSES	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy pickled	
Chromium	0.574	0.235
Copper	2.481	1.306
Lead	0.195	0.169
Nickel	2.507	1.658
Zinc	1.906	0.796
TTO	0.848	0.444
Oil and grease	26,120	15.672

(I) For alternate monitoring

Table 63
Pickling Rinse For Forged Parts

	PSES	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/offkg (pounds per 1,000,000 offpounds) of copper or copper alloy forged parts pickled	
Chromium	1.723	0.705
Copper	7.444	3.918
Lead	0.587	0.509
Nickel	7.522	4.975
Zinc	5.720	2.389
TTO	2.546	1,332
Oil and grease(1)	78.360	47,016

(1) For alternate monitoring

Table 64 Pickling Bath

	PSES	
1 1000	Maximum for any I day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy pickled	
Chromium	0.051	0.020
Copper	0.220	0.116
Lead	0.017	0.015
Nickel	0.222	0,147
Zinc	0.169	0.070
TTO	0.075	0.039
Oil and grease(1)	2.320	1,392

(1) For alternate monitoring

Table 65 Pickling Fume Scrubber

	PSES	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy pickled	
Chromium	0.275	0.112
Copper	1.189	0.626
Lead	0.093	0.081
Nickel	1.201	0.795
Zinc	0.913	0,381
TTO	0.406	0.212
Oil and grease(1)	12.520	7.512

(1) For alternate monitoring

# Table 66 Tumbling or Burnishing

	PSES	
1 11 2/11 1 1 11	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy tumbled or burnished	
Chromium	0.256	0.104
Copper	1.107	0.583
Lead	0.087	0.075
Nickel	1.119	0.740
Zinc	0.851	0.355
TTO	0.378	0.198
Oil and grease(1)	11.660	6,996

Table 67 Surface Coating

	PSES	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy surface coated	
Chromium	0.326	0.133
Copper	1.411	0.743
Lead	0.111	0.096
Nickel	1.426	0.943
Zinc	1.084	0.453
TTO	0.482	0.252
Oil and grease(1)	14.860	8.916

(1) For alternate monitoring

Table 68 Miscellaneous Waste Streams

	PSES	<del></del>
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pour off-pounds) of c alloy formed	nds per 1,000,000 copper or copper
Chromium	0.009	0.003
Copper	0.041	0.021
Lead	0.003	0.002
Nickel	0.041	0.027
Zinç	0.031	0.013
TTO	0.014	0.007
Oil and grease(1)	0.436	0.261

(1) For alternate monitoring
History: Cr. Register, May, 1989, No. 401, eff. 6-1-89.

NR 253.15 Pretreatment standards for new sources. Except as provided in s. NR 211.13, any existing [new] source subject to this subchapter which introduces pollutants into a POTW shall comply with ch. NR 211 and achieve the following PSNS:

Table 69 Hot Rolling Spent Lubricant

	PSNS	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollut- ant property	mg/off-kg (pounds pounds) of copper of rolled	per 1,000,000 off- or copper alloy hot
Chromium	0.038	0.015
Copper	0.131	0.062
Lead	0.010	0.0092
Nickel	0.056	0.038
Zinc	0.105	0.043
TTO	0.035	0.035
Oil and grease(1)	1.030	1.030

(I) For alternate monitoring

Table 70 Cold Rolling Spent Lubricant

	PSNS	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pour off-pounds) of c alloy cold rolled	
Chromium	0.140	0.056
Copper	0.485	0.231
Lead	0.037	0.034
Nickel	0.208	0.140
Zinc	0.386	0.159
TTO	0.128	0.128
Oil and grease(1)	3.790	3.790

(1) For alternate monitoring

Table 71

Drawing Spent Lubricam(1)			
D-110-1100-1	PSNS		
	Maximum for any 1 day	Maximum for monthly average	
Pollutant or pollutant property	nig/off-kg (pound off-pounds) of co alloy drawn	s per 1,000,000 pper or copper	
Chromium	0.031	0.012	
Copper	0.108	0.051	
Lead	0.0085	0.0076	
Nickel	0.046	0.031	
Zinc	0.086	0.035	
TTO	0.028	0.028	
Oil and grease(2)	0.850	0.850	

(I) These standards are applicable only to those plants which actually discharge the drawing spent lubricant waste stream at the copper forming site. If these wastewaters are hauled off-site for disposal or are otherwise not discharged at the copper forming site, these standards are neither applicable nor allowable.

Table 72 Solution Heat Treatment

3010	aton Heat Treatmen	nt .
	PSNS	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pour off-pounds) of c alloy heat treated	
Chromium	0.239	0.096
Copper	0.826	0.394
Lead	0.064	0.058
Nickel	0.355	0.239
Zinc	0.658	0.271
TTO	0.219	0.219
Oil and grease(1)	6.460	6.460

Table 73
Extrusion Heat Treatment

	PSNS	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pour off-pounds) of c alloy heat treate	nds per 1,000,000 copper or copper d
Chromium	0.00074	0.00030
Copper	0.0020	0.0010
Lead	0.00020	0.00018
Nickel	0.0010	0.00074
Zinc	0.0020	0.00084
TTO	0.00068	0.00068
Oil and grease(1)	0.020	0.020

(1) For alternate monitoring

Table 74 Annealing With Water

	PSNS	
	Maximum for	Maximum for
	any 1 day	monthly average
Pollutant or pollutant property	mg/off–kg (pour off–pounds) of c alloy annealed w	
Chromium	0.458	0.186
Copper	1.587	0.756
Lead	0.124	0.111
Nickel	0.682	0.458
Zinc	1.264	0.520
TTO	0.421	0.421
Oil and grease <sup>(1)</sup>	12.400	12.400

(1) For alternate monitoring

Table 75 Annealing With Oil

	PSNS	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pour off-pounds) of c alloy annealed w	
Chromium	0	0
Copper	0	0
Lead	0	0
Nickel	0	0
Zinc	0	0
TTO	0	0
Oil and grease <sup>(1)</sup>	0	0

(1) For alternate monitoring

Table 76
Alkaline Cleaning Rinse

	PSNS	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pour off-pounds) of c alloy alkaline cle	
Chromium	1,559	0.632
Copper	5.393	2,570
Lead	0.421	0.379
Nickel	2,317	1,559
Zinc	4.298	1.769
TTO	1.432	1,432
Oil and grease <sup>(1)</sup>	42.140	42,140

(1) For alternate monitoring

Table 77
Alkaline Cleaning Rinse For Forged Parts

Maximum for any 1 day	Maximum for monthly average
mg/off_kg (nounds	1 000 000
mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy alkaline cleaned	
4.677	1.896
16.181	7.711
1.264	1.137
6.953	4.677
12.894	5.309
4.298	4.298
126.420	126.420
	off-pounds) of cop alloy alkaline clear 4.677 16.181 1.264 6.953 12.894 4.298

Table 78	
Alkaline Cleaning Bati	h

	PSNS	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/offkg (pour offpounds) of c alloy alkaline cle	
Chromium	0.017	0.0070
Copper	0.059	0.028
Lead	0.0046	0.0042
Nickel	0.025	0.017
Zinc	0.047	0.019
TTO	0.015	0.015
Oil and grease(1)	0.46	0.46

Table 79 Pickling Rinse

	PSNS	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pour off-pounds) of c alloy pickled	nds per 1,000,000 copper or copper
Chromium	0.216	0.087
Copper	0.748	0.356
Lead	0.058	0.052
Nickel	0.321	0.216
Zinc	0.596	0.245
TTO	0.198	0.198
Oil and grease(1)	5.850	5.850

(1) For alternate monitoring

Table 80
Pickling Rinse For Forged Parts

	PSNS	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pour off-pounds) of c alloy forged part	
Chromium	0.649	0.263
Copper	2.246	1.070
Lead	0.175	0.157
Nickel	0.965	0.649
Zinc	1.790	0.737
TTO	0.596	0.596
Oil and grease <sup>(1)</sup>	17.550	17.550

(1) For alternate monitoring

Table 81 Pickling Bath

	PSNS	
1 100	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy pickled	
Chromium	0.042	0.017
Copper	0.148	0.070
Lead	0.011	0.010
Nickel	0.063	0.042
Zinç	0.118	0.048
TTO	0.039	0.039
Oil and grease(1)	1.160	1.160

(1) For alternate monitoring

Table 82 Pickling Fume Scrubber

·.	PSNS	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000) off-pounds) of copper or copper alloy pickled	
Chromium	0.231	0.093
Copper	0.801	0.381
Lead	0.062	0.056
Nickel	0.344	0.231
Zinc	0.638	0.262
TTO	0.212	0.212
Oil and grease(1)	6.260	6.260

(1) For alternate monitoring

Table 83
Tumbling or Burnishing

	PSNS	
	Maximum for any 1 day	Maximum for monthly average
Poliutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy tumbled or burnished	
Chromium	0.215	0.087
Copper	0.746	0.355
Lead	0.058	0.052
Nickel	0.320	0.215
Zinc	0.594	0.244
TTO .	0.198	0.198
Oil and grease(1)	5.830	5.830

Table 84 Surface Coating

	ourrace coating	
	PSNS	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy surface coated	
Chromium	0.274	0.111
Copper	0.951	0.453
Lead	0.074	0.066
Nickel	0.408	0.274
Zinc	0.757	0.312
TTO	0.252	0,252
Oil and grease <sup>(1)</sup>	7.430	7.430

<sup>(1)</sup> For alternate monitoring

Table 85 Miscellaneous Waste Streams

	PSNS	
, V.	Maximum for any 1 day	Maximum for monthly average
Poliutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy formed	
Chromium	0.008	0.003
Copper	0.027	0.013
Lead	0.0021	0.0019
Nickel	0.011	0.008
Zinc	0.022	0.009
TTO	0.007	0.007
Oil and grease <sup>(1)</sup>	0.218	0.218

Note: The Wisconsin administrative code corresponds to the code of federal regulations as cross referenced in the following table:

State Code	Corresponding Federal Regulation	
s. NR 205.03	40 CFR 401.11	
s. NR 205.04	40 CFR 401.11	
ch, NR 211	40 CFR Part 403	
s. NR 211.03	40 CFR 403.03	
s. NR 211.13	40 CFR 403.7	
s. NR 211.14	40 CFR 403.13	
ch. NR 253	40 CFR Part 468	
ch. NR 256	40 CFR Part 464	

<sup>(1)</sup> For alternate monitoring
History: Cr. Register, May, 1989, No. 401, eff. 6-1-89.