2

LRB-2529/2 MGG:nwn:rs

2009 ASSEMBLY BILL 356

July 28, 2009 – Introduced by Representatives Hraychuck, Brooks, Roys, Townsend, Jorgensen, Radcliffe, Petrowski, Hubler, Gunderson, Tauchen, Murtha, Ballweg, Ripp, Suder and Spanbauer, cosponsored by Senators Holperin, Taylor, Vinehout, Harsdorf, A. Lasee and Grothman. Referred to Committee on Tourism, Recreation and State Properties.

1 AN ACT to amend 340.01 (2g); and to create 340.01 (27g) of the statutes;

relating to: modifying the definition of all-terrain vehicle.

Analysis by the Legislative Reference Bureau

Current law defines an "all-terrain vehicle" (ATV) as an engine-driven device with a width of not more than 48 inches and a net weight of 900 pounds or less that is equipped with a seat designed to be straddled by the vehicle operator and that is designed to travel on at least three low-pressure tires. Under current law, a low-pressure tire is a tire that has a minimum width of six inches, that is designed to be mounted on a rim with a maximum diameter of 12 inches, and that is designed to be inflated with an operating pressure not to exceed six pounds per square inch.

This bill increases the maximum width of an ATV to 50 inches. The bill specifies that the width of an ATV must be 50 inches or less at the time of manufacture and that it be designed by the manufacturer to travel on three or more low–pressure tires in order to meet the definition. As to the requirements for a low–pressure tire, the bill eliminates the requirement for the size of the rim and increases the the maximum operating pressure for a low–pressure tire to ten pounds per square inch.

For further information see the *state* fiscal estimate, which will be printed as an appendix to this bill.

The people of the state of Wisconsin, represented in senate and assembly, do enact as follows:

ASSEMBLY BILL 356

1

2

3

4

5

6

7

8

9

10

11

12

13

SECTION 1. 340.01 (2g) of the statutes is amended to read:

340.01 **(2g)** "All-terrain vehicle" means an engine-driven device which has a net weight of 900 pounds or less, which has is originally manufactured with a width of 48 50 inches or less, which is equipped with a seat designed to be straddled by the operator and which is designed by the manufacturer to travel on 3 or more low-pressure tires. A low-pressure tire is a tire which has a minimum width of 6 inches, which is designed to be mounted on a rim with a maximum diameter of 12 inches and which is designed to be inflated with an operating pressure not to exceed 6 pounds per square inch as recommended by the manufacturer.

SECTION 2. 340.01 (27g) of the statutes is created to read:

340.01 **(27g)** "Low-pressure tire" means a tire that has a minimum width of 6 inches and that is designed to be inflated with an operating pressure not to exceed 10 pounds per square inch as recommended by the manufacturer.

14 (END)