466

File De 30-1957 9 am.

STATE OF WISCONSIN) S: BOARD OF HEALTH

TO ALL TO WHOM THESE PRESENTS SHALL COME, GREETINGS:

I, Carl N. Neupert, M. D., Executive Secretary of the Wisconsin State Board of Health and custodian of the official records of said Board, do hereby certify that the annexed rules and regulations (H 66.01 to H 66.06, inclusive, of the Wisconsin Administrative Code) relating to Servicing Septic Tanks, Seepage Pits, Grease Traps or Privies were duly approved and adopted by this Board on October 25, 1957 pursuant to authority vested in said Board by Sec. 146.20, Wis. Stats.

I further certify that said copy has been compared by me with the original on file in this department, and that the same is a true copy thereof, and of the whole of such original.

The attached rules shall take effect on the first day of the month following publication in the Wisconsin Administrative Register, as provided in Sec. 227.026 (1), Wis. Stats., subject to approval under the provisions of Sec. 14.225.

hereunto set my hand and affixed the official seal of the department at the State Office Building in the City of Madison, this

IN TESTIMONY WHEREOF, I have

the City of Madison, this 28th day of October, 1957.

Seal

Executive Secretary M. D.

## CHAPTER H 66

SERVICING SEPTIC TANKS, SEEPAGE PITS, GREASE TRAPS OR PRIVIES

H 66.01 Applicability. These rules relating to the servicing of septic tanks, seepage pits, grease traps or privies shall be applicable to any person who engages in the servicing business and to any person servicing sewage treatment and disposal units on real estate owned or leased by him in keeping with section 146.20, Wisconsin Statutes.

H 66.02 Definitions. For the purpose of these rules:

- (1) Board means the state board of health.
- (2) Person means any individual, partnership, association and body politic or corporate.
- (3) Licensee means any person, including any licensed plumber, engaged in the business of servicing septic tanks, seepage pits, grease traps or privies who has met the requirements of law and rules of the board.
- (4) Servicing means the cleaning, removing and disposing of scum, liquid, sludge or other wastes from a septic tank, seepage pit, grease trap or privy.
- H 66.03 General requirements. (1) Hereafter any person proposing to engage in the business of servicing sewage disposal units shall have his equipment inspected by and obtain a license from the board before commencing operations. A person engaged in the business prior to July 1, 1957 shall be licensed upon application to the

board without pre-inspection. Any licensee shall permit his equipment to be inspected upon request and at such time and place as may be designated by the board.

- (2) Every licensee shall have sufficient knowledge of sanitation and of the principles underlying the operation of septic tanks, seepage pits, grease traps and privies to safeguard public health and welfare. In the case of a new licensee or in case of doubt as to qualifications of an existing licensee the board may require applicants, initially or upon renewal, to take an oral or written examination to demonstrate that they qualify for licensure.
- (3) All work shall be performed in a proper and sanitary manner to the benefit of the property owners and the public at large. The property served shall be left in a sanitary condition.
- (4) Every licensee or every person servicing sewage disposal units for himself shall conform to the requirements of H 62.20 (1) (f), Wisconsin Administrative Code, in the disposal of wastes. Disposal sites selected by local officials for disposal of wastes removed from sewage treatment and soil absorption units shall be located and operated so as to prevent stream or lake pollution and nuisances. In spreading of wastes over lands, as permitted in H 62.20 (1) (f), the rate of application shall not exceed thirty gallons per each 100 square feet of area.
- (5) Pumping or dumping the contents of the serviced unit on the premises or on the highway when transporting the contents for dumping shall be prohibited. Any accidental spillage on the ground on the premises serviced or on highways shall be cleaned up and the area be disinfected so as to render it harmless to humans and animals.

- (6) When in use, the vehicle, implements and containers shall be operated in such manner as not to become a health hazard or a nuisance. When in storage all vehicles, tanks, containers, hoses, pipes, pumps and appurtenances shall be covered, capped, sealed or so protected as not to cause an odor nuisance, permit the breeding of flies, attract rodents or become objectionable to any person.
- (7) The filling of servicing tanks or containers with water derived directly from lakes or streams is not permitted whenever other sources are available. If water is taken from a stream or lake for flushing purposes, the water shall be disposed of in the same manner as the wastes. Discharge of wastes or flushing water to a stream or lake shall be cause for immediate suspension of the license.
- H 66.04 <u>Vehicles</u>, <u>implements and containers</u>. (1) The vehicles and implements used in the servicing business shall be used for no other purpose except operations of a similar nature, namely, the hauling of waste materials. However, use of the vehicles for fire protection service if flushed, decontaminated and filled with clean water will be allowed.
- (2) Each tank shall be strong enough for all conditions of operation, be leak proof, and designed to be kept tightly closed to prevent spillage of contents or escape of odors while in transit or storage. Tanks should be constructed of steel or other suitable metal and be mounted on a truck chassis.
- (3) Licensed plumbers engaged in the business of servicing sewage disposal units shall paint their name and type and number of plumbing license on each side of each vehicle used in the business

in the manner set forth in subsection 146.20 (3) (c). The capacity of the tank in gallons shall be painted in a contrasting color on the rear end of any vehicle used in the business by any licensee in letters and numbers at least 2 inches high. The sides and rear end of the tanks should preferably be used for the identification and capacity signs.

- (4) All portable containers used in the servicing of sewage disposal units shall be constructed of metal, be water-tight, and be equipped with tight fitting lids. Transportation of wastes in portable containers shall not be allowed by a licensee without board approval of the equipment to be used, such approval to be only for one year periods.
- (5) Hoses and piping shall be mounted and stored so as to prevent leakage in transit. Ends of hoses and pipes shall be connected or be fitted with caps when not in use.
- (6) Discharge valves on tanks shall be water-tight and shall be located and constructed so as to permit unobstructed discharge into the place of disposal.
- (7) Pumps shall be adequate for the required service and preferably of the diaphragm type. The installation shall be designed to prevent backflow or leakage. Connections shall be provided with caps or seals.
- (8) Facilities for washing the vehicles, tanks, implements, tools, etc., shall be available and of such design as to prevent an odor nuisance, breeding of flies, attraction of rodents or other objectionable conditions.
- (9) All vehicles and all equipment shall be maintained in good condition at all times.

- H 66.05 <u>Inspection</u>. (1) When a vehicle is to be inspected the licensee or prospective licensee shall have the tank one-third full of water. During the inspection, the operator shall insert the suction hose into an opening in the tank and recirculate the water through the pump and back into the tank, however, if this is impractical, a suitable alternate means of testing shall be provided. At this time, the pumping equipment, hoses, hose connections and tanks shall be checked for adequacy and for leaks. Discharge valves shall be checked for leaks and as to location.
- (2) All portable receptacles shall be present at the time of inspection. The licensee shall fill several of the portable receptacles with water upon request to demonstrate that they are water-tight. The receptacles shall be clean.
- H 66.06 <u>License renewal denial</u>. Equipment and operating procedures shall be inspected before the end of each license year. The renewal of license shall be denied if the equipment is found to be unsatisfactory or the operations are faulty and not in accord with the law or rules.



## The State of Misconsin

BOARD OF HEALTH

STATE OFFICE BUILDING

IN REPLY PLEASE REFER TO:

MADISON 2

October 28, 1957

Mr. James J. Burke Revisor of Statutes 321 Northeast, State Capitol Madison 2, Wisconsin

Dear Mr. Burke:

As provided in Section 227.023, Wisconsin Statutes, I hereby submit a certified copy of Chapter H 66, Servicing Septic Tanks, Seepage Pits, Grease Traps or Privies, of the Wisconsin Administrative Code as adopted by the Wisconsin State Board of Health on October 25, 1957, for publication in the Wisconsin Administrative Register. It is hoped that the rules can be published in the November issue of the Register so the effective date may be December 1, 1957.

Copies of these rules are also being submitted to the Governor as required by Section 14.225 and to the Secretary of State as required by Section 227.023, Wisconsin Statutes.

Respectfully submitted,

Carl N. Neupert, M. D.

Executive Secretary

dр

Enclosures 2