

(5) Where such exhaust pipe passes through any combustible wall, partition, ceiling or floor, a clearance of not less than 2 inches shall be provided around the pipe, and the exposed woodwork shall be protected by metal, or such pipe may run through a ventilated double metal thimble, having an air space of not less than 1 inch between the inner and outer rings of such thimble. Such exhaust pipes shall not be closer than 6 inches to any unprotected combustible wall, partition or woodwork.

**Ind 65.08 Glue pots and soldering furnaces.** (1) All glue pots and soldering furnaces, when in use, shall rest on an incombustible base, and there shall be no unprotected woodwork within 12 inches from the same.

(2) Wooden work benches may be used as a base for the same, only when covered with metal over  $\frac{1}{8}$  inch sheet asbestos, to a distance of not less than 18 inches beyond the pot or furnace on all sides.

**Ind 65.09 Calcium carbide.** Calcium carbide shall be stored in covered, water-tight metal cans, outside of the main building in an isolated, well-ventilated building, under lock and key, and such carbide cans shall be raised above the floor not less than 2 inches to permit the free circulation of air. Not more than one such can shall be opened at one time, or until such can is used up.

**Ind 65.10 Smokehouses.** (1) Every building used for smoking meat and located within a distance of 25 feet from any other buildings, shall have walls of brick, stone or concrete, not less than 8 inches thick, an incombustible floor and roof, and an iron door overlapping the door opening at least one inch at the top and on both sides with hinges and hasp embedded in the wall, and shall have a brick or metal vent or smoke flue to the outside, except as follows:

(a) Small smokehouses for retail meat markets may be located in the basement or on the main floor of the building, if constructed of 8 inch brick wall or its equivalent, with roof of brick arch, tile or concrete, the flue to have 6 inch brick walls, the foundation and floor to be of incombustible materials, not less than 3 inches thick. If such smokehouse is placed on any wooden floor, then the smokehouse floor shall be built of incombustible material at least 5 inches thick, and shall have air spaces running horizontally through the same. The floor under the same shall be supported to safely carry such additional load.

**Ind 65.11 Picker rooms.** (1) Cotton, moss, hair, excelsior and other pickers and shredders shall be housed and operated in an isolated building, or in a room with fire-resistive ceiling, walls and floor, with self-closing, metal-clad doors.

(2) A window or other outside ventilation shall be provided.

(3) Such rooms shall be thoroughly cleaned up at the close of each day's work.

(4) Where steam is available, a live steam jet shall be installed in each such room, and an approved chemical fire extinguisher shall be kept on the outside of the door leading to such room.

*Cr 65.12*