

Chapter NR 275

PAVING AND ROOFING MATERIALS

NR 275.01	Purpose.	NR 275.06	Application of effluent limitations and standards.
NR 275.02	Applicability.	NR 275.10	Effluent limitations, best practicable treatment.
NR 275.03	Definitions.	NR 275.11	Effluent limitations, best available treatment.
NR 275.04	Compliance with effluent limitations and standards.	NR 275.12	Standards of performance (SOP).
NR 275.05	Modification of effluent limitations.	NR 275.13	Pretreatment standards.

NR 275.01 Purpose. The purpose of this chapter is to establish effluent limitations, standards of performance, and pretreatment standards for discharges of process wastes from the paving and roofing materials (tars and asphalts) category of point sources and subcategories thereof.

Note: The authority for promulgation of this chapter is set forth in ch. NR 205.

History: Cr. Register, June, 1977, No. 258, eff. 7-1-77.

NR 275.02 Applicability. The effluent limitations, standards of performance, pretreatment standards, and other provisions in this chapter are applicable to pollutants or pollutant properties in discharges of process waste resulting from manufacture in any of the following subcategories.

- (1) Asphalt paving and roofing emulsion.
- (2) Asphalt concrete.
- (3) Asphalt roofing.
- (4) Printed asphalt felt and linoleum.

History: Cr. Register, June, 1977, No. 258, eff. 7-1-77.

NR 275.03 Definitions. Definitions of terms and meanings of abbreviations used in this chapter are set forth in ch. NR 205 except that for subcategory (1) only "process waste" means also runoff from material storage areas.

History: Cr. Register, June, 1977, No. 258, eff. 7-1-77.

NR 275.04 Compliance with effluent limitations and standards. Discharge of pollutants from facilities subject to the provisions of this chapter may not exceed, as appropriate:

- (1) By July 1, 1977 effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available;
- (2) By July 1, 1983 effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable;
- (3) Pretreatment standards for discharges to publicly owned treatment works;
- (4) Standards of performance for new sources.

History: Cr. Register, June, 1977, No. 258, eff. 7-1-77; r. and recr. Register, August, 1983, No. 332, eff. 9-1-83.

NR 275.05 Modification of effluent limitations.

(1) Effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available may be modified in accordance with this section.

(2) An individual discharger or other interested person may submit evidence to the department that factors relating to the equipment or facilities involved, the process applied, or other such factors related to such discharger are fundamentally different from the factors considered in the establishment of the effluent limitations. On the basis of such evidence or other available information the department will make a written determination that such factors are or are not fundamentally different for that facility compared to those specified in the applicable sections of the EPA

development document identified in sub. (3). If such fundamentally different factors are found to exist, the department shall establish for the discharge effluent limitations in the WPDES permit either more or less stringent than the limitations in this chapter, to the extent dictated by such fundamentally different factors. Such limitations must be approved by EPA which may approve, disapprove, or specify other limitations.

(3) The EPA development document for effluent limitations guidelines and new source performance standards, identified by category title, by EPA document number and by publication date, applicable in accordance with sub. (2) is:

Paving and Roofing Materials, EPA 440/1-75/049-a, July 1975

(4) Copies of the development document identified in sub. (3) are available for inspection at the office of the department of natural resources, the secretary of state's office, and the office of the legislative reference bureau, and may be obtained for personal use from the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20460.

History: Cr. Register, June, 1977, No. 258, eff. 7-1-77; correction made in (4) under s. 13.92 (4) (b) 6., Stats., Register April 2013 No. 688.

NR 275.06 Application of effluent limitations and standards. (1) The effluent limitations and standards set forth in this chapter shall be used in accordance with this section to establish the quantity or quality of pollutants or pollutant properties which may be discharged by a point source subject to the provisions of this chapter, except as:

(a) They may be modified in accordance with s. NR 275.05,

(b) They may be superseded by more stringent limitations and standards necessary to achieve water quality standards or meet other legal requirements, or

(c) They may be supplemented or superseded by standards or prohibitions for toxic pollutants or by additional limitations for other pollutants required to achieve water quality.

(2) The production basis for application of the limitations and standards set forth in this chapter shall be the daily average of a maximum month in each subcategory subject to the provisions of this chapter.

History: Cr. Register, June, 1977, No. 258, eff. 7-1-77.

NR 275.10 Effluent limitations, best practicable treatment. The following effluent limitations for all or specific subcategories establish, except as provided in s. NR 275.05, the quantity or quality of pollutants or pollutant properties which may be discharged by a facility subject to the provisions of this chapter after application to process wastes of the best practicable control technology currently available (BPT).

(1) There shall be no discharge resulting from manufacture in subcategory (2).

(2) The pH of all discharges shall be within the range of 6.0 to 9.0.

(3) Discharges resulting from manufacture in subcategory (1) shall be limited to runoff from material storage areas as set forth in the BPT column of table 1 in lbs/1000 gallons of runoff.

(4) The 30-day average and daily maximum limitations for suspended solids for subcategories (3) and (4) are the BPT limitations set forth in table 2 in lbs/1000 lbs, or kg/1000 kg, of product.

History: Cr. Register, June, 1977, No. 258, eff. 7-1-77.

NR 275.11 Effluent limitations, best available treatment. The following effluent limitations for all or specific subcategories establish the quantity or quality of pollutants or pollutant properties which may be discharged by a facility subject to the provisions of this chapter after application to process wastes of the best available technology economically achievable (BAT).

(1) There shall be no discharge resulting from manufacture in subcategory (2).

(2) The pH of all discharges shall be within the range of 6.0 to 9.0.

(3) Discharges resulting from manufacture in subcategory (1) shall be limited to runoff from material storage areas as set forth in the BAT column of table 1 in lbs/1000 gallons of runoff.

(4) The 30-day average and daily maximum limitations for suspended solids for subcategories (3) and (4) are the BAT limitations set forth in table 2 in lbs/1000 lbs, or kg/1000 kg, of product.

History: Cr. Register, June, 1977, No. 258, eff. 7-1-77.

NR 275.12 Standards of performance (SOP). The following effluent limitations for all or specific subcategories establish the quantity or quality of pollutants or pollutant properties which may be discharged by a facility which is a new source subject to the provisions of this chapter.

(1) There shall be no discharge resulting from manufacture in subcategory (2).

(2) The pH of all discharges shall be within the range of 6.0 to 9.0.

(3) Discharges resulting from manufacture in subcategory (1) shall be limited to runoff from material storage areas as set forth in the SOP column of table 1 in lbs/1000 gallons of runoff.

(4) The 30-day average and daily maximum limitations for suspended solids for subcategories (3) and (4) are the SOP limitations set forth in table 2 in lbs/1000 lbs, or kg/1000 kg, of product.

History: Cr. Register, June, 1977, No. 258, eff. 7-1-77.

NR 275.13 Pretreatment standards. The pretreatment standards for discharges to publicly owned treatment works from sources subject to the provisions of this chapter shall be as set forth in ch. NR 211.

History: Cr. Register, June, 1977, No. 258, eff. 7-1-77; r. and recr. Register, August, 1983, No. 332, eff. 9-1-83.

Table 1
Runoff Effluent Limitations

	BPT	BAT	SOP
Suspended solids			
30 day average		0.125	0.125
daily maximum		0.188	0.188
Oil and grease			
30 day average	0.125	0.083	0.083
daily maximum	0.167	0.125	0.125

Table 2
Effluent Limitations for Suspended Solids

	Subcategory (3)		Subcategory (4)	
	30 day ave.	Daily max.	30 day ave.	Daily max.
BPT limitations	0.038	0.056	0.025	0.038
BAT limitations	0.019	0.028	0.013	0.019
SOP limitations	0.019	0.028	0.013	0.019