Chapter NR 262

PORCELAIN ENAMELING

NR 262.01	Purpose.		tainable by the application of the best available technology eco-
NR 262.015	Applicability.		nomically achievable.
NR 262.02	General definitions.	NR 262.23	New source performance standards.
NR 262.03	Monitoring and reporting requirements.	NR 262.24	Pretreatment standards for existing sources.
NR 262.04	Compliance date for pretreatment standards for existing sources	NR 262.25	Pretreatment standards for new sources.
NR 262.10	(PSES). Applicability; description of the steel basis material subcategory.	NR 262.30	Applicability; description of the aluminum basis material subcategory.
NR 262.11	Effluent limitations representing the degree of effluent reduction at- tainable by the application of the best practicable control technol- ogy currently available.	NR 262.31	Effluent limitations representing the degree of effluent reduction at- tainable by the application of the best practicable control technol- ogy currently available.
NR 262.12	Effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.	NR 262.32	Effluent limitations representing the degree of effluent reduction at- tainable by the application of the best available technology eco-
NR 262.13	New source performance standards.	ND 262.22	nomically achievable.
NR 262.14	Pretreatment standards for existing sources.	NR 262.33	New source performance standards.
NR 262.15	Pretreatment standards for new sources.	NR 262.34	Pretreatment standards for existing sources.
NR 262.20	Applicability; description of the cast iron basis material subcategory.	NR 262.35	Pretreatment standards for new sources.
NR 262.21	Effluent limitations representing the degree of effluent reduction at-	NR 262.40	Applicability; description of the copper basis material subcategory.
	tainable by the application of the best practicable control technol-	NR 262.43	New source performance standards.
	ogy currently available.	NR 262.45	Pretreatment standards for new sources.
NR 262.22	Effluent limitations representing the degree of effluent reduction at-	NR 262.50	Cross-references.

NR 262.01 Purpose. The purpose of this chapter is to establish effluent limitations, standards of performance, and pretreatment standards for discharges of process wastes from the porcelain enameling category of point sources and its subcategories.

History: Cr. Register, October, 1986, No. 370, eff. 11-1-86.

1

- **NR 262.015 Applicability. (1)** Except as provided in subs. (2) and (3), the provisions of this chapter apply to any porcelain enameling facility which discharges pollutants to waters of the state or introduces pollutants into a publicly owned treatment works.
- (2) Any existing porcelain enameling facility which prepares or coats less than 1600 m²/day and which introduces less than 60,000 l/day of wastewater into a publicly owned treatment works is not controlled by the pretreatment standards for existing sources established by this rule. Such facilities shall comply with the provisions of 40 CFR Part 403.
- (3) This chapter does not apply to the porcelain enameling on precious metal basis material.
- **(4)** When wastewaters from coating cast iron are co-treated with wastewaters from coating steel, the limitations for coating steel contained in s. NR 262.11 may be applied to the entire wastestream.

History: Cr. Register, October, 1986, No. 370, eff. 11-1-86.

- **NR 262.02 General definitions.** In addition to the definitions set forth in 40 CFR Part 401, the following definitions apply to this chapter:
- (1) "Area coated" means the area of basis material covered by each coating of enamel.
- (2) "Area processed" means the total basis material area exposed to processing solutions.
- **(3)** "Basis material" means the metal part or base onto which porcelain enamel is applied.
- **(4)** "Coating operations" means all of the operations associated with preparation and application of the vitreous coating. Usually this includes ballmilling, slip transport, application of

slip to the work pieces, cleaning and recovery of faulty parts, and firing (fusing) of the enamel coat.

- **(5)** "Control authority" means the publicly owned treatment works if it has an approved pretreatment program; in the absence of such a program, the state.
- **(6)** "Existing source" means any source that is not a new source.
- (7) "Metal preparation" means any and all of the metal processing steps preparatory to applying the enamel slip. Usually this includes cleaning, pickling and applying a nickel flash or chemical coating.
- **(8)** "New source," as defined for PSES and PSNS, means any building, structure, facility, or installation from which there is or may be a discharge of pollutants, the construction of which commenced after April 27, 1984.
- **(9)** "New source," as defined for BPT, BAT, BCT, and NSPS, means any point source the construction of which commenced after October 21, 1985.
- (10) "Porcelain enameling" means the entire process of applying a fused vitreous enamel coating to a metal basis material. Usually this includes metal preparation and coating operations.
- (11) "Precious metal" means gold, silver, or platinum group metals and the principal alloys of those metals.

History: Cr. Register, October, 1986, No. 370, eff. 11-1-86.

NR 262.03 Monitoring and reporting requirements.

- (1) Periodic analyses for chromium as may be required under 40 CFR Part 122 or 403 is not required when both of the following conditions are met:
- (a) The first wastewater sample of each calendar year has been analyzed and found to contain less than $0.08\ \text{mg/l}$ chromium.
- (b) The owner or operator of the porcelain enameling facility certifies in writing to the control authority that chromium is not contained in the raw materials or process chemicals of that facility and will not be used in the facility.
 - (2) The "monthly average" regulatory values shall be the ba-

sis for the monthly average discharge in direct discharge permits and for pretreatment standards. Compliance with the monthly discharge limit is required regardless of the number of samples analyzed and averaged.

History: Cr. Register, October, 1986, No. 370, eff. 11-1-86.

NR 262.04 Compliance date for pretreatment standards for existing sources (PSES). The compliance date for pretreatment standards for existing sources is November 25, 1985.

History: Cr. Register, October, 1986, No. 370, eff. 11-1-86.

NR 262.10 Applicability; description of the steel basis material subcategory. This subcategory applies to discharges to waters of the state and introduction of pollutants into publicly owned treatment works from porcelain enameling on steel basis materials.

History: Cr. Register, October, 1986, No. 370, eff. 11-1-86.

NR 262.11 Effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available. Except as provided in 40 CFR 125.30 to 125.32, any existing point source subject to this subcategory shall achieve the following effluent limitations for metal preparation operations and for coating operations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

	BPT effluent limitations					
	Maximum for monthly					
	Maximum for any 1 day average					
Pollutant or						
pollutant	Metal	Coating	Metal	Coating		
property	preparation	operation	preparation	operation		
	Metric un	its-mg/m ² of a	area processed	or coated		
Chromium	16.82	3.41	6.81	1.38		
Lead	6.01	1.21	5.21	1.06		
Nickel	56.46	11.43	40.05	8.11		
Zinc	53.26	10.78	22.43	4.54		
Aluminum	182.2	36.87	74.47	15.07		
Iron	112.12	22.69	56.06	11.34		
Oil and grease.	800.84	162.1	480.51	97.23		
TSS	1642.0	332.2	800.9	162.0		
pH	(1)	(1)	(1)	(1)		
	English units pounds per 1 million ft ² of area					
	processed or coated					
Chromium	3.45	0.07	1.4	0.29		
Lead	1.23	0.25	1.07	0.22		
Nickel	11.57	2.34	8.2	1.66		
Zinc	10.91	2.21	4.6	0.93		
Aluminum	37.32	7.85	15.26	3.09		
Iron	22.96	4.65	11.48	2.32		
Oil and grease.	164.03	33.19	98.42	19.92		
TSS	337.0	68.1	164.0	33.2		
pH	(1)	(1)	(1)	(1)		
¹ Within the range 7.5 to 10.0.						

History: Cr. Register, October, 1986, No. 370, eff. 11-1-86.

NR 262.12 Effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable. Except as provided in 40 CFR 125.30 to 125.32 any existing point source subject to this subcategory shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable:

	BAT effluent limitations					
		Maximum for monthly				
	Maximum f	or any 1 day	aver	rage		
Pollutant or						
pollutant	Metal	Coating	Metal	Coating		
property	preparation	operation	preparation	operation		
	Metric un	its-mg/m ² of a	area processed	or coated		
Chromium	16.82	0.53	6.81	0.22		
Lead	6.01	0.19	5.21	0.16		
Nickel	56.5	1.78	40.05	1.26		
Zinc	53.3	1.68	22.43	0.71		
Aluminum	182.0	5.74	74.48	2.35		
Iron	112.12	3.53	56.06	1.77		
	English un	its-pounds per	· 1 million ft ² c	of area pro-		
		cessed o	or coated			
Chromium	3.45	0.11	1.4	0.05		
Lead	1.23	0.04	1.07	0.03		
Nickel	11.57	0.37	8.2	0.26		
Zinc	10.91	0.35	4.6	0.15		
Aluminum	37.32	1.18	15.26	0.48		
Iron	22.96	0.72	11.48	0.36		

History: Cr. Register, October, 1986, No. 370, eff. 11-1-86.

NR 262.13 New source performance standards.

Any new source subject to this subcategory shall achieve the following new source performance standards:

	NSPS				
	Maximum for monthly				
	Maximum f	or any 1 day	avei	rage	
Pollutant or					
pollutant	Metal	Coating	Metal	Coating	
property	preparation	operation	preparation	operation	
	Metric un	its-mg/m ² of a	area processed	or coated	
Chromium	3.7	0.47	1.5	0.19	
Lead	1.0	0.13	0.9	0.11	
Nickel	12.0	1.51	6.3	0.79	
Zinc	10.2	1.29	4.2	0.53	
Aluminum	30.3	3.82	12.4	1.56	
Iron	28.0	3.53	14.0	1.77	
Oil and grease	100.0	12.6	100.0	12.6	
TSS	150.0	18.91	120.0	15.12	
pH	(1)	(1)	(1)	(1)	
	English un		1 million ft ²	of area pro-	
		cessed o	or coated		
Chromium	0.76	0.1	0.31	0.04	
Lead	0.21	0.03	0.19	0.03	
Nickel	2.46	0.31	1.29	0.16	
Zinc	2.09	0.27	0.86	0.11	
Aluminum	6.21	0.78	2.54	0.32	
Iron	5.74	0.72	2.87	0.36	
Oil and grease	20.48	2.58	20.48	2.58	
TSS	30.72	3.87	24.58	3.1	
pH	(1)	(1)	(1)	(1)	

¹Within the range 7.5 to 10.0.

History: Cr. Register, October, 1986, No. 370, eff. 11-1-86.

NR 262.14 Pretreatment standards for existing sources. (1) Except as provided in 40 CFR 403.7 and 403.13, any existing source subject to this subcategory which introduces pollutants into a publicly owned treatment works shall comply with 40 CFR Part 403 and achieve the following pretreatment standards for existing sources.

DEPARTMENT OF NATURAL RESOURCES

	PSES				
			Maximum i	for monthly	
	Maximum fo	or any 1 day	avei	rage	
Pollutant or pollutant property	Metal preparation	Coating operation	Metal preparation	Coating operation	
		Milligrams p	er liter (mg/l)		
Chromium	0.42		0.17		
Lead	0.15		0.13		
Nickel	1.41		1.0		
7inc	1 33		0.56		

(2) In cases where POTWs find it necessary to impose mass effluent pretreatment standards the following equivalent mass standards are provided:

	PSES				
		Maximum for monthly			
	Maximum fo	or any 1 day	aver	rage	
Pollutant or					
pollutant	Metal	Coating	Metal	Coating	
property	preparation	operation	preparation	operation	
	Metric un	its-mg/m ² of a	rea processed	or coated	
Chromium	16.82	0.53	6.81	0.22	
Lead	6.01	0.19	5.21	0.16	
Nickel	56.5	1.78	40.1	1.26	
Zinc	53.3	1.68	22.5	0.71	
	English uni	ts-pounds per	1 million ft ² o	f area pro-	
	cessed or coated				
Chromium	3.45	0.11	1.4	0.05	
Lead	1.23	0.04	1.07	0.03	
Nickel	11.6	0.37	8.2	0.26	
Zinc	10.9	0.35	4.6	0.15	

History: Cr. Register, October, 1986, No. 370, eff. 11-1-86.

NR 262.15 Pretreatment standards for new sources. Except as provided in 40 CFR 403.7 and 403.13, any new source subject to this subcategory which introduces pollutants into a publicly owned treatment works shall comply with 40 CFR Part 403 and achieve the following pretreatment standards for new sources:

		PS	NS		
			Maximum f	for monthly	
	Maximum f	or any 1 day	aver	rage	
Pollutant or					
pollutant	Metal	Coating	Metal	Coating	
property	preparation	operation	preparation	operation	
	Metric u	nits-mg/2of ar	ea processed of	or coated	
Chromium	3.7	0.47	1.5	0.19	
Lead	1.0	0.13	0.9	0.11	
Nickel	12.0	1.51	6.3	0.79	
Zinc	10.2	1.29	4.2	0.53	
	English units-pounds per 1 million ft ² of area				
	processed or coated				
Chromium	0.76	0.1	0.31	0.04	
Lead	0.2	0.03	0.19	0.02	
Nickel	2.46	0.31	1.29	0.16	
7inc	2.09	0.27	0.86	0.11	

History: Cr. Register, October, 1986, No. 370, eff. 11-1-86.

NR 262.20 Applicability; description of the cast iron basis material subcategory. This subcategory applies to discharges to waters of the state and introductions of pollutants into publicly owned treatment works from porcelain enameling of cast iron basis materials.

History: Cr. Register, October, 1986, No. 370, eff. 11-1-86.

- NR 262.21 Effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available. Except as provided in 40 CFR 125.30 to 125.32, any existing point source subject to this subcategory shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available:
- (1) There may not be discharge of process wastewater pollutants from metal preparation operations.
- **(2)** The discharge of process wastewater pollutants from all porcelain enameling coating operations may not exceed the values set forth below:

	BPT effluent limitations				
Pollutant or	Maximum	for any 1	Maximum for		
pollutant property	da	y	monthly	average	
	mg/m ² (Pounds per million ft ²) of area coated				
Chromium	0.29	(0.06)	0.12	(0.024)	
Lead	0.11	(0.02)	0.09	(0.02)	
Nickel	0.98	(0.02)	0.7	(0.15)	
Zinc	0.93	(0.19)	0.39	(0.08)	
Aluminum	3.16	(0.65)	1.29	(0.27)	
Iron	0.86	(0.18)	0.44	(0.09)	
Oil and grease	13.86	(2.48)	8.32	(1.71)	
TSS	28.42	(5.82)	13.86	(2.84)	
pH	(1)	(1)	(1)	(1)	

Within the range 7.5 to 10.0.

History: Cr. Register, October, 1986, No. 370, eff. 11-1-86.

NR 262.22 Effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable. Except as provided in 40 CFR 125.30 to 125.32, any existing point source subject to this subcategory shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable:

- (1) There may not be discharge of process wastewater pollutants from metal preparation operations.
- **(2)** The discharge of process wastewater pollutants from all porcelain enameling coating operations may not exceed the values set forth below:

	BAT effluent limitations				
Pollutant or pollutant property	Maximum for any 1 Maximum for day monthly average				
	mg/m ² (Pounds per million ft ²) of area coated				
Chromium	0.53	(0.11)	0.22	(0.05)	
Lead	0.19	(0.04)	0.16	(0.03)	
Nickel	1.78	(0.37)	1.26	(0.26)	
Zinc	1.68	(0.35)	0.71	(0.15)	
Aluminum	5.74	(1.18)	2.35	(0.48)	
Iron	1.55	(0.32)	0.79	(0.16)	

History: Cr. Register, October, 1986, No. 370, eff. 11-1-86.

NR 262.23 New source performance standards. Any new source subject to this subcategory shall achieve the following new source performance standards:

- (1) There may not be discharge of process wastewater pollutants from metal preparation operations.
- **(2)** The discharge of process wastewater pollutants from all porcelain enameling coating operations may not exceed the values set forth below:

	NSPS				
Pollutant or pollutant property	Maximum for any 1 Maximum for day monthly average				
	mg/m ² (Pounds per million ft ²) of area coated				
Chromium	0.47	(0.1)	0.19	(0.04)	
Lead	0.13	(0.03)	0.11	(0.02)	
Nickel	0.69	(0.14)	0.47	(0.1)	
Zinc	1.29	(0.27)	0.53	(0.11)	
Aluminum	3.82	(0.78)	1.56	(0.32)	
Iron	1.55	(0.32)	0.79	(0.16)	
Oil and grease	12.6	(2.58)	12.6	(2.58)	
TSS	18.91	(3.87)	15.12	(3.1)	
Ha	(1)	(1)	(1)	(1)	

¹Within the range 7.5 to 10.0.

History: Cr. Register, October, 1986, No. 370, eff. 11-1-86.

NR 262.24 Pretreatment standards for existing sources. (1) Except as provided in 40 CFR 403.7 and 403.13, any existing source subject to this subcategory which introduces pollutants into a publicly owned treatment works shall comply with 40 CFR Part 403 and achieve the following pretreatment standards for existing sources:

- (a) There may not be discharge of process wastewater pollutants from metal preparation operations.
- (b) The discharge of process wastewater pollutants from all porcelain enameling coating operations may not exceed the values set forth below:

	PSES				
Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average			
	Milligrams per liter (mg/l)				
Chromium	0.42	0.17			
Lead	0.15	0.13			
Nickel	1.41	1.0			
Zinc	1.33	0.56			

- (2) In cases where POTWs find it necessary to impose mass pretreatment standards the following equivalent mass standards are provided:
- (a) There may not be discharge of process wastewater pollutants from metal preparation operations.
- (b) The discharge of process wastewater pollutants from all porcelain enameling coating operations may not exceed the values set forth below:

	PSES				
Pollutant or	Maximu	m for any	Maxin	num for	
pollutant property	1	day	monthly	average	
	mg/m2 (Pounds per million ft2) of area coated				
Chromium	0.53	(0.11)	0.22	(0.05)	
Lead	0.19	(0.04)	0.16	(0.03)	
Nickel	1.78	0.37	1.26	(0.26)	
Zinc	1.68	(0.35)	0.71	(0.15)	

History: Cr. Register, October, 1986, No. 370, eff. 11-1-86.

NR 262.25 Pretreatment standards for new sources. Except as provided in 40 CFR 403.7, any new source subject to this subcategory which introduces pollutants into a publicly owned treatment works shall comply with 40 CFR Part 403 and achieve the following pretreatment standards for new sources.

- (1) There may not be discharge of process wastewater pollutants from metal preparation operations.
- (2) The discharge of process wastewater pollutants from all porcelain enameling coating operations may not exceed the values set forth below:

	PSNS			
Pollutant or	Maximum for any		Maxim	
pollutant property _	1 day		monthly average	
	mg/m ² (Pounds per million ft ²) of area coated			ea coated
Chromium	0.47	(0.1)	0.19	(0.04)
Lead	0.13	(0.03)	0.11	(0.02)
Nickel	0.69	(0.14)	0.47	(0.1)
Zinc	1.29	(0.27)	0.53	(0.11)

History: Cr. Register, October, 1986, No. 370, eff. 11-1-86.

NR 262.30 Applicability; description of the aluminum basis material subcategory. This subcategory applies to discharges to waters of the state and introductions of pollutants into publicly owned treatment works from porcelain enameling of aluminum basis materials.

History: Cr. Register, October, 1986, No. 370, eff. 11-1-86.

NR 262.31 Effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available. Except as provided in 40 CFR 125.30 to 125.32, any existing point source subject to this subcategory shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable:

	BPT effluent limitations			
	Maximum for mont Maximum for any 1 day average			
Dollatont on	- Wiaxiiiiuiii i	of ally I day	avei	age
Pollutant or pollutant	Metal	Coating	Metal	Coating
property	preparation	operation	preparation	operation
property			area processed	
Chromium	16.34	6.32	6.63	2.56
Lead	5.84	2.26	5.06	1.96
Nickel	54.85	21.21	38.9	15.04
Zinc	51.73	20.01	21.79	8.43
Aluminum	176.98	68.44	72.35	27.98
Iron	47.85	18.5	24.51	9.48
Oil and grease				
	777.92	300.84	466.76	108.5
TSS	1594.74	616.68	777.92	300.82
pH	(1)	(1)	(1)	(1)
	English units-pounds per 1 million ft ² of area			
	processed or coated			
Chromium	3.35	1.3	1.37	0.53
Lead	1.2	0.47	1.04	0.4
Nickel	11.24	4.35	7.97	3.08
Zinc	10.6	4.1	4.46	1.73
Aluminum	36.25	14.02	14.82	5.73
Iron	9.8	3.79	5.02	1.94
Oil and grease				
	159.33	61.61	95.6	36.97
TSS	326.62	126.33	159.33	61.61
pH	(1)	(1)	(1)	(1)

¹Within the range 7.5 to 10.0.

History: Cr. Register, October, 1986, No. 370, eff. 11-1-86.

NR 262.32 Effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable. Except as provided in 40 CFR 125.30 to 125.32, any existing point source subject to this subcategory shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.

DEPARTMENT OF NATURAL RESOURCES

1.26

0.48

0.16

Pollutant or pollutant

Chromium....

Lead......

Nickel

Aluminum....

Iron....

property

Metal

16.34

5.84

54.85

BAT effluent limitations Maximum for any Maximum for monthly average 1 day Coating Metal Coating preparation preparation operation property Metric units-mg/m² of area processed or coated 0.53 6.62 0.22 0.19 5.06 0.16

38.9

14.82

5.02

51.74 1.68 21.79 1.71 Zinc.... Aluminum.... 176.98 5.74 72.35 2.35 47.85 1.55 24.51 0.8 Iron.... English units-pounds per 1 million ft² of area processed or coated 1.36 Chromium.... 0.05 0.11 Lead...... 1.2 0.04 1.04 0.03 Nickel 11.24 0.37 7.97 0.26 Zinc..... 10.6 0.35 4.46 0.35

1.18

0.32

1.78

History: Cr. Register, October, 1986, No. 370, eff. 11-1-86.

36.25

9.8

NR 262.33 New source performance standards. Any new source subject to this subcategory shall achieve the following new source performance standards:

	NSPS			
	Maximum for any		Maximu	m for
_	1 da	ıy	monthly average	
Pollutant or				
pollutant	Metal	Coating	Metal	Coating
property	preparation	operation	preparation	operation
	Metric unit	ts-mg/m²of a	rea processed o	r coated
Chromium	3.6	0.47	1.46	0.19
Lead	0.97	0.13	0.88	0.11
Nickel	5.35	0.69	3.6	0.47
Zinc	9.92	1.29	4.09	0.53
Aluminum	29.46	3.82	12.06	1.56
Iron	11.96	1.55	6.13	0.79
Oil and grease	97.24	12.6	97.24	12.6
TSS	145.86	18.91	116.69	15.12
pH	(1)	(1)	(1)	(1)
•	English units-pounds per 1 million ft ² of area			
	processed or coated			
Chromium	0.74	0.1	0.3	0.04
Lead	0.2	0.03	0.18	0.2
Nickel	1.1	0.14	0.74	0.1
Zinc	2.03	0.27	0.84	0.11
Aluminum	6.03	0.78	2.47	0.32
Iron	2.45	0.32	1.26	0.16
Oil and grease	19.92	2.58	19.92	2.58
TSS	29.88	3.87	23.9	3.1
pH	(1)	(1)	(1)	(1)
Within the range 7.5 to 10.0.				

History: Cr. Register, October, 1986, No. 370, eff. 11-1-86.

NR 262.34 Pretreatment standards for existing **sources.** (1) Except as provided in 40 CFR 403.7 and 403.13, any existing source subject to this subcategory which introduces pollutants into a publicly owned treatment works shall comply with 40 CFR Part 403 and achieve the following pretreatment standards for existing sources:

	PSES		
Pollutant or pollutant	Maximum for any 1	Maximum for	
property	day monthly ave		
	Milligrams per liter (mg/1)		
Chromium	0.42	0.17	
Lead	0.15	0.13	
Nickel	1.41	1.0	
Zinc	1.33	0.56	

(2) In cases where POTWs find it necessary to impose mass pretreatment standards the following equivalent mass standards are provided:

	PSES			
	Maximum for any 1 day		Maxim monthly	um for average
Pollutant or pollutant property	Metal preparation	Coating operation	Metal preparation	Coating operation
	Metric un	its-mg/m ² of	area processed	or coated
Chromium	16.34	0.53	6.62	0.22
Lead	5.84	0.19	5.06	0.16
Nickel	54.85	1.78	38.9	1.26
Zinc	51.74	1.68	21.79	1.71
	English units-pounds per 1 million ft ² of area			
	processed or coated			
Chromium	3.35	0.11	1.36	0.05
Lead	1.2	0.04	1.04	0.03
Nickel	11.24	0.37	7.97	0.25
Zinc	10.6	0.35	4.46	0.35

History: Cr. Register, October, 1986, No. 370, eff. 11-1-86.

NR 262.35 Pretreatment standards for new sources. Except as provided in 40 CFR 403.7, any new source subject to this subcategory which introduces pollutants into a publicly owned treatment works shall comply with 40 CFR Part 403 and achieve the following pretreatment standards for new sources:

	PSNS			
	Maximum for any		Maximum for	
	1 d	lay	monthly	average
Pollutant or				
pollutant	Metal	Coating	Metal	Coating
property	preparation	operation	preparation	operation
	Metric un	its-mg/m ² of	area processed	or coated
Chromium	3.6	0.47	1.46	0.19
Lead	0.97	0.13	0.88	0.11
Nickel	5.35	0.69	3.6	0.47
Zinc	9.92	1.29	4.09	0.53
	English units-pounds per 1 million ft ² of area pro-			
	cessed or coated			
Chromium	0.74	0.1	0.3	0.04
Lead	0.2	0.03	0.18	0.02
Nickel	1.1	0.14	0.74	0.1
Zinc	2.03	0.27	0.84	0.11

History: Cr. Register, October, 1986, No. 370, eff. 11-1-86.

NR 262.40 Applicability; description of the copper basis material subcategory. This subcategory applies to discharges to waters of the state and introductions of pollutants into publicly owned treatment works from porcelain enameling of copper basis materials.

History: Cr. Register, October, 1986, No. 370, eff. 11-1-86.

NR 262.43 New source performance standards. Any new source subject to this subcategory shall achieve the following new source performance standards:

	NSPS			
	Maximum for monthly			
	Maximum f	or any 1 day	average	
Pollutant or				
pollutant	Metal	Coating	Metal	Coating
property	preparation	operation	preparation	operation
	Metric un	its-mg/m ² of a	area processed	or coated
Chromium	6.23	0.46	2.52	0.19
Lead	1.69	0.13	1.52	0.11
Nickel	9.25	0.69	6.23	0.47
Zinc	17.16	1.29	7.07	0.53
Aluminum	50.97	3.82	20.86	1.56
Iron	20.69	1.55	10.6	0.79
Oil and grease	168.23	12.6	168.23	12.6
TSS	252.35	18.91	201.88	15.12
pH	(1)	(1)	(1)	(1)
	English units-pounds per 1 million ft ² of area pro-			
		cessed o	or coated	
Chromium	1.28	0.1	0.52	0.04
Lead	0.35	0.03	0.31	0.03
Nickel	1.9	0.14	1.28	0.1
Zinc	3.52	0.27	1.45	0.11
Aluminum	10.44	0.78	4.27	0.32
Iron	4.24	0.32	2.17	0.16
Oil and grease	34.46	2.58	34.46	2.58
TSS	51.69	3.87	41.35	3.1
pH	(1)	(1)	(1)	(1)

Within the range 7.5 to 10.0.

History: Cr. Register, October, 1986, No. 370, eff. 11-1-86.

NR 262.45 Pretreatment standards for new sources. Any new source subject to this subcategory which introduces pollutants into a publicly owned treatment works shall

comply with 40 CFR Part 403 and achieve the following pretreatment standards for new sources:

	PSNS			
	Maximum for monthly			
	Maximum f	or any 1 day	avei	age
Pollutant or				
pollutant	Metal	Coating	Metal	Coating
property	preparation		preparation	
	Metric un	its-mg/m² of a	area processed	or coated
Chromium	6.23	0.46	2.52	0.19
Lead	1.69	0.13	1.52	0.11
Nickel	9.25	0.69	6.23	0.47
Zinc	17.16	1.29	7.07	0.53
	English units-pounds per 1 million ft ² of area pro-			
	cessed or coated			
Chromium	1.28	0.1	0.52	0.04
Lead	0.35	0.03	0.31	0.02
Nickel	1.9	0.14	1.28	0.1
Zinc	3.52	0.27	1.45	0.11

History: Cr. Register, October, 1986, No. 370, eff. 11-1-86.

NR 262.50 Cross-references. The federal citations in this chapter correspond to provisions of the Wisconsin Administrative Code and Wisconsin Statutes. The federal citations may be cross-referenced in the following table:

CODE OF FEDERAL REGULATIONS	CORRESPONDING STATE
	CODE SECTION
40 CFR Part 466	ch. NR 262
40 CFR 125.30 to 125.32	s. NR 211.14, s. 283.13 (3),
	Stats.
40 CFR Part 401	chs. NR 205, 215, 219
40 CFR Part 403	chs. NR 211, 217
40 CFR 403.7	s. NR 211.13
40 CFR 403.13	s. NR 211.14

History: Cr. Register, October, 1986, No. 370, eff. 11-1-86.