

Chapter NR 538

APPENDIX

Table 1

Initial Certification and Recertification
Water Leach Test
ASTM D3987-12

| Numerical Standard (mg/L) | | Parameter | Foundry System Sand | Coal Ash | FGD Gypsum | Other |
|---------------------------|----------------|--------------------------|---------------------|----------|------------|-------|
| A ¹ | B ² | | | | | |
| 0.006 | 0.03 | Antimony | X | X | X | X |
| 0.01 | 0.05 | Arsenic | X | X | X | X |
| 2 | 10 | Barium | | X | | X |
| 0.004 | 0.02 | Beryllium | X | X | | X |
| 2 | 10 | Boron | | X | X | X |
| 0.005 | 0.025 | Cadmium | X | X | | X |
| 250 | 1250 | Chloride | | X | | X |
| 0.1 | 0.5 | Chromium, Total | X | X | | X |
| 0.04 | 0.2 | Cobalt | X | X | | X |
| 1.3 | 6.5 | Copper | X | | | X |
| 4 | 20 | Fluoride | | X | X | X |
| 0.015 | 0.075 | Lead | X | X | | X |
| 0.3 | 1.5 | Manganese | | | X | X |
| 0.002 | 0.01 | Mercury | | X | X | X |
| 0.04 | 0.2 | Molybdenum | | X | | X |
| 0.1 | 0.5 | Nickel | X | | | X |
| 10 | 50 | Nitrite + Nitrate (as N) | | | | X |
| 2 | 10 | Phenol | X | | | X |
| 0.05 | 0.25 | Selenium | | X | X | X |
| 250 | 1250 | Sulfate | | X | | X |
| 0.002 | 0.01 | Thallium | | X | X | X |
| 0.375 | 0.75 | Vanadium | | | | X |
| 25 | 125 | Zinc | | | | X |

Notes:

1 - Column A –Industrial byproducts that have concentrations below these standards may be used as geotechnical fill no less than 3 feet from the water table at the time of placement in accordance with s. NR 538.12 (2) (b), or no less than 5 feet from the water table when used for nonmetallic mine reclamation under s. NR 538.10 (2) (f). Standards are based on the enforcement exceedance values in s. NR 140.10 or recommended standard updates from the Wisconsin department of health services.

2 - Column B –Industrial byproducts that have concentrations above Column A but below Column B may be used as geotechnical fill no less than 5 feet from the water table at the time of placement in accordance with s. NR 538.12 (2) (c). Standards are based on 5 times the enforcement exceedance values in s. NR 140.10.

Table 2
Initial Certification and Recertification
Bulk Analysis

| Numerical Standard (mg/kg) | Parameter | Foundry System Sand | Coal Ash | FGD Gypsum | Other |
|----------------------------|-----------------------|---------------------|----------|------------|-------|
| 97.3 | Antimony | X | X | X | X |
| 8 | Arsenic | X | X | X | X |
| 8600 | Barium | | X | | X |
| 122 | Beryllium | X | X | X | X |
| 43600 | Boron | | X | | X |
| 104 | Cadmium | X | X | | X |
| 1.9 | Chromium, Hexavalent | X | X | X | X |
| 35.2 | Cobalt | X | | | X |
| 52 | Lead | X | X | | X |
| 13.7 | Mercury | | X | X | X |
| 1220 | Molybdenum | | X | | X |
| 264 | Nickel | X | | | X |
| 1210 | Selenium | | X | X | X |
| 2.4 | Thallium | | X | X | X |
| 773 | Vanadium | | X | | X |
| 73000 | Zinc | | | | X |
| 19.9 | Benz(a)anthracene | X | | | X |
| 2.0 | Benzo(a)pyrene | X | | | X |
| 20 | Benzo(b)fluoranthene | X | | | X |
| 200 | Benzo(k)fluoranthene | X | | | X |
| 2000 | Chrysene | X | | | X |
| 2 | Dibenzo(ah)anthracene | X | | | X |
| 20 | Indeno(123-cd)pyrene | X | | | X |
| 75.8 | 1-methyl naphthalene | X | | | X |
| 628 | 2-methylnaphthalene | X | | | X |
| 25.1 | Naphthalene | X | | | X |
| 4710 | Pyrene | X | | | X |

Notes:

Standards are based on Wisconsin department of health services potential ingestion and inhalation exposure modelling results.

Table 3
FGD Byproduct for Soil or Plant Additive Standards
Total Elemental Analysis

| Parameter | Numerical Standard (mg/kg) |
|------------------|-------------------------------|
| Antimony | 1.5 |
| Arsenic | 13.1 |
| Barium | 1000 |
| Beryllium | 2.5 |
| Boron | 200 |
| Cadmium | 1.0 |
| Chromium (Total) | 100 |
| Copper | 95 |
| Lead | 52 |
| Manganese | 2937 |
| Mercury | 3.13 |
| Molybdenum | 10 |
| Nickel | 100 |
| Selenium | 50 |
| Thallium | 1.0 |
| Vanadium | 136 |
| Zinc | 150 |

Notes:

Values are derived from the NRCS Conservation Practice Standard Code 333, “Amending Soil Properties With Gypsum Products,” June, 2015, screening values or ch. NR 720 Background Threshold Values for lead, manganese and zinc which have background values exceeding the NRCS screening values. Mercury values are based on the ch. NR 720 Direct Contact Remedial Concentration Limits (RCLs).

Table 4

| Beneficial Use Methods | | Must contain less than the concentration specified for the parameters in the following Appendix Tables: | | |
|------------------------|---|---|-----|-----|
| NR 538.10 | | 1 ^{3,4} | 2 | 3 |
| (1) | Contained or Converted Uses (a) Encapsulated uses (b) Waste stabilization or solidification (c) Supplemental fuels (d) Daily cover | --- | --- | --- |
| (2) | Geotechnical Fill (a) Building sub-base (b) Paved lot sub-base (c) Soil/gravel cover (d) Feed and manure storage structures (e) Transportation embankments (f) Non-metallic mine reclamation ² | X | --- | --- |
| (3) | Construction Uses (a) Paved roadway base course (b) Base aggregates (c) Utility trench backfill (d) Tank, vault or tunnel abandonment (e) Slabjacking material (f) Soil and pavement base stabilization for structural improvements (g) Flowable fill for structural improvements (h) Bonded surface course | X | --- | --- |
| (4) | Unconfined uses (a) Unbonded Surface Course (b) Winter road abrasives (c) Manufactured soil | X | X | --- |
| (5) | Soil or Plant Additives (a) Flue gas desulphurization material (b) Agricultural liming agents ¹ | --- | --- | X |

Notes:

1 – Byproducts intended for use as agricultural liming agents must contain concentrations less than the values listed in s. NR 204.07 (5) (c).

2 – Byproducts intended for use as part of a nonmetallic mine reclamation project must either be designated as “select foundry sand” by the department under s. NR 538.06 (3) (f) or contain concentrations less than the values listed in Appendix, Table 1, Column A.

3 – Table 1 contains numeric standards under Column A and Column B. The standards under Column B determine the eligible uses under s. NR 538.08 and the standards under Column A determine the separation to groundwater for geotechnical fill uses under s. NR 538.10(2).

4 - Select foundry sand must contain less than the concentration specified for the parameters in Table 1, Column B as required under s. NR 538.03(12m).