Chapter Ind 4

ELEVATOR CODE

	4.01	Purpose (p. 1)	Ind 4.39	Loca
	4.02	Scope (p. 2)	T	15)
Ind	4.03	Installations and alterations (p. 3)	Ind 4.40	Priva 16)
Ind	4.04	Petition for variance (p. 3)	Ind 4.41	Hand
Ind	4.05	Enforcement (p. 4)		16)
	4.06	Plan examination and approval	Ind 4,42	Hois
		(p. 4)		and t
Ind	4.07	Tests and inspections (p. 5)	Ind 4.43	Driv
	4.08	Certificate of operation (p. 6)	Ind 4.44	Han
	4.09	Certification of inspectors (p. 7)	Ind 4.45	Prot
	4.10	Plan approvals by certified in-	Ind 4.46	Addi
	4,10	spectors (p. 7)	1 1110	inspe
Ind	4.11	Inspections by certified inspec-		tors
ina	4.11	tors (p. 7)	Ind 4.47	Test
Ind	4.20	Adoption of standards by refer-	ind mit	insta
1 mu	4.40	ence (p. 7)	Ind 4.48	Test
Ind	4.21	Changes, additions or omissions	Ind 4.49	Hyd
ma	3.441	to ANSI/ASME A17.1-1981 (p.	Ind Into	inspe
		8)	Ind 4.50	Insp
Ind	4.22	Introduction (p. 8)	1110 3100	tors
	4.23		Ind 4.51	Inst
	4.24	Definitions (p. 8) Construction of hoistways and	1110 4.01	vice
1110	4.24		Ind 4.52	Mai
End	4.25	hoistway enclosures (p. 8) Machine rooms and machinery	Ind 4.53	Maj
mu	4.40		Ind 4.54	Incr
Ind	4,26	spaces (p. 9) Installation of pipes or ducts con-	1110 4.04	chan
mu	4,40	veying gases, vapors or liquids in		mael
		any hoistway, machine room or	Ind 4.55	Cha
		machinery space (p. 9)	1110 4.00	cont
Ind	4.27	Guarding of exposed equipment	Ind 4.56	Add
ma	4.21	(p. 10)	1110 4100	eme
Ind	4.28	Pits (p. 10)		19)
	4.29	Bottom and top clearances and	Ind 4.57	Rep
inu	4.00	runbys for elevator cars and	1110 1.01	dam
		counterweights (p. 10)		(p, 1
Ind	4.30	Hoistway-door locking devices,	Ind 4.58	Lim
Ind	3.00	car door or gate electric contacts,	1110 1100	plat
		hoistway access switches, and el-	Ind 4.59	Тур
		evator parking devices (p. 11)	Ind 4.60	Priv
Ind	4,31	Passenger-car enclosures (p. 12)	1110 1100	20)
	4.32	Car and counterweight safeties	Ind 4.61	Acce
		(p. 12)		evat
Ind	4.33	Speed governors (p. 13)	Ind 4.70	Scor
	4.34	Operating devices and control	Ind 4.71	Gen
1110	1,01	equipment (p. 13)	Ind 4.72	Spec
Ind	4.35	Emergency operation and signal	114 111-	whe
	1100	devices (p. 14)	Ind 4.73	Spec
Ind	4.36	Splicing and replacement of sus-		whe
		pension ropes (p. 15)	Ind 4.74	Sper
Ind	4.37	Hoistways, hoistway enclosures		way
		and related construction (p. 15)		
Ind	4.38	Collection of oil leakage (p. 15)		

ĺ

j

tion of stopping switches (p.

۱.,

- ate residence elevators (p.
- d and power dumbwaiters (p.

- stways, hoistway enclosures related construction (p. 16) ring-machine brakes (p. 17) d dumbwaiters (p. 17) tection required (p. 17) litional acceptance tests and ection for hydraulic eleva-(p. 17) is and inspections of existing allations (p. 17)
- (p. r), s and inspections of existing allations (p. 17) is of safeties (p. 17) iraulic elevators, additional ections and tests (p. 18) sections and tests of escala-and moving walks (p. 18) callations placed out of ser-

- allations placed out of ser-(p. 18) ntenance (p. 18) or alterations (p. 18) ease or decrease in travel and rage in location of the driving hine (p. 19) nge in type of operation or irol (p. 19) lition of emergency recall and received.

 - gency in-car operation (p.
 - airs and replacements of aged, broken or worn parts 9)
 - itation of load, speed and
 - form area (p. 19) es of driving machines (p. 19) ato residence inclined lifts (p.
 - essibility requirements for el-tors (p. 20) pe (p. 22) teral requirements (p. 22) cela requirements for vertical selehair lifts (p. 25) cela requirements for inclined selehair lifts (p. 26) cela requirements for stair-y chair lifts (p. 27)

Note: Chapter Ind 4 as it existed on January 31, 1983 was repealed and a new chapter Ind 4 was created effective February 1, 1983.

PURPOSE AND SCOPE

Ind 4.01 Purpose. The purpose of this chapter is to protect the health, safety and welfare of the public and employes by establishing minimum standards for the design, construction, installation, operation, inspec-Register, November, 1984, No. 347

WISCONSIN ADMINISTRATIVE CODE

ind 4

 $\mathbf{2}$

tion, testing, maintenance, alteration and repair of machines and mechanical devices installed in all public buildings and places of employment.

History: Cr. Register, January, 1983, No. 325, eff. 2-1-83.

Ind 4.02 Scope. (1) SPECIFIED EQUIPMENT. This chapter shall apply to the following equipment installed in public buildings and places of employment:

(a) Elevators;

(b) Power dumbwaiters;

(c) Escalators;

(d) Moving walks;

(e) Stage and orchestra lifts;

(f) Material lifts and dumbwaiters with automatic transfer devices;

(g) Special purpose personnel elevators;

(h) Lifts for the physically disabled.

(2) EXEMPTED EQUIPMENT. This chapter shall not apply to the following equipment:

(a) Conveyors complying with ANSI B20.1;

(b) Tiering or piling machines used to move material to and from storage, and located and operated entirely within one story;

(c) Equipment for feeding or positioning materials at machine tools, printing presses and similar types of equipment;

(d) Hoists for raising or lowering materials and which are provided with unguided hooks, slings and similar means for attachment to the materials;

(e) Skip or furnace hoists;

(f) Wharf ramps;

(g) Amusement devices, except equipment specified in sub. (1);

(h) Stage curtain hoists:

(i) Lift bridges;

(j) Railroad car lifts or dumpers;

(k) Mechanical lifts serving only the floor level on which the lift is located and used only for the transfer of material or equipment;

(1) Mechanized parking garage equipment and automotive hoists used only for maintenance or repair of motor vehicles; Register, November, 1984, No. 347

(m) Personnel hoists and belt manlifts covered by chs. Ind 1000-2000.

Note: Conveyors, personnel hoists and manlifts located in the private sector are covered by the Occupational Health and Safety Act. In the public sector this equipment is covered by chs. Ind 1000-2000, Wis. Adm. Code.

History: Cr. Register, January, 1983, No. 325, eff. 2-1-83.

INSTALLATIONS, ENFORCEMENT AND PETITION FOR MODIFICATION

Ind 4.03 Installations and alterations. (1) NEW INSTALLATIONS. Unless otherwise provided in this chapter, all new installations shall conform to the requirements of this chapter.

(2) EXISTING INSTALLATIONS. (a) Applicable code requirements. All existing installations shall conform to the applicable sections in this chapter and rules in effect on the contract date of the initial installation.

(b) Maintenance. All existing installations of equipment under the scope of this chapter shall comply with s. Ind 4.52.

(3) PROHIBITED INSTALLATIONS. (a) New and existing installations. 1. Belt or chain driven machines. Belt or chain driven machines shall not be used for any passenger elevator installation, except oil hydraulic elevators.

2. Friction gearing or clutch mechanism. Friction gearing or a clutch mechanism shall not be used to connect a driving-machine drum or sheave to the main driving gear of any elevator.

3. Continuous pressure operation. Continuous pressure button operation from the landings shall not be used for passenger elevators.

4. Drum type installations. Drum type freight elevator installations equipped with a mechanical brake shall not have hoistway limit switches, car door or gate electric contacts, hoistway landing door or gate electric contacts or any combination thereof.

5. Power attachments on hand-power elevators. Power attachments, such as worm reduction units, rope clutch or rope grip devices, belts to improvised rope wheels, or any similar device, shall not be installed on any hand elevator unless all requirements for power elevators are complied with.

(b) New installations. 1. Counterbalance elevators. Elevator cars shall not counterbalance each other.

2. Hand cable controls. Hand cable control power operated elevators and dumbwaiters are prohibited.

(4) ALTERATIONS, REPAIRS AND REPLACEMENTS. All alterations, repairs and replacements of parts shall comply with the applicable sections of this chapter.

History: Cr. Register, January, 1983, No. 325, eff. 2-1-83.

Ind 4.04 Petition for variance. The department shall consider and may grant a variance to an administrative rule upon receipt of a fee and a completed petition for variance form from the owner, provided an equivalent degree of safety is established in the petition for variance which meets the intent of the rule being petitioned. The department may

Register, November, 1984, No. 347

impose specific conditions in a petition for variance to promote the protection of the health, safety and welfare of the employes or the public. Violations of those conditions under which the petition variance is granted constitutes a violation of these rules.

History: Cr. Register, January, 1983, No. 325, eff. 2-1-83; am. Register, November, 1984, No. 347, eff. 12-1-84.

Ind 4.05 Enforcement. This chapter shall be used by the department, municipality and insurance inspectors certified by the department. The department shall have the responsibility for interpreting the rules, including those in the incorporated ANSI/ASME A17.1 code, and for the approval of equipment and material.

History: Cr. Register, January, 1983, No. 325, eff. 2-1-83.

PLAN APPROVALS AND INSPECTIONS

Ind 4.06 Plan examination and approval. (1) PLAN SUBMITTAL. Plans and specifications for all new installations and the following alterations shall be submitted to the department or municipality for examination and approval:

(a) Increase in rated load or speed;

(b) Increase in dead weight of car by 10% or more;

(c) Increase or decrease in travel;

(d) Change in classification from freight to passenger service;

(e) Addition of hoistway doors or gates; and

(f) Relocation of machine room.

(2) INFORMATION REQUIRED ON PLANS. At least 3 sets of plans, including specifications, shall be submitted by the manufacturer's representative or the distributor who furnishes the equipment. The plans shall include the following:

(a) A plan of car, hoistway and machine room showing all clearances, including all inside car dimensions specified in s. Ind 4.61 (4);

(b) A section through hoistway, pit and car showing all applicable dimensions. All landings shall be clearly shown, indicating types of hoistway doors or gates used;

(c) Working clearances around machine, controller and disconnecting means showing dimensions to adjacent or opposite walls and equipment, or both.

(d) The size and weight per foot of guiderails and details of their support, including reinforcement where required.

(3) APPLICATION FOR INSTALLATION OR REMODELING. Prior to commencing work, at least 2 completed copies of the department application form shall be submitted to the department for all new installations, alterations listed in sub. (1) (a) to (f) and the following alterations.

(a) Change in type of operation or control;

Register, November, 1984, No. 347

Ind 4