## Chapter RL 112

## EQUIPMENT

RL 112.01	Ring	RL 112.05	Dress
	Emergency equipment		Mouthpieces
RL 112.03		RL 112.07	
RL 112.04	Bandage specifications	RL 112.08	Corner equipment

RL 112.01 Ring. All exhibitions shall be conducted in a ring which meets the following requirements:

(1) The ring shall be a square of not less than 16 nor more than 20 feet on a side within the ropes. The apron of the ring floor shall extend at least 18 inches beyond the ropes. The ring may not be more than 4 feet above the floor of the building or grounds of an outdoor arena and shall have 3 sets of suitable steps for the use of boxers, coaches, and officials, one in each boxer's corner and one in a neutral corner or area for use by ringside physicians and referees.

(2) The ring shall be circumscribed with at least 3 ropes. Ropes may not be less than one inch in diameter. Ropes may not be made of metal. Ropes shall be wrapped securely with soft material. If 3 ropes are used, they shall extend in parallel 2, 3, and 4 feet above the ring floor. If 4 ropes are used, the lowest rope shall be 18 inches above the ring floor, If 4 ropes are used, the lowest rope shall be 18 inches, and the fourth rope 54 inches above the ring floor. The ring floor shall be padded with a one-inch layer of padding of felt, rubber or other similar material, placed on a one-inch base of building board or similar supporting base. Padding shall be covered with canvas, duck, or similar material tightly stretched and laced securely in place, preferably under the apron.

(3) Ring posts shall be at least 3 inches in diameter, extending from the floor to the height of 58 inches above the ring floor. Ropes shall be connected to posts with the extension not shorter than 18 inches. Turnbuckles shall be covered with a protective padding. Full-length vertical corner pads shall be secured in place.

History: Cr. Register, August, 1985, No. 356, eff, 9-1-85.

RL 112.02 Emergency equipment. The professional club holding the permit shall have oxygen equipment, airways of assorted sizes, and a stretcher available at ringside.

History: Cr. Register, August, 1985, No. 356, eff. 9-1-85.

RL 112.03 Gloves. Gloves approved by the inspector shall be worn by boxers in all bouts. After July 1, 1987, only thumbless gloves will be approved.

(1) Boxing gloves may be not less than 8 oz, each in weight.

(2) Gloves shall be whole, clean and in sanitary condition. Breaking, roughing or twisting of gloves is prohibited. No foreign substances may Register, August, 1985, No. 356

## 106 WISCONSIN ADMINISTRATIVE CODE RL 112

be applied to gloves except for wrapping around the wrist area to safely secure the laces.

History: Cr. Register, August, 1985, No. 356, eff. 9-1-85.

RL 112.04 Bandage specifications. (1) Boxers shall wear one 2-inch by 10 yard roll of cotton gauze on each hand during all bouts and exhibitions except as follows:

(a) The roll worn by boxers weighing more than 156 pounds may be longer than 10 yards, but may not exceed 12 yards.

(b) Boxers may use one training wrap type bandage on each hand not to exceed 6 feet 6 inches in length, held in place by a strip of one-inchadhesive tape not more than 8 inches in length around each wrist.

(2) No substance other than above prescribed may be used between the fingers or over the knuckles.

History: Cr. Register, August, 1985, No. 356, eff. 9-1-85.

**RL** 112.05 **Dress.** (1) Boxers shall box in proper dress including an approved foul-proof protection cup, trunks with a belt line below or at the waistline, shoes of soft material, without spikes, cleats or heels, and socks which may extend to within one inch below the knee.

(2) Boxers may not wear metal straps, buckles, necklaces, jewelry or other objects.

(3) Boxers may not use any type of grease or other substance on the body.

History: Cr. Register, August, 1985, No. 356, eff. 9-1-85.

RL 112.06 Mouthpieces. Boxers shall wear a fitted mouthpiece at the beginning of each round.

History: Cr. Register, August, 1985, No. 356, eff. 9-1-85.

RL 112.07 Headgear. Boxers may wear headgear. Headgear shall be approved by the inspector and meet substantially the following specifications:

(1) Headgear shall be adjustable to different head sizes.

(2) The total weight may not exceed 12 ounces.

(3) The outer casing of the headgear shall be constructed of tanned sheepskin of not less than 2, nor more than 3 ounces in weight.

(4) Padding at back of head, ears, and temple area shall consist of ¼-inch thickness of closed-cell padding.

(5) Padding for the area above the eyes shall consist of a combination padding of ¼-inch closed-cell padding and ¾-inch latex foam rubber cemented together.

(6) Padding for the ears shall consist of ½-inch flat foam rubber on the outside, fitted in a semi-circle.

(7) Lace tips or any exposed metal is prohibited. The buckle under the chin shall be thoroughly protected. Register, August, 1985, No. 356 (8) The inner casing of the headgear shall be lined with 2 % ounces of tanned unfinished sheepskin.

(9) All padding shall be cemented to the casing.

History: Cr. Register, August, 1985, No. 356, eff. 9-1-85.

RL 112.08 Corner equipment. (1) Every second working in a boxer's corner shall have the following equipment:

(a) First aid supplies.

(b) Clean towels.

(c) Sterile gauze pads, sterile cotton and cotton tipped swabs.

(d) Ice-filled bag.

(2) Seconds shall submit first aid kits and corner equipment to the ringside physician for inspection and approval before an exhibition.

History: Cr. Register, August, 1985, No. 356, eff. 9-1-85.

Register, August, 1985, No. 356